

**RoHS
Compliant**

Applications

Smart Communication Devices, PDA, Game equipment, Smart Factory, etc.

Features

- Plastic molded 32.768kHz SMD crystal unit of heat resistance
- High precision and reliability
- High reliable environmental performance
- Automatic mounting and reflow soldering








Specifications

Frequency Range	: 32.768 kHz
Frequency Tolerance	: +20ppm
Load Capacitance	: 9pF, 12.5pF, or specify
Operating Temperature Range	: -40°C to +85°C, or specify
Storage Temperature Range	: -55°C to +125°C
Drive Level	: 1μW Max.
Turnover Temperature	: ±25°C±5°C
Parabolic Coefficient	: $(-0.035 \pm 0.005) \times 10^{-6}/^{\circ}\text{C}^2$
Shunt Capacitance	: 0.8pF Typ.
Aging (at 25°C)	: +3ppm at first year

Fundamental

32.768kHz	: 65kΩ Max.
-----------	-------------

Dimensions



Dimensions : Millimetres

Part Number Table

Description	Part Number
Crystal, 32.768KHz, 12.5PF, 7mm × 1.5mm	MPJK-7M-32.768-12.5-20-65-C

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.