





**FIBERS** 

# LL3-LM36450 | LL3

**FIBERS** 



### Ordering information

Туре	Part no.
LL3-LM36450	2073492

Other models and accessories -> www.sick.com/LL3

Illustration may differ

#### Detailed technical data

Features	
Device type	Fibers, fiber suitable for WLL260
Functional principle	Proximity system
Functional principle detail	Consisting of a sender and a receiver
For fiber-optic sensor	GLL170(T), WLL180
Fiber length	450 mm
Fiber material	Glass
Jacket material	Polyvinylchlorid (PVC)
Fiber head material	Chrome-plated metal coil
Outer diameter, fiber-optic cable connec- tion	2.2 mm
Fiber-optic head design	Flat type, 90° deflection
Fiber arrangement	Multi-fiber – linear arrangement
Core structure	Multi-fiber – linear arrangement
Angle of dispersion < 60 °	No
Compatibility with infrared light (1,450 nm)	Yes <sup>1)</sup>
Highly flexible/elastic fibers (bend radius 1–4 mm)	No
Adapter end sleeves required	No
Angle of dispersion	60°
Integrated lens	No
Minimal object diameter	0.5 mm
Compatibility tip adapters	No

 $^{1)}\ensuremath{\,\text{Reduced}}\xspace$  sensing ranges possible when using a fiber-optic amplifier with infrared light.

#### Mechanics/electronics

Bend radius, fibre-optic cable	20 mm
Ambient operating temperature	-10 °C +60 °C
Classifications	
ECLASS 5.0	27270905
ECLASS 5.1.4	27270905
ECLASS 6.0	27270905
ECLASS 6.2	27270905

	0707000F
ECLASS 7.0	27270905
ECLASS 8.0	27270905
ECLASS 8.1	27270905
ECLASS 9.0	27270905
ECLASS 10.0	27270905
ECLASS 11.0	27270905
ECLASS 12.0	27270905
ETIM 5.0	EC002651
ETIM 6.0	EC002651
ETIM 7.0	EC002651
ETIM 8.0	EC002651
UNSPSC 16.0901	39121528

### Sensing ranges with WLL180T


Operating mode 16 µs	50 mm
Operating mode 70 µs	160 mm
Operating mode 250 µs	210 mm
Operating mode 2 ms	230 mm
Operating mode 8 ms	261 mm
Note	Sensing ranges related to fiber-optic sensors with type of light: visible red light

## Sensing ranges with GLL170

Operating mode 250 µs	70 mm
Sensing ranges with GLL170T	
Operating mode 50 µs	171 mm
Operating mode 250 µs	325 mm

#### Dimensional drawing (Dimensions in mm (inch))

LL3-LM36450



# SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

# WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com



Online data sheet

