



# SR102 THRU SR110

## 1.0 AMP. Schottky Barrier Rectifiers



Voltage Range  
20 to 100 Volts  
Current  
1.0 Ampere


### Features

- ✧ Low forward voltage drop
- ✧ High current capability
- ✧ High reliability
- ✧ High surge current capability

### Mechanical Data

- ✧ Cases: DO-41 molded plastic
- ✧ Epoxy: UL 94V-O rate flame retardant
- ✧ Lead: Axial leads, solderable per MIL-STD-202, Method 208 guaranteed
- ✧ Polarity: Color band denotes cathode end
- ✧ High temperature soldering guaranteed: 250°C/10 seconds/.375", (9.5mm) lead lengths at 5 lbs., (2.3kg) tension
- ✧ Weight: 0.33 gram

### DO-41



Dimensions in inches and (millimeters)

### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.  
Single phase, half wave, 60 Hz, resistive or inductive load.  
For capacitive load, derate current by 20%

Type Number	SR102	SR103	SR104	SR105	SR106	SR109	SR110	Units
Maximum Recurrent Peak Reverse Voltage	20	30	40	50	60	90	100	V
Maximum RMS Voltage	14	21	28	35	42	63	70	V
Maximum DC Blocking Voltage	20	30	40	50	60	90	100	V
Maximum Average Forward Rectified Current See Fig. 1	1.0							A
Peak Forward Surge Current, 8.3 ms Single Half Sine-wave Superimposed on Rated Load (JEDEC method)	40				30		A	
Maximum Instantaneous Forward Voltage @ 1.0A	0.55		0.70		0.80		V	
Maximum D.C. Reverse Current @ T <sub>A</sub> =25°C at Rated DC Blocking Voltage @ T <sub>A</sub> =100°C	0.5 10				0.05 -		mA mA	
Typical Thermal Resistance (Note 1) R <sub>θ</sub> JA	50							°C/W
Typical Junction Capacitance (Note 2)	110			80		28		pF
Operating Junction Temperature Range T <sub>J</sub>	- 65 to +125				-65 to +150			°C
Storage Temperature Range T <sub>STG</sub>	-65 to +150							°C

Notes: 1. Thermal Resistance from Junction to Ambient Vertical P.C. Board Mounting, 0.375"(9.5mm) Lead Length

2. Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

## RATINGS AND CHARACTERISTIC CURVES (SR102 THUR SR110)

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- TYPICAL FORWARD CHARACTERISTICS




FIG.3- TYPICAL REVERSE CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE




FIG.5- MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

