

Features

- Can be heat sealed
- Available in various formats
- Custom printing available
- Available in various gauges



Specifications

Colour	: Pink
External Height	: 355mm
External Width	: 254mm
Bag Type	: ESD
Charge Decay Time	: 2s
Enclosure Material	: Low Density Polyethylene
End To End Resistance	: 50MΩ
Surface Resistivity Max.	: 10,000MΩ/sq

Material Structure

The main carrier of this product is based on linear or low density polyethylene with an amine free additive system which differs from traditional amine containing antistats. It is recommended for all antistatic applications that currently use tertiary amines. The non-reactivity of this product makes it ideal for use within an electronics production environment.

Physical Properties

Tensile Strength Elongation Break

When measured according to BS2782, method 301E and Annex B of Defence Standard 93-13/Issue 1, At the tensile strength in both the longitudinal and transverse directions shall not be less than 12Mpa and the elongation break shall not be less than 250% in either direction. For open widths less than 150mm only the longitudinal properties can be measured.

Note: 1Pa = 1N/m²

Tear Resistance

When measured according to BS2782 method 308A and Annex C of DEF 93-13/1, the tear resistance of the material in both the longitudinal and transverse directions shall not be less than 50N/mm thickness.

Electrical Properties

Surface Resistivity (Inside/Outside)	: At 28.8°C abd 12% RH <1011Ω/sq
Static Decay Rate	: (5,000V at 28.8°C and 12% RH) <2 seconds

Part Number Table

Description	Part Number
Pink ESD Bag, Open, 10"×14", PK100	MP-001-0021

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.