

Y8A34A2-C2A8000XXX

Passive distribution boxes

PLUG CONNECTORS AND CABLES





Ordering information

Туре	Part no.
Y8A34A2-C2A8000XXX	2115733

Other models and accessories → www.sick.com/Passive_distribution_boxes



Detailed technical data

Technical specifications


Accessory group	Distributors
Accessory family	Junction boxes
Connection type head A	3-pin
Shielding	Unshielded
Reference voltage	
	≤ 24 V DC
Current loading	2 A
Authorizations	UL CE
UL File No.	E238799
Enclosure rating	IP65/ IP67
Items supplied	5 x labeling plates
Overvoltage category	III

Classifications

ECLASS 5.0	27279201
ECLASS 5.1.4	27279201
ECLASS 6.0	27279201
ECLASS 6.2	27279201
ECLASS 7.0	27279201
ECLASS 8.0	27279201
ECLASS 8.1	27279201
ECLASS 9.0	27440108
ECLASS 10.0	27440108
ECLASS 11.0	27440108
ECLASS 12.0	27440108
ETIM 5.0	EC002585
ETIM 6.0	EC002585
ETIM 7.0	EC002585


ETIM 8.0	EC002585
UNSPSC 16.0901	31163032

Dimensional drawing (Dimensions in mm (inch))



Connection diagram

Cd-480



Recommended accessories

Other models and accessories

www.sick.com/Passive_distribution_boxes

	Brief description	Туре	Part no.			
Device protection (mechanical)						
	1 piece, Protective cap for M8 socket or unused ports	DOS-08SK	5340762			
Plug connecto	Plug connectors and cables					
Coni Sign Cabl Desc Appl Coni Sign Cabl Desc Coni Sign Cabl Desc Appl Coni Coni Coni Coni Coni Coni Coni Coni	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 5 m, 8-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Application: Zones with oils and lubricants, Drag chain operation, Robot 	YF2A18- 050UA5XLEAX	2095653			
	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 10 m, 8-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Application: Zones with oils and lubricants, Drag chain operation, Robot 	YF2A18- 100UA5XLEAX	2095654			
	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 20 m, 8-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Application: Zones with oils and lubricants, Drag chain operation, Robot 	YF2A18- 200UA5XLEAX	2095680			
	 Connection type head A: Female connector, M12, 8-pin, straight, A-coded Connection type head B: Flying leads Signal type: Sensor/actuator cable Cable: 30 m, 8-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Application: Zones with oils and lubricants, Drag chain operation, Robot 	YF2A18- 300UA5XLEAX	2095681			
100	 Connection type head A: Female connector, M8, 3-pin, straight, A-coded Connection type head B: Male connector, M8, 3-pin, straight, A-coded Signal type: Sensor/actuator cable Cable: 5 m, 3-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Application: Zones with oils and lubricants, Drag chain operation, Robot 	YF8U13- 050UA1M8U13	2096308			

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

