

Productname : ZINC PRIMER
Ref.Nr.: UK10175-3-120109
Creationdate : 12.01.09
Replaces: 15.02.08

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname : ZINC PRIMER
Aerosol

Application : Anti Corrosion Products

Company : CRC Industries UK Ltd.
 Castlefield Industrial Estate, Wyllds Rd, Bridgwater,
 Somerset,
 UK, TA64DD
Tel.: (+44)(0)1278 727200
Fax: (+44)(0)1278 425644
E-mail : hse.uk@crcind.com

In case of emergency : (+44)(0)1278 727200

Subsidiaries		Tel	Fax
CRC Industries Europe	Touwslagerstraat 1 9240 Zele Belgium	(+32) (0) 52 / 45 60 11	(+32) (0) 52 / 45 00 34
CRC Industries Finland	Asemanrinne 13, 08500 Lohja AS	(+358)(0)19/32921	(+358)(0)19/383676
CRC Industries France	12, Bld des Martyrs de Chateaubriant F-95102 Argenteuil Cédex	(+33)(0)1/34112000	(+33)(0)1/34110996
CRC Industries Deutschland	Südring 9, 76473 Iffezheim	(+49)(0)7229/3030	(+49)(0)7229/303266
CRC Industries Iberia	Gremio del cuero S/N, 40195 Segovia	(+34)921/427546	(+34)921/436270
CRC Industries Sweden	Kryptongatan 14, 43153 Mölndal	(+46)(0)31/7068480	(+46)(0)31/273991

2. HAZARD IDENTIFICATION

Health and Safety : Extremely Flammable
(DME propellant)
Repeated exposure may cause skin dryness or cracking.
Vapours may cause drowsiness and dizziness.

Environment : Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Other hazards : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.

3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	203-539-1	1-5		R10	A
dimethyl ether	115-10-6	204-065-8	30-60	F+	12	A
xylene	1330-20-7	215-535-7	0-1	Xn	10-20/21-38	A



Productname : ZINC PRIMER
Ref.Nr.: UK10175-3-120109
Creationdate : 12.01.09
Replaces: 15.02.08

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
ethyl acetate	141-78-6	205-500-4	5-10	F,Xi	11-36-66-67	B
Naphtha (petroleum), hydrotreated light (benzene<0.1%)	64742-49-0	265-151-9	1-5	Xn	10-65-66-67	B,P
trizinc bis(orthophosphate)	7779-90-0	231-944-3	<2.5	N	50/53	
butanone; ethyl methyl ketone	78-93-3	201-159-0	5-10	F,Xi	11-36-66-67	A
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	96-29-7	202-496-6	<0.1	Xn	21-40-41-43	
Explanation notes						
A : substance with Community workplace exposure limit						
B : substance with national established workplace exposure limit						
P : not classified as carcinogen, less than 0.1% w/w benzene (Einecs-nr. 200-753-7)						

Remark: for substances with workplace exposure limits see point 8.

Note H and P of Annex I (67/548/EEC) apply for the naphtha's in this product.

(* Explanation risk-phrases : see chapter 16)

4. FIRST AID MEASURES

General Advice : If symptoms persist always call a doctor

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water for several minutes
Seek medical advice

Contact with skin : Wash with water and soap.

Inhalation : Fresh air, keep warm and at rest.
Seek medical attention if ill effects occur

Ingestion : Ingestion is unlikely to occur
If swallowed accidentally, do not induce vomiting and seek medical advice.

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): < 0 °C

Explosion limits : upper limit : not available

lower limit : not available

Extinguishing media : foam, carbon dioxide or dry agent

Fire-fighting procedures : Keep container(s) exposed to fire cool, by spraying with water

Unusual exposure hazard : Aerosols may explode if heated above 50°C
In case of fire, do not breathe fumes



Productname : ZINC PRIMER
Ref.Nr.: UK10175-3-120109
Creationdate : 12.01.09
Replaces: 15.02.08

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Shut off all ignition sources
 Ensure adequate ventilation

Environmental precautions : Do not allow to enter public sewers and watercourses

Cleaning methods : Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

Handling procedures : Use only in well ventilated areas
 Keep away from heat and sources of ignition
 Do not spray on a naked flame or incandescent material.
 Do not pierce or burn aerosols, even after use.
 Do not breathe aerosols or vapours.
 Avoid contact with skin and eyes.

Storage procedures : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
 Keep in a cool, dry, well ventilated place
 Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures : Ensure adequate ventilation
 Keep away from heat and sources of ignition
 Take precautionary measures against static discharges

Personal protection : It is advisable to take precautions to avoid contact with skin and eyes when handling the product.
 Use only in well ventilated areas

inhalation : In case of insufficient ventilation, wear suitable respiratory equipment.
 (Filter type AX)

hands and skin : Wear suitable protective gloves
 (butylrubber)

eyes : Wear safety goggles.

Exposure limits :

Hazardous ingredient	CAS-nr	method	
EU established exposure limits:			
1-methoxy-2-propanol; monopropylene glycol methyl ether	107-98-2	TWA	100 ppm
		STEL	150 ppm
dimethyl ether	115-10-6	TWA	1000 ppm
		STEL	100 ppm
xylene	1330-20-7	TWA	50 ppm
		STEL	100 ppm
butanone; ethyl methyl ketone	78-93-3	TWA	200 ppm
		STEL	300 ppm



Productname :	ZINC PRIMER	Creationdate :	12.01.09
Ref.Nr.:	UK10175-3-120109	Replaces:	15.02.08

Disposal should be in accordance with local, state or national legislation

14. TRANSPORT

UN-number :	1950
Road/Rail - ADR/RID :	UN1950 Aerosols Class : 2, PG : NA, Class code : 5F, Label : 2.1
Sea - IMDG :	UN1950 Aerosols Ltd Qty Class : 2.1, PG : NA, Label : 2.1
EmS	F-D,S-U
Air - IATA/ICAO :	UN1950 Aerosols, flammable Class : 2.1, PG : NA, Label : RFG
Packing instr. LQ	Y203
PAX	203
CAO	203

15. REGULATORY INFORMATION

Warning symbol(s) :	F+
Risk-phrase(s) :	R12: Extremely flammable. R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R66: Repeated exposure may cause skin dryness or cracking. R67: Vapours may cause drowsiness and dizziness.
Safety-phrase(s) :	S2: Keep out of the reach of children. S16: Keep away from sources of ignition - No smoking. S23: Do not breathe spray. S35: This material and its container must be disposed of in a safe way. S51: Use only in well-ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Without adequate ventilation formation of explosive mixtures may be possible.



Productname :	ZINC PRIMER	Creationdate :	12.01.09
Ref.Nr.:	UK10175-3-120109	Replaces:	15.02.08

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC.

***Explanation risk-phrases:**

R10: Flammable.
R11: Highly flammable.
R12: Extremely flammable.
R20/21: Harmful by inhalation and in contact with skin.
R36: Irritating to eyes.
R38: Irritating to skin.
R40: Limited evidence of a carcinogenic effect.
R41: Risk of serious damage to eyes.
R43: May cause sensitization by skin contact.
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

This Material Safety Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Material Safety Data Sheet will be sent to you upon simple request or can be found on our website : www.crcind.com. We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

