

**SERIES:** SWI10-N | **DESCRIPTION:** AC-DC POWER SUPPLY


**FEATURES**

- up to 12 W continuous power
- DoE Level VI efficiency
- universal input voltage range
- ultra-compact case
- no load power consumption < 0.075 W
- over voltage, over current, and short circuit protections
- UL/cUL, PSE, FCC safety approvals
- Class II construction


**MODEL**

| MODEL      | output voltage<br>(Vdc) | output current<br>max<br>(A) | output power<br>max<br>(W) | ripple and noise <sup>1</sup><br>max<br>(mVp-p) | efficiency level |
|------------|-------------------------|------------------------------|----------------------------|-------------------------------------------------|------------------|
| SWI10-5-N  | 5                       | 2                            | 10                         | 250                                             | VI               |
| SWI10-12-N | 12                      | 1                            | 12                         | 200                                             | VI               |

Notes: 1. At full load, 25°C, at 115/230 Vac input, 20 MHz bandwidth oscilloscope, output terminated with 0.1  $\mu$ F and 10  $\mu$ F capacitors.

**PART NUMBER KEY**


## INPUT

| parameter                 | conditions/description               | min | typ | max   | units |
|---------------------------|--------------------------------------|-----|-----|-------|-------|
| voltage                   |                                      | 90  |     | 264   | Vac   |
| frequency                 |                                      | 47  |     | 63    | Hz    |
| current                   | at nominal input voltage             |     |     | 0.5   | A     |
| leakage current           | at nominal input voltage & frequency |     |     | 0.25  | mA    |
| no load power consumption | at 115/230 Vac                       |     |     | 0.075 | W     |

## OUTPUT

| parameter     | conditions/description   | min | typ | max | units |
|---------------|--------------------------|-----|-----|-----|-------|
| regulation    |                          |     | ±5  |     | %     |
| start-up time | at nominal input voltage |     |     | 3   | s     |
| rise time     | at nominal input voltage |     |     | 100 | ms    |

## PROTECTIONS

| parameter                | conditions/description          | min | typ | max | units |
|--------------------------|---------------------------------|-----|-----|-----|-------|
| over voltage protection  | 5 Vdc output model              |     |     | 12  | Vdc   |
|                          | 12 Vdc output model             |     |     | 25  | Vdc   |
| over current protection  | output shut down, auto recovery |     |     | 4.5 | A     |
|                          | 5 Vdc output model              |     |     | 2.5 | A     |
|                          | 12 Vdc output model             |     |     |     | A     |
| short circuit protection |                                 |     |     |     |       |

## SAFETY & COMPLIANCE

| parameter         | conditions/description                                                 | min    | typ            | max | units      |
|-------------------|------------------------------------------------------------------------|--------|----------------|-----|------------|
| isolation voltage | input to output at 10 mA for 1 minute                                  |        | 3,000<br>4,242 |     | Vac<br>Vdc |
| safety approvals  | UL/cUL, PSE                                                            |        |                |     |            |
| EMI/EMC           | FCC Part 15B Class B                                                   |        |                |     |            |
| MTBF              | as per Telcordia SR-332 (Issue 2), at 115/230 Vac, full load, 0°C~40°C | 50,000 |                |     | hours      |
| RoHS              | 2011/65/EU                                                             |        |                |     |            |

## ENVIRONMENTAL


| parameter             | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature |                        | 0   |     | 40  | °C    |
| storage temperature   |                        | -20 |     | 70  | °C    |
| operating humidity    | non-condensing         | 20  |     | 85  | %     |
| storage humidity      | non-condensing         | 20  |     | 80  | %     |

## MECHANICAL

| parameter  | conditions/description | min | typ | max | units |
|------------|------------------------|-----|-----|-----|-------|
| dimensions | 69 x 28.8 x 57.3       |     |     |     | mm    |
| inlet plug | North America, 2-pin   |     |     |     |       |
| weight     |                        |     | 90  |     | g     |


## MECHANICAL DRAWING

units: mm



## DC CORD

units: mm

**Table 1**

| MODEL NO.  | CABLE          | CORD LENGTH  |
|------------|----------------|--------------|
| SWI10-5-N  | UL2468, 20 AWG | 1,500 mm ±50 |
| SWI10-12-N | UL2468, 22 AWG | 1,500 mm ±50 |

## DC PLUG TYPE PART NUMBER KEY

**XXX**

**Plug Polarity:**  
P = Center Positive  
N = Center Negative


**Plug Code:**  
X = Choose a code from the options below

**Plug Angle:**  
"blank" = Straight  
R = Right Angle


| Plug Polarity |             | Code   |                   | Dimensions (mm)  |      |     | Plug Angle |       |
|---------------|-------------|--------|-------------------|------------------|------|-----|------------|-------|
| Center Pos.   | Center Neg. | Option | Type              | A                | B    | C   | Straight   | Right |
| •             | •           | 5      | Standard          | 5.5              | 2.1  | 9.5 | •          | •     |
| •             | •           | 6      | Standard          | 5.5              | 2.5  | 9.5 | •          | •     |
| •             | •           | 7      | Standard          | 3.5              | 1.35 | 9.5 | •          | •     |
| •             | •           | 8      | Standard          | 3.8              | 1.35 | 9.5 | •          | •     |
| •             | •           | 9      | Standard          | 3.8              | 1.05 | 9.5 | •          | •     |
| •             | •           | 10     | Locking           | 5.5              | 2.1  | 9.5 | •          | N/A   |
| •             | •           | 11     | Locking           | 5.5              | 2.5  | 9.5 | •          | N/A   |
| •             | •           | 12     | EIAJ-1            | 2.35             | 0.7  | 9.5 | •          | •     |
| •             | •           | 13     | EIAJ-2            | 4.0              | 1.7  | 9.5 | •          | •     |
| •             | •           | 14     | EIAJ-3            | 4.75             | 1.7  | 9.5 | •          | •     |
| N/A           | N/A         | ST     | Stripped & Tinned |                  |      |     | N/A        | N/A   |
| N/A           | N/A         | MUB    | USB               | Micro USB Type B |      |     | •          | N/A   |

Note: 1. Contact CUI for additional plug options


## Standard




## EIAJ




## Locking



## Stripped &amp; Tinned



## USB



## REVISION HISTORY

| rev. | description          | date       |
|------|----------------------|------------|
| 1.0  | initial release      | 12/12/2016 |
| 1.01 | company logo updated | 09/21/2020 |

The revision history provided is for informational purposes only and is believed to be accurate.

**CUI INC**

a bel group

**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

CUI offers a one (1) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.