## **ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION**

Part Number: 1559 Page 1 of 1 Pages			Issue: Issue Date:	6 1/18/2006
			Effective Date:	2/15/2006
Α.	Construction			Diameters
	1) Component 1	1 X 1 HOOKUP		
	a) Conductor	14 (41/30) AWG TC		
	b) Insulation	0.016" Wall, Nom. PVC		0.106+/- 0.002
	(1) Color(s)	WHITE, BLACK, RED, GREE	EN, YELLOW, BLU	E, BROWN
		ORANGE, GRAY, VIOLET		,
В.	Industry Approvals			
	1) Military	MIL-W-76B TYPE MW	80°C / 1000V	
C.	Physical & Mechanical Properties			
	1) Temperature Range	-40 to 80°C		
	2) Bend Radius	10X Cable Diameter		
	3) Pull Tension	32 Lbs, Maximum		
D.	Electrical Properties	(For Engineering purposes of	only)	
	1) Voltage Rating	1000 V <sub>RMS</sub>		
	2) Inductance	0.04 µH/ft, Nominal		
	3) Conductor DCR	2.8 Ω/1000ft @20°C, Nomin	al	
Ε.	Other	_		
	1) Packaging			
	a) 1000 FT			

b) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.