## ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 2403C Issue: 6

Page 1 of 1 Pages Issue Date: 11/3/2008 Effective Date: 11/10/2008

A. Construction <u>Diameters (In)</u>

1) Component 1 3 X 1 COND a) Conductor 22 (7/30) AWG TC

b) Insulation 0.016" Wall, Nom. Polyethylene(PE) 0.062

(1) Color(s)

1	Cond	Color	Cond	Color	Cond	Color
	1	BLACK	2	RED	3	NATURAL

2) Cable Assembly 3 Components Cabled a) Twists: 6.0 Twists/foot (min)

3) Shield: Alum/Mylar Tape, 25% Overlap, Min.

a) Foil Directionb) Drain WireFoil Facing Out22 (7/30) AWG TC

4) Jacket 0.020" Wall, Nom.,PVC 0.178 (0.188 Max.)

a) Color(s) SLATE

b) Print ALPHA WIRE-\* P/N 2403C 3C 22 AWG

SHIELDED 75C (UL) TYPE CMG OR AWM 2093 ----

C(UL) CMG FT4 ROHS

\* = Factory Code

**B.** Industry Approvals

1) UL AWM/STYLE 2093 60°C / 300 V<sub>RMS</sub>

CMG 75°C

VW-1

CSA International C(UL) TYPE CMG 75°C

FT4

3) EU Directive 2002/95/EC(RoHS):

All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.

4) California Proposition 65: The

The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

C. Physical & Mechanical Properties

1) Temperature Range -20 to 75°C

Bend Radius
Pull Tension
10X Cable Diameter
22 Lbs, Maximum

D. Electrical Properties (For Engineering purposes only)

1) Voltage Rating 300 V<sub>RMS</sub>

2) Capacitance 18.5 pf/ft @1 kHz, Nominal Conductor to Conductor

3) Ground Capacitance 33 pf/ft @1 kHz, Nominal 0.2 µH/ft, Nominal

5) Conductor DCR 16.3 Ω/1000ft @20°C, Nominal 11.7 Ω/1000ft @20°C, Nominal

6) OA Sh Other

1) Packaging

a) 1000 FT

b) BOX 1000FT

c) BOX 500FT

d) 500 FT

e) 328 FT

f) 100 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

## ALPHA WIRE COMPANY CUSTOMER PRODUCT SPECIFICATION

Part Number: 2403C Issue: 6

Page 2 of 1 Pages Issue Date: 11/3/2008 Effective Date: 11/10/2008

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.