

TE Internal #: 2408840-4

Socket Contact, Tin over Nickel, 600 VAC, 12 AWG Wire Size, 2.5 - 4 mm<sup>2</sup> Wire Size, Crimp, Copper Alloy, Power, -13 - 194 °F [-25 - 90 °

Cl

View on TE.com >



#### Connectors > Contacts > Connector Contacts











Contact Type: Socket

Contact Mating Area Plating Material: Tin over Nickel

Wire Contact Termination Area Plating Material: Tin over Nickel

Operating Voltage: 600 VAC

Wire Size: 12 AWG

**Features** 

## **Electrical Characteristics**

Termination Method to Wire & Cable

Product Terminates To

Operating Voltage	600 VAC
Contact Features	
Mating Tab Width	3.2 mm[.126 in]
Mating Tab Thickness	2.3 mm[.091 in]
Contact Orientation	Straight
Contact Underplating Material	Nickel
Contact Type	Socket
Contact Mating Area Plating Material	Tin over Nickel
Wire Contact Termination Area Plating Material	Tin over Nickel
Contact Base Material	Copper Alloy
Contact Current Rating (Max)	23 A
Termination Features	

Crimp

Wire & Cable



#### Mechanical Attachment

Wire Insulation Support	With
Dimensions	
Compatible Insulation Diameter Range	2.5 - 4 mm[.161 in]
Wire Size	2.5 - 4 mm <sup>2</sup>
Usage Conditions	
Operating Temperature Range	-25 - 90 °C[-13 - 194 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Method	Reel

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling



based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# Compatible Parts





# Customers Also Bought





## **Documents**

### **Product Drawings**

Socket Contact of HCI 6.2mm Pitch

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_2408840-4\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2408840-4\_A.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_2408840-4\_A.2d\_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions**of use

### Datasheets & Catalog Pages

HIGH-CURRENT-INTERCONNECT-CONNECTOR-SYSTEM

English

Socket Contact, Tin over Nickel, 600 VAC, 12 AWG Wire Size, 2.5 - 4 mm² Wire Size, Crimp, Copper Alloy, Power, -13 - 194 °F [-25 - 90 °C]



**Product Specifications** 

**Application Specification** 

English