

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 6210/12C
Page 1 of 1 Pages

Issue: 4
Issue Date: 5/26/2005
Effective Date: 8/1/2005

A. Construction

Diameters (In)

- 1) Component 1 12 X 1 PAIR
 - a) Conductor 24 (7/32) AWG TC
 - b) Insulation 0.016" Wall, Nom. Polypropylene, Foam 0.056
 - (1) Color Code Alpha Wire Company Color Code A

Pair	Color	Pair	Color	Pair	Color
1	BLACK-RED	5	BLACK-BROWN	9	RED-WHITE
2	BLACK-WHITE	6	BLACK-YELLOW	10	RED-BLUE
3	BLACK-GREEN	7	BLACK-ORANGE	11	RED-YELLOW
4	BLACK-BLUE	8	RED-GREEN	12	RED-BROWN

- c) Pair 2/Cond Cabled Together
- (1) Twists: 8.0 Twists/foot (min)
- 2) Component 2 1 X 1 COND
 - a) Conductor 24 (7/32) AWG TC
 - b) Insulation 0.016" Wall, Nom. Polypropylene, Foam 0.056
 - (1) Color(s)

Cond	Color	Cond	Color	Cond	Color
1	RED				

- 3) Cable Assembly 13 Components Cabled
- a) Twists: 2.2 Twists/foot (min)
- 4) Shield: Alum/Mylar Tape, 25% Overlap, Min.
- a) Foil Direction Foil Facing Out
- b) Drain Wire 24 (7/32) AWG TC
- 5) Jacket 0.035" Wall, Nom., PVC 0.455 (0.477 Max.)
- a) Color(s) SLATE
- b) Ripcord 1 End 810 Denier Nylon
- c) Print ALPHA WIRE-* P/N 6210/12C 12PR/1C 24 AWG
SHIELDED 75C (UL) TYPE CM OR AWM 2919 LOW VOLTAGE
COMPUTER CABLE --- LLXXXXXX CSA TYPE CMG FT4
ROHS

* = Factory Code

[Note: Product may have c(UL) or CSA markings depending upon plant of manufacture.]

B. Industry Approvals

- 1) UL AWM/STYLE 2919 80°C / 30 V_{RMS}
CM 75°C
VW-1
- 2) CSA International CMG 60°C
FT4
- 3) EU Directive 2002/95/EC(RoHS):
All materials used in the manufacture of this part are in compliance with EU Directive 2002/95/EU regarding the restriction of use of certain hazardous substances in electrical and electronic equipment. Consult Alpha Wire's web site for compliance Date of Manufacture.
- 4) California Proposition 65: The outer surface materials used in the manufacture of this part meet the requirements of California Proposition 65.

C. Physical & Mechanical Properties

- 1) Temperature Range -20 to 80°C
- 2) Bend Radius 10X Cable Diameter
- 3) Pull Tension 91 Lbs, Maximum

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.
Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

ALPHA WIRE COMPANY
CUSTOMER PRODUCT SPECIFICATION

Part Number: 6210/12C
Page 2 of 1 Pages

Issue: 4
Issue Date: 5/26/2005
Effective Date: 8/1/2005

- D. Electrical Properties** (For Engineering purposes only)
- 1) Voltage Rating 300 VRMS
 - 2) Characteristic Impedance 105 Ω +/- 10
 - 3) Mutual Capacitance 12.5 pf/ft @1 kHz, Nominal
 - 4) Ground Capacitance 22 pf/ft @1 kHz, Nominal
 - 5) Velocity of Propagation 78 %
 - 6) Attenuation, Max dB/100ft 0.25 @ 100 kHz
0.8 @ 1 MHz
5.8 @ 50 MHz
- E. Other**
- 1) Packaging
 - a) 1000 FT
 - b) 500 FT

Although Alpha Wire Company ("Alpha") makes every reasonable effort to ensure their accuracy at the time of publication, information and specifications described herein are subject to errors or omissions and to changes without notice, and the listing of such information and specifications does not ensure product availability.

Alpha provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Alpha be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary) whatsoever, even if Alpha has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.