# 2484637-1 <

TE Internal #: 2484637-1 SMA RF Interface, Jack, 50 Ω, Threaded, 0 – 18 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount

#### View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: SMA

RF Connector Style: Jack

Impedance:  $50 \Omega$ 

RF Connector Coupling Mechanism: Threaded

Operating Frequency: 0 – 18 GHz

### Features

### Product Type Features

RF Interface	SMA
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
PCB Mount Orientation	Edge
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	
Impedance	50 Ω
Body Features	
Body Underplating Material	Nickel
Body Material	Brass

**C** For support call+1 800 522 6752

#### 2484637-1

SMA RF Interface, Jack, 50  $\Omega$ , Threaded, 0 – 18 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount



Body Material Finish	Plated
Body Plating Material	Gold
Contact Features	
RF Connector Center Contact Underplating Material	Nickel
	30 µin
RF Connector Contact Configuration	Captivated Contacts
RF Connector Center Contact Plating Material	Gold (Au)
RF Connector Center Contact Material	Beryllium Copper
Termination Features	
Termination Post & Tail Length	4.75 mm
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical
Usage Conditions	

# Operation/Application

Operating Temperature Range

Operating Frequency	0 – 18 GHz
Packaging Features	
Packaging Quantity	100
Packaging Method	Tray
Other	
Outer Contact Plating Material	Gold (Au)
Dielectric Material	Polytetrafluoroethylene (PTFE)
<b>Product Compliance</b> For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU RoHS Directive 2011/65/EU EU ELV Directive 2000/53/EC	Compliant with Exemptions Not Yet Reviewed

-65 – 165 °C[-85 – 329 °F]

#### 2484637-1

SMA RF Interface, Jack, 50  $\Omega$ , Threaded, 0 – 18 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount



 Current ECHA Candidate List: JUNE 2024 (241)
Candidate List Declared Against: JAN 2024 (240)
SVHC > Threshold:
Pb (4% in Component Part)
Attice Safe Usage Statements:
Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free

#### Halogen Content

Solder Process Capability

Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be

# **Compatible Parts**



#### 2484637-1

SMA RF Interface, Jack, 50  $\Omega$ , Threaded, 0 – 18 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount



## Documents

Product Drawings SMA Jack RA Edge Mnt Solder Tab 18 GHz

English

#### **CAD** Files

Customer View Model ENG\_CVM\_CVM\_2484637-1\_1.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_2484637-1\_1.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_2484637-1\_1.3d\_stp.zip

English

#### 3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Product Specification

English