

Dual Port Gigabit PCI Express Server Network Adapter Card - PCIe NIC

Product ID: ST1000SPEXD4



The ST1000SPEXD4 PCI Express Dual-Port Gigabit Network Card lets you add two gigabit Ethernet ports to a client, server or workstation through a single PCIe slot. Each port provides 10/100/1000 Mbps capable Ethernet and is fully compatible with IEEE 802.3/u/ab standards.

Suitable for any standard PCI Express-enabled system, the 2-port Ethernet card supports full-duplex flow control for maximum data transfer speeds of up to 2000 Mbps - an ideal 2-port NIC for setting up dual-homed, or multi-homed host configurations providing added security to corporate networks.

The dual-port server adapter is compliant with the PCIe 2.0 standard and features support for Jumbo Frames and 802.1q VLAN tagging as well as Wake on LAN (WoL). The adapter includes an optional low-profile / half-height bracket that can be used for installation into a standard or small form-factor computer chassis.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Ideal for VM environments with multiple operating systems, requiring shared or dedicated NICs

- Provide redundant connectivity to ensure an uninterrupted network connection
- Configure a dual-homed proxy or gateway system for an added layer of security
- Specially designed for desktop PC clients, servers, and workstations with few PCI Express slots available

Features

- Two 10/100/1000Mbps compatible RJ-45 Ethernet ports
- Up to 9K Jumbo Frame support
- Compatible with PCI Express Base Specification 2.0 (backward compatible with 1.0a/1.1)
- Fully Compliant with IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, and supports IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
- Supports Microsoft NDIS5 Checksum Offload (IP, TCP, UDP) and Large send Offload
- Wake-on-LAN / Remote Wake-up support
- Configured with standard profile bracket, low profile/half-height bracket included
- Supports Pair Swap / Polarity / Skew Correction

Hardware

Warranty	2 Years
Ports	2
Interface	RJ45 (Gigabit Ethernet)
Bus Type	PCI Express
Card Type	Standard Profile (LP bracket incl.)
Port Style	Integrated on Card
Industry Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab PCI Express Base Specification 2.0
Chipset ID	Realtek - RTL8111 ASMedia - ASM1182E

Performance

Maximum Data Transfer	2000 Mbps (full-duplex), 1000 Mbps (half-duplex)
-----------------------	--

Rate		
Compatible Networks		10/100/1000 Mbps
Auto MDIX		Yes
Full Duplex Support		Yes
Jumbo Frame Support		9K max.
Promiscuous Mode		Yes
Supported Protocols		IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full Duplex Flow Control
Connector(s)		
Connector Type(s)		1 - PCI Express x1
External Ports		2 - RJ-45
Software		
OS Compatibility		Windows 2000, XP, Vista, 7, 8, 8.1, 10, 11 Windows Server 2003, 2008 R2, 2012, 2012 R2, 2016, 2019 Mac OS 10.4 to 10.9 Linux 2.4.x and up - <i>LTS Versions only</i>
Special Notes / Requirements		
System and Cable Requirements		Available PCI Express slot
Indicators		
LED Indicators		2 - Yellow - Gigabit Mode 2 - Green - Link/Activity
Power		
Input Voltage		12V DC
Output Voltage		12V DC
Environmental		
Operating Temperature		0C to 70C (32F to 158F)
Storage Temperature		0C to 100C (32F to 212F)

Humidity 10~90% RH

Physical Characteristics

Color	Green
Material	Steel
Product Length	3.6 in [9.3 cm]
Product Width	0.7 in [1.8 cm]
Product Height	4.7 in [12.0 cm]
Weight of Product	1.9 oz [53.0 g]

Packaging Information

Package Quantity	1
Package Length	6.8 in [17.2 cm]
Package Width	5.6 in [14.2 cm]
Package Height	1.3 in [3.2 cm]
Shipping (Package) Weight	4.8 oz [136.0 g]

What's in the Box

Included in Package	1 - PCIe Network Card
	1 - Low Profile Bracket
	1 - Instruction Manual

**Product appearance and specifications are subject to change without notice.*