


CONDUCTIVE INJECTION MOLDED HINGED BOXES

IMPROVED BOX STYLE

- · Stronger hinges and latches
- · Tongue and groove closure
- · Thicker, stronger walls

EASY TO ORDER

- · Available in small case lots
- · Arrive completely assembled
- · Ask about custom inserts







SPECIFICATIONS

These products meet and/or exceed ANSI/ESD S20.20-2021 and ANSI/ESD S541-2019.

INJECTION MOLDED HINGED BOXES		
PROPERTY	VALUE (U.S.)	TEST METHOD
Surface Resistivity	<16 Ohms/sq	D257
Volume Resistivity	<13 Ohms/sq	D257
Electrostatic Decay Rate	<2 sec	FTMS101C 4046.1
Impact Strength, IZOD		
Notched 1/8" Section	5.0 ft-Ib/in	D256
Unnotched 1/8" Section	No Break	D4812
Tensile Strength	3200 psi	D638
Tensile Elongation	>10.0%	D638
Tensile Module	.15x10 ⁶ psi	D638
Flexural Strength	4700 psi	D790
Fexural Modulus	.17x10 ⁶ psi	D790

All values are for pre-formed materials. Electrical values will vary with each individual design. All information, recommendations and suggestions appearing in this bulletin concerning the use of our products are based upon tests and data believed to be reliable: however, it is the user's responsibility to determine the suitability for their own use of the products described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Conductive Containers, Inc. as to the effects of such use or the results to be obtained, nor does Conductive Containers, Inc. assume any liability arising out of use, by others, of the products referred to herein. Nor is the information herein to be construed as absolutely complete since additional information may be necessary or desirable, when particular or exceptional conditions or circumstances exist orbecause of applicable laws or government regulations. Nothing herein contained is to be construed as permission or as a recommendation to infringe any patent.

