

## **PILLOWPACKS**

- Perfect for fragile, sensitive and expensive components
- · ESD safe foam forms around the parts
- No tooling required
- Provides great physical protection
- Fits multiple sized components

PN	LXWXH(D)	QTY/CASE
PP2020	2 X 2 X 1/4"	100
PP2525	2-9/16 x 2-9/16 x 1/2"	150
PP2535	3-1/2 x 2-9/16 x 1/2"	100
PP3545	4-5/8 x 3-1/2 x 1/2"	50
PP7035	7 x 3-1/2 x 1/2"	50



## **SPECIFICATIONS**

These products meet and/or exceed ANSI/ESD S20.20-2021 and ANSI/ESD S541-2019.

INJECTION MOLDED HINGED BOXES				
PROPERTY	VALUE (U.S.)	TEST METHOD		
Surface Resistivity	<16 Ohms/sq	D257		
Volume Resistivity	<1 <sup>3</sup> Ohms/sq	D257		
Electrostatic Decay Rate	<2 sec	FTMS101C 4046.1		
Impact Strength, IZOD				
Notched 1/8" Section	5.0 ft-lb/in	D256		
Unnotched 1/8" Section	No Break	D4812		
Tensile Strength	3200 psi	D638		
Tensile Elongation	>10.0%	D638		
Tensile Module	.15x10 <sup>6</sup> psi	D638		
Flexural Strength	4700 psi	D790		
Fexural Modulus	.17x10 <sup>6</sup> psi	D790		

PILLOWSTAT FOAM				
PROPERTY	VALUE (U.S.)	TEST METHOD		
Color	Black	Visual		
Volume Resistance	103-105 Ohms/sq	ANSI/ESD STM11.12-2021		
Surface Resistance	103-105 Ohms/sq	ANSI/ESD STM11.11-2022		
Static Decay Rate	0.01 Sec	ASTM D-257		
Density	4.8 - 5.2 lbs/ft3	ASTM D-3574-01		
Indent Force Deflection @ 25%	7-17 psi	ASTM D-3574-01		
Shelf Life	Long Term			

All values are for pre-formed materials. Electrical values will vary with each individual design. All information, recommendations and suggestions appearing in this bulletin concerning the use of our products are based upon tests and data believed to be reliable: however, it is the user's responsibility to determine the suitability for their own use of the products described herein. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Conductive Containers, Inc. as to the effects of such use or the results to be obtained, nor does Conductive Containers, Inc. assume any liability arising out of use, by others, of the products referred to herein. Nor is the information herein to be construed as absolutely complete since additional information may be necessary or desirable, when particular or exceptional conditions or circumstances exist orbecause of applicable laws or government regulations. Nothing herein contained is to be construed as permission or as a recommendation to infringe any patent.

