# 3.0 USB Type B to Type A Receptacle Metal Feed Through Connector

## multicomp PRO







MP-CP30107

MP-CP30109

#### **Features**

- · Fits standard XLR Ø24mm cutout.
- No soldering or punch termination. Use standard cable for each connector style.
- · Front or rear mounted.

#### **Specifications**

Contact Resistance  $:\le 30 \text{m}\Omega$ Dielectric Strength :500 V ACInsulation Resistance  $:1000 \text{M}\Omega$ Operating Temperature  $:-25^{\circ}\text{C}$  to  $+85^{\circ}\text{C}$ 

Rated Current : 1.5A Rated Voltage : 30V

Lifetime : >1500 mating cycles

Material


Metal Frame : Diecast, Black or Nickel plated

USB Connector : PBT

USB Contacts : Gold plated

Contacts : Brass, Tin or Nickel plated

#### **Diagram**



Dimensions : Millimetres

### **Part Number Table**

Description	Part Number
3.0 USB Type B to Type A Receptacle, Metal Feed Through Connector, Nickel CSK hole	MP-CP30107
3.0 USB Type B to Type A Receptacle, Metal Feed Through Connector Black CSK hole	MP-CP30109

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

