
2477168-1 - ACTIVE

TE Internal #: 2477168-1 SMC RF Interface, Jack, 50 ohm, Threaded, 0 – 10 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount

View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: SMC

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 7.06 mm [.275 in]

Impedance: 50Ω

RF Connector Coupling Mechanism: Threaded

Features

Product Type Features

RF Interface	SMC
RF Connector Style	Jack
Connector System	Cable-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
PCB Mount Orientation	Right Angle
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	
Impedance	50 Ω
Body Features	
Body Material	Brass
Body Material Finish	Plated

C For support call+1 800 522 6752

2477168-1

SMC RF Interface, Jack, 50 ohm, Threaded, 0 – 10 GHz Operating Frequency, Cableto-Board, 1 Position, Printed Circuit Board, Board Mount



Body Plating Material	Gold
Contact Features	
	30 µin
RF Connector Contact Configuration	Captivated Contacts
RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Brass
Termination Features	
Termination Post & Tail Length	3.94 mm[.155 in]
Termination Method to PCB	Through Hole - Solder
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical
Detent	Without
Dimensions	
Profile Height from PCB	3.94 mm[.155 in]

Product Length	14.1 mm[.555 in]
RF Connector Mated Outer Diameter (Approximate)	7.06 mm[.275 in]
Usage Conditions	
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Operating Frequency	0 – 10 GHz
Packaging Features	
Packaging Quantity	1
Packaging Method	Bag
Other	
Outer Contact Plating Material	Gold (Au)
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>

2477168-1

SMC RF Interface, Jack, 50 ohm, Threaded, 0 – 10 GHz Operating Frequency, Cableto-Board, 1 Position, Printed Circuit Board, Board Mount



EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (3.34% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Documents

Product Drawings SMC Jack RA PCB Thru Hole Gold 10 GHz

2477168-1

SMC RF Interface, Jack, 50 ohm, Threaded, 0 – 10 GHz Operating Frequency, Cableto-Board, 1 Position, Printed Circuit Board, Board Mount



English **CAD** Files 3D PDF 3D **Customer View Model** ENG_CVM_CVM_2477168-1_1.3d_stp.zip English **Customer View Model** ENG_CVM_CVM_2477168-1_1.2d_dxf.zip English Customer View Model ENG_CVM_CVM_2477168-1_1.3d_igs.zip English By downloading the CAD file I accept and agree to the Terms and Conditions of use Datasheets & Catalog Pages SMC-Connectors-Product-Extension-en-flyer English

Product Specifications Product Specification English