2477171-1 <

TE Internal #: 2477171-1 SMC RF Interface, Plug, 50 ohm, RG 174/U / RG 188 A/U / RG 316 /U, Threaded, 0 – 6 GHz Operating Frequency, Cable-to-Cable, 1 Position, Wire & Cable

View on TE.com >



Connectors > RF Connectors > Coax Connectors



RF Interface: SMC

RF Connector Style: Plug

RF Connector Mated Outer Diameter (Approximate): 6.35 mm [.25 in]

Impedance: 50Ω

Compatible With RF Cable Type: RG 174/U, RG 188 A/U, RG 316/U

Features

Product Type Features

RF Interface	SMC
RF Connector Style	Plug
Compatible With RF Cable Type	RG 174/U, RG 188 A/U, RG 316/U
Connector System	Cable-to-Cable
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	
Impedance	50 Ω
Body Features	
Body Underplating Material	Nickel
Cable Connector Orientation	Straight

2477171-1

SMC RF Interface, Plug, 50 ohm, RG 174/U / RG 188 A/U / RG 316/U, Threaded, 0 – 6 GHz Operating Frequency, Cable-to-Cable, 1 Position, Wire & Cable



Body Material	Brass
Body Material Finish	Plated
Body Plating Material	Gold
Contact Features	
	30 µin
RF Connector Contact Configuration	Sliding
Ferrule Plating Material	Gold over Nickel
Crimp Type	Hexagonal Crimping
Ferrule Material	Brass
RF Connector Center Contact Plating Material	Gold
RF Connector Center Contact Material	Beryllium Copper
Termination Features	
Termination Method to Wire & Cable	Solder
Mechanical Attachment	
RF Connector Coupling Mechanism	Threaded
Connector Mounting Type	Cable Mount (Free-Hanging)
RF Contact Captivation Method	Mechanical
Detent	Without
Dimensions	
Product Length	16 mm[.63 in]
RF Connector Mated Outer Diameter (Approximate)	6.35 mm[.25 in]
Usage Conditions	
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Operating Frequency	0 – 6 GHz
Packaging Features	
Packaging Quantity	1
Packaging Method	Bag
Other	
Coupling Nut Plating Material	Gold over Nickel
Coupling Nut Plating Finish	Plated
Outer Contact Plating Material	Gold (Au)

2477171-1

SMC RF Interface, Plug, 50 ohm, RG 174/U / RG 188 A/U / RG 316/U, Threaded, 0 – 6 GHz Operating Frequency, Cable-to-Cable, 1 Position, Wire & Cable



Coupling Nut Base Material	Brass
Additional Features	Shrink Tubing
Dielectric Material	PTFE
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Pb (3.34% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Soldar Process Capability	Not reviewed for solder process capability

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts

2477171-1

SMC RF Interface, Plug, 50 ohm, RG 174/U / RG 188 A/U / RG 316/U, Threaded, 0 – 6 GHz Operating Frequency, Cable-to-Cable, 1 Position, Wire & Cable







Documents

Product Drawings SMC Plug Str Crimp RG174 188A 316 6 GHz

English

CAD Files 3D PDF

3D

Customer View Model ENG_CVM_CVM_2477171-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2477171-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2477171-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

Datasheets & Catalog Pages SMC-Connectors-Product-Extension-en-flyer

English

Product Specifications Product Specification

English