True RMS Mini Clamp Meter





Features

- 2000 Counts Display
- LCD Backlight
- Manual & Auto Ranging
- 17mm Jaw Capacity
- NCV Detector

- Data Hold
- MAX/MIN & Relative Modes
- Auto Power Off
- Low Battery Indication
- Input Protection

Electrical Specifications

| Basic Functions | Range | Best Accuracy |
|------------------------|-------------------|-------------------|
| AC Current | 2A/20A/200A | ±(2.5% +5 digits) |
| Jaw Capacity | 17mm | |
| Auto Power Off | Around 15 minutes | |
| Low Battery Indication | ≤ 2.5V | |

General Characteristics

| Safety Rating | : CAT II 600V, CAT III 300V |
|----------------|-----------------------------|
| Power | : AAA 1.5V Batteries × 2 |
| LCD Size | : 39.3mm × 26.5mm |
| Product Colour | : Orange & Grey |
| Product Weight | : 160g |
| Product Size | : 155mm × 60mm × 33.5mm |
| | |

| Accessories | Qty. | Note |
|------------------|----------|---------------------------|
| Operating Manual | 1 piece | - |
| Battery | 2 pieces | 1.5V AAA × 2, Replaceable |

Part Number Table

| Description | Part Number |
|-------------------------------------|-------------|
| True RMS Mini Clamp Meter, 17mm Jaw | 72-3500 |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. TENMA is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands Farnell.com/exclusive-brands Element14.com/exclusive-brands

