True RMS Mini Clamp Meter Multicomp PRO





Features

- 2000 Counts Display
- LCD Backlight
- Manual & Auto Ranging
- 17mm Jaw Capacity
- Diode and Continuity Test
- NCV Detector
- VFC Function

- · Continuity Buzzer
- Data Hold
- Zero/MAX/MIN Modes
- · Auto Power Off
- · Low Battery Indication
- Input Protection
- Input Impedance for DCV: $10M\Omega$

Electrical Specifications

Basic Functions	Range	Best Accuracy	
AC Current	2A/20A/100A	±(2.5% +5 digits)	
DC Current	2A/20A/100A	±(2% +3 digits)	
AC Voltage	2V/20V/200V/600V	±(1% +3 digits)	
DC Voltage	200mV/2V/20V/200V/600V	±(0.7% +3 digits)	
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2ΜΩ/20ΜΩ	±(1% +2 digits)	
Capacitance	2nF/20nF/200nF/2µF/20µF/200µF/2mF/20mF	±(4% +5 digits)	
Jaw Capacity	17mm		
Auto Power Off	Around 15 minutes		
Low Battery Indication	≤ 2.5V		

General Characteristics

Safety Rating : CAT II 600V, CAT III 300V Power : AAA 1.5V Batteries × 2 LCD Size : 39.3mm × 26.5mm Product Colour : Orange & Grey

Product Weight : 170g

Product Size : 175mm × 60mm × 33.5mm

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



True RMS Mini Clamp Meter Multicomp PRO



Accessories	Qty.	Note
Operating Manual	1 piece	-
Test Leads	1 pair	Leads length: 900mm, Rod length: 136mm Tip length: 15.7mm Safety level: CAT III 1000V/CAT IV 600V 10A
Battery	2 pieces	1.5V AAA × 2, Replaceable

Part Number Table

Description	Part Number	
True RMS Mini Clamp Meter, 17mm Jaw	72-2985	

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

