
<mark>МацокУ</mark> Mallory Sonalert Products, Inc.					t#: JTC028-YG-CDL		
Sales Outline Drawing				Revisio	Α		
Specifications:							
Stack Number:	1	2					
LED Color:	YELLOW	GREEN					
LED Operation:	Continuous	Continuous					
Connection Wires:	Yellow and Brown	Green and Brown					
LED Current Draw:	<60 mA	<40 mA					
Rated Voltage:	24 VAC/DC						
Operating Voltage:			20-28 VAC/DC				
Sound Level Category:	Loud	Loud	Loud		Loud		
Mode of Operation:	Continuous	Medium Pulse (5PPS)	Double Pulse (0.5	PPS)	Continuous for 5 sec then 0.1s beep until reset		
Connection:	Black and Gray Wires	Black and Gray Wires;	Black and Gray Wires	; Purple	Black and Gray wires; Orange and		
		Orange wire connected	wire connected	to	Purple wires connected to		
		to Green/Yellow wire	Green/Yellow wire		Green/Yellow wire		
Sound Current Draw:	40mA Max.	40mA Max.	40mA Max.		40mA Max.		
Loudness @ 1m:	80-85 dB(A) Typ.						
Frequency:	2000 ± 500 Hz						
Total Max Current:	<140mA with all LED's and sound unit working						
Operating Temperature:	-25° ~ +60°C						
Lens Color:	Transparent - matching LED stack color						
Material:	Lexan CFR7431						
Mounting Method:	Direct Mount using 1/2" NPT Stainless Steel Pipe and Nut						
Weight Typical (g):	315						
NEMA 12:	Approved						
Options:		Please contact factory.					

**Dimensions:** Inches (mm)

## **cUL Recognized CE Certified**

**ROHS Compliant** 



LED OPERATION: CONNECT STACK COLOR WIRE TO POWER AND BROWN WIRE TO POWER.

SOUND OPERATION: CONNECT GRAY AND BLACK WIRES TO POWER FOR CONTINUOUS SOUND.

FOR MEDIUM PULSE, CONNECT GRAY & BLACK TO POWER AND ORANGE WIRE TO GREEN/YELLOW WIRE. FOR DOUBLE PULSE, CONNECT GRAY & BLACK TO POWER AND PURPLE WIRE TO GREEN/YELLOW WIRE. FOR CONT/BEEP, CONNECT GRAY & BLACK TO POWER AND ORANGE & PURPLE TO GREEN/YELLOW WIRE.