multicomp PRO



RoHS Compliant

Specifications

Nominal Voltage		1.2V/cell
Capacity	Typical	2600mAh/0.2CmA
	Minimum	2300mAh/0.2CmA
Charge	Standard	0.1CmA for 16 hrs.
	Rapid	1CmA for 1.2hrs.(approx.) (With- $\Delta V = 5$ to 10mV/cell, Temp., Time charging control)
	Trickle	0.03CmA (1 month)
Maximum Discharge Current		3CmA
Discharge Cut-off Voltage		1V/cell
Cycle Life		500 cycles (See Note:1)
Applicable Temperature	Standard Charge	0 to +45°C
	Rapid Charge	0 to +40°C
	Discharge	-10°C to +60°C
Storage	Within one year	-20°C to +35°C
	Within 3 months	-20°C to +45°C
	Within 1 month	-20°C to +55°C
Relative Humidity Range		65% ±20%
Dimension		D = 14.3mm max., H = 50.5mm max.
Weight		Approx. 30g

Part Number Table

Description	Part Number
NiMH Rechargeable Battery, AA, 1.2V, 2300mAh, 4PK Blister	MP001176
NiMH Rechargeable Battery, AA, 1.2V, 2300mAh, Tag 1PK	MP001177

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

