

NiMH Rechargeable AAA (High Top) Battery 1.2V, 900mAh

multicompPRO

**RoHS
Compliant**



Specifications

Nominal Voltage		1.2V/cell
Capacity	Typical	1000mAh/0.2CmA@20°C
	Minimum	900mAh/0.2CmA@20°C
Charge	Standard	0.1CmA for 16 hrs.
	Rapid	0.5CmA for 2.2hrs.(approx.) -ΔV = 0 to 5mV/cell, Temp. cut-off = 45 to 50°C, dT / dt = 0.8°C/ min. Ta = 0 to 40°C.
	Trickle	0.03CmA
Maximum Discharge Current		1CmA (Continuous) 3CmA (Pulse)
Discharge Cut-off Voltage		1V/cell
Cycle Life		500 cycles (See Note:1)
Applicable Temperature	Standard Charge	0 to +45°C
	Rapid Charge	0 to +40°C
	Discharge	-10°C to +60°C
Storage	Within one year	-20°C to +20°C
	Within 3 months	-20°C to +30°C
	Within 1 month	-20°C to +40°C
Relative Humidity Range		65% ±20%
Dimension		D = 10.5mm max., H = 44.5mm max.
Weight		Approx. 12.5g

Part Number Table

Description	Part Number
NiMH Rechargeable Battery, AAA, 1.2V, 900mAh, 4PK Blister	MP001178
NiMH Rechargeable Battery, AAA, 1.2V, 900mAh, Tag 1PK	MP001179

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO