




Description:

The 2N3902 is a silicon NPN transistor in a TO-3 type Package designed for use in high voltage inverters, converters, switching regulators and line Operated amplifiers.

**RoHS
Compliant**



Maximum Ratings:

Characteristic	Symbol	Rating	Unit
Collector-Emitter Voltage	V_{CEX}	700	V
Collector-Emitter Voltage	$V_{CEO(sus)}$	400	
Emitter Base Voltage	V_{EB}	5	
Collector Current -Continuous	I_C	3.5	A
Peak Base Current	I_B	2	
Total Device Dissipation $-(T_C = +75^{\circ}C)$, Derate Above $95^{\circ}C$	P_D	100 1.33	W W/ $^{\circ}C$
Operating Junction Temperature Range	T_J	-65 to +150	$^{\circ}C$
Storage Temperature Range,	T_{stg}	-65 to +200	
Thermal Resistance, Junction-to-Case	R_{thJC}	0.75	$^{\circ}C/W$
Maximum Lead temperature (During Soldering, 1/8" from case, 5sec)	T_L	+275	$^{\circ}C$

Electrical Characteristics: ($T_C = +25^{\circ}C$ Unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Max	Unit
-----------	--------	-----------------	-----	-----	------

OFF Characteristics (Note 2)

Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	$I_C = 100mA, I_B = 0$	325	-	V
Collector Cutoff Current	I_{CEO}	$V_{CE} = 400V, V_{BE} = 0$	-	0.25	mA
Emitter-Base Voltage	I_{EBO}	$I_E = 100mA, I_C = 5V$		5	

ON Characteristics (Note 2)


DC Current Gain	h_{FE}	$V_{CE} = 5V, I_C = 1A$	25	90	
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = 2.5A, I_B = 0.5A$	-	2.5	V
Base-Emitter Saturation Voltage	$V_{BE(sat)}$			2	

Dynamic Characteristics

Current Gain-Bandwidth Product	f_T	$V_{CE} = 10V, I_C = 200mA, f = 1MHz$	2.8	-	MHz
--------------------------------	-------	---------------------------------------	-----	---	-----

Note:

1. Pulse Test : Pulse Width = 5ms, Duty Cycle $\leq 10\%$
2. Pulse Test : Pulse Width = 300 μs , Duty Cycle $\leq 2\%$



Pin Configuration:

Pin 1. Base

Pin 2. Emitter

Collector (Case)

Dim	A	B	C	D	E	F	G	H	I	J	K
Min.	38.75	19.28	7.96	11.18	25.2	0.92	1.38	29.9	16.64	3.88	10.67
Max.	39.96	22.23	9.28	12.19	26.67	1.09	1.62	30.4	17.3	4.36	11.18

Dimensions : Millimetres

Part Number Table

Description	Part Number
Transistor, NPN, 3.5A, 400V, TO-3	2N3902

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.