

DEUTSCH | DEUTSCH DT

TE Internal #: DT04-6P-E008

6 Position Housing, Housing for Male Terminals, Wire-to-Wire, 3.81 mm [.15 in] Centerline, Sealable, Gray, Wire & Cable, Power,

DEUTSCH DT

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > DEUTSCH DT Receptacle Connectors











Number of Positions: 6

Connector & Housing Type: Housing for Male Terminals

Mating Pin Diameter: 1.59 mm [.063 in]

Connector System: Wire-to-Wire
Centerline (Pitch): 3.81 mm [.15 in]

All DEUTSCH DT Receptacle Connectors (231)

Features

Industry Standards

IP Rating	IP6K9K, IP68
Compatible With Agency/Standards Products	SAE J2030
UL Flammability Rating	12mm Flame Test per Standard UL-94

Dimensions

Row-to-Row Spacing	4.45 mm[.175 in]
Compatible Insulation Diameter Range	2.23 – 3.68 mm[.088 – .145 in]
Product Width	20.83 mm[.82 in]
Product Length	58.19 mm[2.291 in]
Connector Height	24.16 mm[.951 in]

Packaging Features

Packaging Quantity	450
Packaging Method	Box



Mechanical Attachment

Strain Relief	Add By Accessory
Terminal Position Assurance	Yes
Mating Alignment Type	Polarized
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Other

Serviceable	Yes
Connector Position Assurance Capable	No
EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

Electrical Characteristics

Operating Voltage	250 VDC
Nominal Voltage Architecture	250 V

Body Features

Cable Exit Angle	180°
Primary Product Color	Gray

Housing Features

Housing Material	PA GF
Centerline (Pitch)	3.81 mm[.15 in]

Contact Features

Contact Size	Size 16
Contact Type	Pin
Mating Pin Diameter	1.59 mm[.063 in]
Contact Current Rating (Max)	13 A

Product Type Features

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	Yes
Primary Locking Feature	Integrated in Housing



Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Blank Cavity Position	0
Number of Positions	6
Number of Rows	2
Usage Conditions	
Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Circuit Application	Power

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) SVHC > Threshold: Octamethylcyclotetrasiloxane (D4) (.5% in Component Part) Dodecamethylcyclohexasiloxane (D6) (.5% in Component Part) Decamethylcyclopentasiloxane (D5) (.5% in Component Part) Article Safe Usage Statements: Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous



materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # W6P WEDGE LOCK, 6P, REC, GRN, DT



TE Part # CAT-J41-DDPC
DEUTSCH DT Plug Connectors



TE Part # CAT-D48-ST273
DEUTSCH Solid Contacts



TE Part # DT04-6P-Contacts REC, 6P, GRY, E



TE Part # CAT-D48-SFT273

DEUTSCH Stamped and Formed
Contacts



TE Part # 2300908-1 0460-003-16329, PIN, SOLID, 20-24AWG, AU



TE Part # 1924487-2 MOUNTING CLIP, AMPSEAL 16



TE Part # CAT-D48-SP729
DEUTSCH Sealing Plugs



TE Part # DT6P-DC PROTECT CVR, 6P, REC, GRY, DT



TE Part # DT-RT1

EXT TOOL, FRONT RELEASE









Also in the Series | DEUTSCH DT





Automotive Connector Caps & Covers (19)




Automotive Housings(738)



Connector Caps & Covers(1)






Customers Also Bought



TE Part #K1145366 Limit switch G12-221-S-015











Documents

Product Drawings REC, 6P, GRY, N, XCAP

English

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_DT04-6P-E008_A.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_DT04-6P-E008_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_DT04-6P-E008_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

TERMINALS AND CONNECTORS

English

ICT Terminals and Connectors Catalogue

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English