

Part Number: 5018442210


**Product Description: 2.00mm Pitch** 

MicroClasp Wire-to-Board Header, Dual Row, Vertical, 22 Circuits, with PCB Locator

Series Number: 501844

**Status:** New Business Not Supported **Product Category: PCB Headers and** 

Receptacles



### **Documents & Resources**

## **Product Environment Compliance**

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	<b>©</b>
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)6225-DC (07 Nov 2024)
EU RoHS	Compliant per EU 2015/863

### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## **EU RoHS Certificate of Compliance**

#### **Part Details**

### General

Status	New Business Not Supported
Category	PCB Headers and Receptacles
Series	501844
Description	2.00mm Pitch MicroClasp Wire-to- Board Header, Dual Row, Vertical, 22 Circuits, with PCB Locator
Application	Signal, Wire-to-Board
Component Type	PCB Header
Product Name	MicroClasp
UPC	822350107983

# Electrical

Current - Maximum per Contact	3.0A
Voltage - Maximum	250V

# Physical

Breakaway	No
Circuits (Loaded)	22
Circuits (maximum)	22
Color - Resin	Natural
Durability (mating cycles max)	30
First Mate / Last Break	No
Glow-Wire Capable	No
Guide to Mating Part	No
Keying to Mating Part	None
Lock to Mating Part	Yes
Material - Plating Mating	Tin
Material - Resin	Polyester
Net Weight	1689.880/mg
Number of Rows	2
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	3.20mm
PCB Locator	Yes
PCB Retention	None
PCB Thickness - Recommended	1.60mm

Pitch - Mating Interface	2.00mm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Shrouded	Fully
Stackable	No
Temperature Range - Operating	-25° to +85°C
Termination Interface Style	Through Hole

This document was generated on Mar 13, 2025