Specifications



Photo is representative

Eaton XL60-2R9348W-R

Eaton XL60 supercapacitor, Capacitance 3000 F, 2.85 V, $0.23m\Omega$ ESR, Weldable Terminal

General specifications	5
PRODUCT NAME	Eaton XL60 medium and large cells supercapacitor
CATALOG NUMBER	XL60-2R9348W-R
UPC	051712707916
PRODUCT HEIGHT	138 mm
PRODUCT WEIGHT	525 g
COMPLIANCES	RoHS Compliant



ТҮРЕ	Single cell
CAPACITANCE	3400 F
PACKING	Bulk
SIZE	60 x 138 mm
TERMINALS	W-terminal
SHAPE	Cylindrical
DC EQUIVALENT SERIES RESISTANCE (ESR)	0.23 mΩ
OPERATING TEMPERATURE RANGE	-40 °C to +65 °C
SERIES	XL60
MAX VOLTAGE	2.85 V
CAPACITANCE	3400 F
LEAKAGE	8 mA
THERMAL RESISTANCE	3.2 °C/W
ENERGY	13680 J
POWER	8.8 kW
PEAK CURRENT (1 SEC)	2700 A
CONTINUOUS CURRENT (15 °C RISE)	143 A
CAPACITANCE END OF LIFE RATING	80%
ESR END OF LIFE RATING	200%
GRADE	Industrial

BROCHURES	Eaton supercapacitors provide reliable start-up for engine design
	Eaton's electronics components portfolio overview brochure
CROSS REFERENCES	Eaton - Maxwell supercapacitor cross reference guide
MANUALS AND USER GUIDES	XL60 Supercapacitor terminal connection quide
	XL60 Technical note: Integration kit and assembly instructions
PRODUCT NOTIFICATIONS	(PCN16044) Supercapacitors definition of the -R part number suffix change
	(PCN15011m) Shipping box and external and internal label update
	(PCN21022) XL60 Vent Change

PROJECT NAME:
PROJECT NUMBER:
PREPARED BY:
DATE:



Eaton Corporation plc

Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

© 2025 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Follow us on social media to get the latest product and support information.

All other trademarks are property of their respective owners.







