

Part Number: 2181011031

Product Description: Micro-Lock Plus-to-Micro-Lock Plus Off-the-Shelf (OTS) Cable Assembly, 2.00mm Pitch, Single Row, 100.00mm Length, 3 Circuits, Black

Series Number: 218101

Status: Active

Product Category: Power and Signal Cable

Assemblies



Documents & Resources

Drawings

2181011031_sd.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	©
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2- 21
REACH SVHC	Not Contained per D(2024)7663-DC (21 Jan 2025)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Power and Signal Cable Assemblies
Series	218101
Description	Micro-Lock Plus-to-Micro-Lock Plus Off-the-Shelf (OTS) Cable Assembly, 2.00mm Pitch, Single Row, 100.00mm Length, 3 Circuits, Black
Assembly Configuration	Dual Ended Connectors
Connector to Connector	Micro-Lock Plus Both Ends
Product Name	Micro-Lock Plus
Туре	Discrete Wire Assembly
UPC	195842350168

Electrical

Current - Maximum per Contact	3.0A
Voltage - Maximum	250V AC (RMS)/DC

Physical

Cable Length 100.00mm Circuits (Loaded) 3 Circuits (maximum) 3 Color - Resin Black Gender Female-Female Lock to Mating Part Yes Material - Metal Copper Alloy Material - Plating Mating Tin Material - Resin Polyester		
Circuits (maximum) Color - Resin Black Gender Female-Female Lock to Mating Part Yes Material - Metal Material - Plating Mating Tin Material - Plating Termination Tin	Cable Length	100.00mm
Color - Resin Black Gender Female-Female Lock to Mating Part Yes Material - Metal Copper Alloy Material - Plating Mating Tin Material - Plating Termination Tin	Circuits (Loaded)	3
Gender Female-Female Lock to Mating Part Yes Material - Metal Copper Alloy Material - Plating Mating Tin Material - Plating Termination Tin	Circuits (maximum)	3
Lock to Mating Part Material - Metal Material - Plating Mating Material - Plating Termination Tin	Color - Resin	Black
Material - Metal Copper Alloy Material - Plating Mating Tin Material - Plating Termination Tin	Gender	Female-Female
Material - Plating Mating Tin Material - Plating Termination Tin	Lock to Mating Part	Yes
Material - Plating Termination Tin	Material - Metal	Copper Alloy
	Material - Plating Mating	Tin
Material - Resin Polyester	Material - Plating Termination	Tin
	Material - Resin	Polyester
Net Weight 2.009/g	Net Weight	2.009/g
Number of Rows 1	Number of Rows	1
Packaging Type Bag	Packaging Type	Bag
Pitch - Mating Interface 2.00mm	Pitch - Mating Interface	2.00mm
Single Ended No	Single Ended	No

Termination Interface Style	Crimp or Compression
Wire/Cable Type	UL 10002
Wire Insulation Diameter	0.90-1.50mm
Wire Size (AWG)	22

This document was generated on Mar 26, 2025