

Productname : PROPOWER CONTACT CLEANER
Creationdate : 12.01.09
Ref.Nr.: UK10432-3-120109
Replaces: 20.02.08

1. IDENTIFICATION OF PRODUCT AND COMPANY

Productname : PROPOWER CONTACT CLEANER
Aerosol

Application : Cleaners - Precision

Company : PROPOWER Premier Farnell plc
150 Armley Road
LEEDS LS12 2QQ
Tel. : +44 (0) 870 129 8608
Fax :

In case of emergency : +44 (0) 8447 880088

2. HAZARD IDENTIFICATION

Health and Safety : Extremely Flammable
Repeated exposure may cause skin dryness or cracking.

Environment : May cause long-term adverse effects in the aquatic environment.

Other hazards : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.

3. COMPOSITION AND INFORMATION ON COMPONENTS

Hazardous ingredient	CAS-nr	EINECS	w/w %	symbol	R-phrases*	Notes
Hydrocarbons,C3-4-rich, petroleum distillate Petroleumgas (1,3-butadiene < 0.1%)	68512-91-4	270-990-9	30-60	F+	12	K
Alkanes (C9-12, iso)	90622-57-4	292-459-0	30-60	Xn	53-65-66	
Explanation notes						
K : not classified as carcinogen, less than 0.1% w/w 1,3-butadiene (Einecs-nr. 203-450-8)						

(* Explanation risk-phrases : see chapter 16)

4. FIRST AID MEASURES

General Advice : The usual precautions for handling chemicals should be observed
If any symptoms should occur, seek medical advice.

Contact with eyes : If substance has got into eyes, immediately wash out with plenty of water

Contact with skin : Wash with water and soap.

Inhalation : Fresh air, keep warm and at rest.

Productname :	PROPOWER CONTACT CLEANER	Creationdate :	12.01.09
Ref.Nr.:	UK10432-3-120109	Replaces:	20.02.08

Ingestion : Ingestion is unlikely to occur
If swallowed accidentally, do not induce vomiting and seek medical advice.

5. FIRE-FIGHTING MEASURES

Flash point (without propellant): 41 °C
Explosion limits : upper limit : 9.4 %
lower limit : 0.6 %
Extinguishing media : foam, carbon dioxide or dry agent
Fire-fighting procedures : Keep container(s) exposed to fire cool, by spraying with water
Unusual exposure hazard : Aerosols may explode if heated above 50°C

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Shut off all ignition sources
Ensure adequate ventilation
Environmental precautions : Do not allow to enter public sewers and watercourses
If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities
Cleaning methods : Absorb spillage in suitable inert material

7. HANDLING AND STORAGE

Handling procedures : Use only in well ventilated areas
Do not pierce or burn aerosols, even after use.
Do not spray on a naked flame or incandescent material.
Do not breathe aerosols or vapours.
Avoid contact with skin and eyes.
Storage procedures : Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C.
Keep in a cool, dry, well ventilated place
Keep out of reach of children.

8. EXPOSURE CONTROL AND PERSONAL PROTECTION

Control procedures : Ensure adequate ventilation
Keep away from heat and sources of ignition
Personal protection : It is advisable to take precautions to avoid contact with skin and eyes when handling the product.
Use only in well ventilated areas
inhalation : In case of insufficient ventilation, wear suitable respiratory equipment.
hands and skin : Wear suitable protective gloves (nitrile)
eyes : Wear safety goggles.

Productname :	PROPOWER CONTACT CLEANER	Creationdate :	12.01.09
Ref.Nr.:	UK10432-3-120109	Replaces:	20.02.08

9. PHYSICAL AND CHEMICAL PROPERTIES (for aerosols without propellant)

Apperance : physical state :	propane/butane propelled liquid
colour :	colourless
odour :	solvent
Boiling point/range :	153 °C
Relative density :	0.748 g/cm ³ (@ 20°C)
pH :	not available
Vapour pressure :	not available
Relative vapour density :	not available
Solubility in water :	Insoluble in water
Flash point :	41 °C
Auto-ignition :	> 200 °C
Viscosity :	not available
Evaporation rate :	not available

10. STABILITY AND REACTIVITY

Conditions to be avoided :	Pressurized container : protect from sunlight and do not expose to temperatures exceeding 50°C. Keep away from heat and sources of ignition No hazardous reactions known if used for its intended purpose
Materials to be avoided :	Strong oxidising agent
Hazardous decomposition compounds :	carbon oxides

11. TOXICOLOGICAL INFORMATION

Inhalation :	Inhalation of solvent vapours may give rise to nausea, headaches and dizziness
Ingestion :	Ingestion is unlikely to occur After vomiting of swallowed product aspiration into lungs is likely. Solvents may induce chemical pneumonia.
Skin contact :	Prolonged skin contact will result in defatting of the skin
Eye contact :	Irritating to eyes
Other information:	No experimental data available

12. ECOLOGICAL INFORMATION

Other adverse effects :	May cause long-term adverse effects in the aquatic environment. Do not allow to enter public sewers and watercourses If polluted water reaches drainage systems or water courses, immediately inform appropriate authorities
--------------------------------	--

Productname :	PROPOWER CONTACT CLEANER	Creationdate :	12.01.09
Ref.Nr.:	UK10432-3-120109	Replaces:	20.02.08

No experimental data available

13. WASTE DISPOSAL

National regulations : Disposal should be in accordance with local, state or national legislation

14. TRANSPORT

UN-number :	1950
Road/Rail - ADR/RID :	UN1950 Aerosols Class : 2, PG : NA, Class code : 5F, Label : 2.1
Sea - IMDG :	UN1950 Aerosols Ltd Qty Class : 2.1, PG : NA, Label : 2.1
EmS	F-D,S-U
Air - IATA/ICAO :	UN1950 Aerosols, flammable Class : 2.1, PG : NA, Label : RFG
Packing instr. LQ	Y203
PAX	203
CAO	203

15. REGULATORY INFORMATION

Warning symbol(s) : F+

Risk-phrase(s) : R12: Extremely flammable.
R53: May cause long-term adverse effects in the aquatic environment.
R66: Repeated exposure may cause skin dryness or cracking.

Safety-phrase(s) : S2: Keep out of the reach of children.
S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe spray.
S37: Wear suitable gloves.
S51: Use only in well-ventilated areas.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Regulation (EC) No 648/2004 on detergents: aliphatic hydrocarbons > 30 %

Productname :	PROPOWER CONTACT CLEANER	Creationdate :	12.01.09
Ref.Nr.:	UK10432-3-120109	Replaces:	20.02.08

16. OTHER INFORMATION

This product should be stored, handled and used in accordance with good industrial hygiene practices and in conformity with any legal regulation.

The information contained herewith is based on the present state of our knowledge and is intended to describe our products from the point of view of safety requirements. It does not guarantee any specific properties.

Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission.

REVISIONS IN CHAPTRE : 8,9

***Explanation risk-phrases:**

R10: Flammable.

R12: Extremely flammable.

R53: May cause long-term adverse effects in the aquatic environment.

R65: Harmful: may cause lung damage if swallowed.

R66: Repeated exposure may cause skin dryness or cracking.