multicomp PRO



Applications

- IP67/NEMA6
- Robust
- Wide Temp. Range
- High Wind Speed Resistant

RoHS Compliant

Features

Embedded Omni Antenna:

- 2x Multi-band 4G/LTE antenna
- 1x Dual-band Wi-Fi antenna
- Antenna Interface : 2 x SMA, 1 x RPSMA.

Electronic Enclosure:

- · Material : High impact, UV resistant outdoor enclosure
- IP67 / NEMA6 water and dustproof
- Power: PoE RJ45 Cat5 gland (excluding ethernet cable)
- Temperature Range: -20°C to +70°C
- Humidity: 95% @ 55°C
- Gore® External Temperature Vent
- Weight: 860g (not including Router)
- Fast Slide-In mounting bracket (fixed/pole, vertical/horizontal pole) SUS304 stainless steel + corrosion resistant

LTE Antenna Specification

Frequency	: 698-960 / 1710-2170 / 2300-2690 MHz
Efficiency	: 43%-78%
Peak Gain	: 6.1 dBi
Output Impedance	: 50Ω
Output V.S.W.R	: 2.5~3 typ.

WiFi Antenna Specification

Frequency: 2400-Efficiency: 66%-Peak Gain: 6.2 dfOutput Impedance: 50ΩOutput V.S.W.R: 2 typ.

: 2400-2500/5150-5850 MHz : 66%-77% : 6.2 dBi

VSWR: LTE

Frequency(MHz)	ANT 02	Frequency(MHz)	ANT 02	Frequency(MHz)	ANT 02
698	2.9	1710	1.9	2300	1.3
960	1.8	2170	1.5	2690	1.2
698-960 MAX	2.9	1710-2170 MAX.	1.9	2300-2690 MAX	2.1





VSWR: WiFi

Frequency(MHz)	ANT 03	Frequency(MHz)	ANT 03
2400	1.7	5150	1.7
2500	2	5850	1.8
2400-2500 Max.	2.1	5150-5850 Max.	1.8



Gain Table : LTE

ANT 01			
Frequency	3D		
(MHz)	Efficiency	Avg. Gain	Peak Gain
698	46%	-3.4	1.2
704	49%	-3.1	1.9
746	45%	-3.5	2.1
760	49%	-3.1	2.1
787	58%	-2.4	3.0
791	61%	-2.2	3.5
824	60%	-2.2	3.9
836	56%	-2.5	3.4
849	57%	-2.5	3.0
869	51%	-2.9	1.9
880	45%	-3.5	1.6
894	43%	-3.6	1.5
900	44%	-3.6	1.4
915	50%	-3.0	2.3
925	56%	-2.6	2.7
940	61%	-2.1	2.9
960	67%	-1.8	3.1

ANT 01				
Frequency	3D			
(MHz)	Efficiency	Avg. Gain	Peak Gain	
1710	66%	-1.8	4.6	
1750	68%	-1.7	4.7	
1785	70%	-1.6	5.2	
1805	72%	-1.4	5.5	
1840	74%	-1.3	5.7	
1850	74%	-1.3	5.7	
1880	73%	-1.4	5.3	
1910	70%	-1.5	5.2	
1920	70%	-1.5	5.0	
1930	72%	-1.4	4.9	
1950	72%	-1.4	4.5	
1960	73%	-1.4	4.4	
1980	73%	-1.4	4.0	
1990	74%	-1.3	3.8	
2110	74%	-1.3	6.1	
2140	75%	-1.3	5.5	
2170	76%	-1.2	5.3	



multicomp PRO

ANT 01			
Frequency	3D		
(MHz)	Efficiency	Avg. Gain	Peak Gain
2300	76%	-1.2	5.9
2400	71%	-1.5	5.4
2500	52%	-2.8	2.5
2570	53%	-2.8	2.4
2595	68%	-1.7	3.3
2600	70%	-1.5	3.4
2620	75%	-1.2	3.6
2690	78%	-1.1	3.8
2700	78%	-1.1	4.1

Gain Table : WiFi

ANT 01			
Frequency	3D		
(MHz)	Efficiency	Avg. Gain	Peak Gain
2400	66%	-1.8	3.3
2450	67%	-1.7	3.9
2500	68%	-1.7	4.4

ANT 01				
Frequency	3D			
(MHz)	Efficiency	Avg. Gain	Peak Gain	
5150	69%	-1.6	5	
5200	70%	-1.5	5.2	
5250	74%	-1.3	5.6	
5300	76%	-1.2	5.5	
5350	77%	-1.1	5.3	
5470	75%	-1.2	5.2	
5600	77%	-1.1	5.9	
5725	77%	-1.2	5.5	
5800	77%	-1.2	6	
5850	76%	-1.2	6.2	

3D Radiation Pattern: LTE





multicomp PRO



3D Radiation Pattern: WiFi



Part Number Table

Description	Part Number
4G LTE and Wi-Fi Embedded Omni Antenna	MP015783

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

