4 Channel Handheld Digital Storage Oscilloscopes Multicomp



Features

- RoHS Compliant
- · Max 100MHz Bandwidth, 1GS/s sample rate
- · Max 14-bit high resolution ADC
- Max 40M record length; max 45000 wfms/s waveform refresh rate
- low back ground noise
- 8 inch 800 × 600 high resolution LCD, multi-touch screen, more user-friendly operation experience
- · SCPI, and LabVIEW supported
- · multi- trigger, and bus decoding function
- multi-interface integration USB host, USB device,LAN, Wifi(optional)

Characteristics	MP720775	MP720645	MP720776	
Bandwidth	70MHz	100MHz		
Sample Rate	1GS/s	-		
Vertical Resolution (A/D)	8 bits		8bits/12bits/14 bits	
Record length	40M			
Waveform Refresh Rate	45,000 wfms/s			
Horizontal Scale (s/div)	1ns/div - 1000s/div	1ns/div - 1000s/div, step by 1 - 2 - 5		
Channel	4	4		
Display	8" colour LCD, 800	8" colour LCD, 800 × 600 pixels display, multi-touch screen		
Input Impedance	1MΩ ± 2%, in para	1M Ω ± 2%, in parallel with 15pF ±5pF		
Max Input Voltage	1MΩ ≤ 300Vrms;	1MΩ ≤ 300Vrms;		
Probe Attenuation Factor	0.001X - 1000X, s	0.001X - 1000X, step by 1 - 2 - 5		
Input Coupling	DC, AC, GND			
Vertical Sensitivity	1mV/div - 10V/div	1mV/div - 10V/div (at input)		
Trigger Type		Edge, Video, Pulse, Slope, Runt, Windows, Timeout, Nth Edge, Logic, I2C, SPI, UART(RS232), and CAN (optional)		
Bus Decoding(optional)	I2C, SPI, RS232,	I2C, SPI, RS232, CAN		
Trigger Mode	Auto, Normal, and	Auto, Normal, and Single		
Automatic Measurement	Vpp, Vavg, Vrms, Freq, Period, Week RMS, Cursor RMS, Vmax, Vmin, Vtop, Vbase, Vamp, Overshoot, Phase A→B↑, Phase A→B↓, Preshoot, Rise Time, Fall Time,+Width, -Width, +Duty, -Duty, Duty Cycle, Delay A→B↑, Delay A→B↓, +Pulse Count, -Pulse Count, Rise Edge Count, Fall Edges Count, Area, Cycle Area			
Waveform Math	+, -, ×, ÷, FFT, FF	+, -, ×, ÷, FFT, FFTrms,Intg,Diff,Sqrt, User Defined Function, Digital Filter		
Waveform Storage	100 waveforms	100 waveforms		
Communication Interface	USB host, USB de	USB host, USB device, USB port for PictBridge,LAN, and WIFI (optional)		
Frequency Counter	Available			
Battery	7.4V, 8000mAh, 5	7.4V, 8000mAh, 5 hours operation		
Dimension (W × H × D)	270mm × 191mm × 48mm			
Device Weight	About 1.7kg	About 1.7kg		

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



4 Channel Handheld Digital Storage Oscilloscopes Multicomp PRO

Standard Warranty: 03 years



UK/EU/ US Power Cord



Power Supply Adapter



Probe



CD Rom



Manual



USB



Probe adjust



Frame



Current Ext Module



BNC-SAN



Test Leads



Standard Bag

Part Number Table

Description	Part Number
Handheld Digital Storage Oscilloscope, 4 Channel, 8-Bits, 70MHz, 1GS/s	MP720775
Handheld Digital Storage Oscilloscope, 4 Channel, 8-Bits, 100MHz, 1GS/s	MP720645
Handheld Digital Storage Oscilloscope, 4 Channel, 14-Bits, 100MHz, 1GS/s	MP720776
Handheld Digital Storage Oscilloscope, 4 Channel, 8-Bits, 100MHz, 1GS/s	MP720645 US

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro



Page <2> 07/07/25 V1.2