# PU610 AS&PU610DG AS

## DESCRIPTION

- Industrial protective glove.
- Synthetic coating on a synthetic textile liner.
- 2 versions available :
- Palm fit coating (PU610AS)
- Finger tips coating (PU610 DG AS)
- Elastic knit wrist to ensure snug fit.
- 5 sizes available: 6, 7, 8, 9 and 10.
- Trade unit: 12 pairs, 240 pairs in a transit case.

## **CHARACTERISTICS**

- Glove knitted with a seamless non-stop process.Textile liner made of high-tenacity polyamid
- continuous thread, included copper.
- Fine and stretchable stitches for an excellent comfort.
- Stretchable polyurethane coating.

#### PERFORMANCES

- Excellent comfort and dexterity.
- Antistatic properties as the finished material offers the user hand protection against electrostatic discharge.
- Low lint glove.
- In compliance with standards EN420 (General requirements), EN388 (Mechanical Hazards) and pr 1149-5 (Protective clothes, Antistatic properties) by the notified laboratory IFTH, Institut Français Textile Habillement.

### **APPLICATIONS**

 Ideal for fine tactile handling, light assembly, electronics industry and photographic laboratory where there is a risk of electrostatic discharge.

#### LIMITATIONS

- Do not use for handling liquids and pointed objects.
- Do not use with a rotating machine in which glove may get caught.
- Limited protection at the wrist.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21rst, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



F



1			



2 Tear 1 Puncture

5 Dexterity

3 Abrasion

EN 388

Order codes 10 (XL) Sizes 6 (XS) 7 (S) 8 (M) 9 (L) PU610 AS 1811E45072 1811E41072 1811E42072 1811E43072 1811E44072 PU610DG AS 181CE45072 181CE41072 181CE42072 181CE43072 181CE44072









• •