

M12 Sensor Cable Assembly

Female M12 - Male M12

multicomp^{PRO}

Actuator and Sensor Cable, PUR – Extension Cable, M12, D-coding

**RoHS
Compliant**



Features

- Female M12, straight, 4-pin
- Male M12, straight, 4-pin
- Jacket material: PUR
- Jacket color: green
- Resistant to chemicals and oils
- Flame-retardant
- Resistance to welding sparks
- Resistant to salt spray
- Approval: CE
- Protection class: IP67
- Cable length: 1m

Technical Data

Connector A

Connector	: Female, M12 × 1, Straight, D-coded
Number of Pins	: 4
Contacts	: Brass, Gold-plated
Contact Carriers	: PA
Coupling Nut/screw	: Brass, Nickel-plated
Connector body	: PUR
Seal	: FKM
Mechanical lifespan	: ≥100 Mating cycles
Pollution degree	: 3
Protection Class	: IP67, (screwed together)
Locking mode	: Screw
Standard	: IEC 61076-2

Connector B

Connector	: Male, M12 × 1, Straight, D-coded
Number of Pins	: 4
Contacts	: Brass, Gold-plated
Contact Carriers	: PA
Coupling Nut/screw	: Brass, Nickel-plated
Connector body	: PUR Black
Locking mode	: Screw
Mechanical lifespan	: ≥100 Mating cycles
Pollution degree	: 3
Protection Class	: IP67, (screwed together)
Standard	: IEC 61076-2

Cable

Cable diameter	: Ø 6.5mm ± 0.3mm
Cable length	: 1m
Cable jacket	: PUR, Green

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp^{PRO}

M12 Sensor Cable Assembly

Female M12 - Male M12

multicompPRO

Core insulation : PVC
Core cross-section : 4 × 0.34mm²
Core colours : 1-YE, 2-WH, 3-OR, 4-BU


Electrical properties at +20°C

Rated Voltage : 250V
Contact resistance : ≤ 5 mΩ
Current : 4A
Insulation resistance : ≥10⁸Ω
Max. Conductor resistance : max. 55.4 Ω/km


Mechanical and chemical properties

Bending radius (stationary installation) : ≥ 5 x Ø
Bending radius (flexible use) : ≥ 10 x Ø
Ambient temperature range (stationary) : -25°C to 80°C
Ambient temperature range (In motion) : -5°C to 80°C
Approvals : CE

Contact assignment



Diagram



Circuit Diagram

CN A	Core colors	CN B
1	YE	1
2	WH	2
3	OR	3
4	BU	4

Dimensions : Millimetres

Part Number Table

Description	Part Number
M12 Sensor Cable, Female M12 to Male M12, PUR, D-Coding, 4 Pins, 1m	MP011276

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicompPRO