# M12 Sensor Connector A-Coded



Receptacle rear mounted, M12, A-Coding, 5-Pin



#### **Features**

M12, Female, 5-Pin
Resistant to salt spray
Protection Class: IP67
Approval: CE

Approval: CECable length: 0.3m

# RoHS Compliant

#### **Technical Data**

Connector

Connector A : Female, M12x1, A-coding

Number of Pins : 5

Contacts : Brass, Gold-plated Copling Nut/screw : Brass, Nickel-plated

Contact Carriers : PA Seal : FKM

Mounting orientation : Rear mount
Mounting thread : M16 × 1.5

Mechanical lifespan : ≥100 Mating cycles

Pollution degree : 3

Protection Class : IP67, (screwed together)

Locking mode : Screw Cable length : 0.3m

Core colours : 1-BN, 2-WH, 3-BU, 4-BK, 5-GY

Core insulation : PVC

Core cross-section :  $5 \times 0.34$ mm<sup>2</sup> Locking mode : Screw

Connection mode : Wire connection Standard : IEC 61076-2

**Electrical properties** 

 Rated Voltage
 : 60V

 Current
 : 4A

 Insulation resistance
 : ≥10 $^8$ Ω

#### **Mechanical and Chemical Properties**

Ambient temperature range (stationary) : -40°C to 80°C

## **Contact assignment**




#### **Connection diagram**

CNI		Core colors
1		BN
2		WH
3		BU
4		BK
5	-	GY

## Diagram





Dimensions: Millimetres

#### Part Number Table

Description	Part Number
M12 Sensor Connector, Receptacle, Rear Mount, A-Coded, 5 Pins	MP011278

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro



Page <1> 21/08/25 V1.1