



Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 1 / 14

Replaced revision:32 (Dated 30/04/2024)

(Somerset)

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name SILCOSET 153

UFI: DD5F-R087-E00T-JE7S

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use Adhesive sealant.

1.3. Details of the supplier of the safety data sheet

Name CHT UK BRIDGWATER LTD

Full address Amber House Showground Road
District and Country TA6 6AJ Bridgwater

England

Tel. +44(0)1278411400

Fax +44(0)1278411444

e-mail address of the competent person

responsible for the Safety Data Sheet info.uk@cht.com

Supplier: CHT Germany GmbH

Bismarckstraße 102 72072 Tübingen Germany

1.4. Emergency telephone number

For urgent inquiries refer to +1-703-527-3887 CHEMTREC (International, 24 hours) (CCN 1014369)

+44 20 3807 3798 CHEMTREC (United Kingdom, 24 hours)

+353 1 901 4670 CHEMTREC (Ireland, 24 hours) +61 2 9037 2994 CHEMTREC (Australia, 24 hours)

+64 9-801 0034 CHEMTREC (New Zealand, 24 hours)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1 H318 Causes serious eye damage. Skin irritation, category 2 H315 Causes skin irritation.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:







Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 2 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 2. Hazards identification

Signal words: Danger

Hazard statements:

H318 Causes serious eye damage. H315 Causes skin irritation

EUH208 DIMETHYLTIN NEODECANOATE

May produce an allergic reaction.

Precautionary statements:

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P280 Wear protective gloves / eye protection / face protection. Immediately call a POISON CENTER / doctor / . . . P310

P264 Wash . . . thoroughly after handling.

Contains: METHYLSILANETRIYL-TRIACETATE

DIACETOXYDI-TERT-BUTOXYSILANE

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

METHYLSILANETRIYL-TRIACETATE

Acute Tox. 4 H302, Skin Corr. 1B H314, Eye Dam. 1 H318, EUH014 **INDEX** $2.5 \le x < 3$

EC 224-221-9 ATE Oral: 500 mg/kg

CAS 4253-34-3

REACH Rea. 21-2119987097-22 **DIACETOXYDI-TERT-BUTOXYSILANE**

INDEX $1.5 \le x < 2$ Skin Corr. 1B H314, Eye Dam. 1 H318 EC 236-112-3

CAS 13170-23-5 REACH Reg. 01-2119987098-20 **OCTAMETHYLCYCLOTETRASILOXANE**

INDEX $0.025 \le x < 0.1$ Repr. 2 H361f, Aquatic Chronic 1 H410 M=10

209-136-7 FC CAS 556-67-2

REACH Reg. 01-2119529238-36

ACETIC ACID

607-002-00-6 Flam. Liq. 3 H226, Skin Corr. 1A H314, Eye Dam. 1 H318, Classification note 0 < x < 0.1INDFX

according to Annex VI to the CLP Regulation: B

FC 200-580-7 CAS 64-19-7

REACH Reg. 01-2119475328-30





SILCOSET 153

Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 3 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 3. Composition/information on ingredients/>

DIMETHYLTIN NEODECANOATE

INDEX 0 < x < 0.1 Repr. 2 H361d, Acute Tox. 4 H302, STOT RE 1 H372, Skin Irrit. 2 H315, Skin

Sens. 1A H317, Aquatic Chronic 3 H412

EC 273-028-6 LD50 Oral: 890 mg/kg

CAS 68928-76-7 REACH Reg. 01-2120770324-57

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. In the event of respiratory symptoms (coughing, wheezing, breathing difficulty, asthma) keep the victim in a comfortable position for breathing. If necessary administer oxygen. If the subject stops breathing, administer artificial respiration. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS



Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 4 / 14

aced revision:32 (Dated 30/04/2024)

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

We recommend, that once opened, the product is used and is not stored

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 18. října 2023, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe
DNK	Danmark	BEK nr 291 af 19/03/2024 (Historisk) Bekendtgørelse om grænseværdier for stoffer og materialer (kemiske agenser) i arbejdsmiljøet
ESP	España	Límites de exposición profesional para agentes químicos en España 2024
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők hatásának kitett munkavállalók egészségének és biztonságának védelméről
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og



Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 5 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 8. Exposure controls/personal protection ...

		grenseverdier), 21. 10. april 2024 kl. 13.55
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei2024, nr.
		2024-0000092805, tot wijziging van deArbeidsomstandighedenregeling in verband met de
		implementatie vanRichtlijn 2022/431
PRT	Portugal	Decreto-Lei n.º 102/2024, de 4 de dezembro. Sumário: Transpõe para a ordem jurídica interna a
		Diretiva (UE) 2022/431, relativa à proteção dos trabalhadores contra riscos ligados à exposição a
		agentes cancerígenos ou mutagénicos e procede à quarta alteração
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24
		czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i
		natężeń czynników szkodliwych dla zdrowia w środowisku pracy
ROU	România	HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea şi completarea Hotărârii Guvernului
		nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția
		lucrătorilor împotriva riscurilor legate de expunerea la agenți ca
RUS	Россия	ПОСТАНОВЛЕНИЕ от 13 февраля 2018 г. N 25 ОБ УТВЕРЖДЕНИИ ГИГИЕНИЧЕСКИХ
		НОРМАТИВОВ ГН 2.2.5.3532-18 "ПРЕДЕЛЬНО ДОПУСТИМЫЕ КОНЦЕНТРАЦИИ (ПДК)
		ВРЕДНЫХ ВЕЩЕСТВ В ВОЗДУХЕ РАБОЧЕЙ ЗОНЫ"
SWE	Sverige	Arbetsmiljöverkets föreskrifter och allmänna råd (AFS 2023:14) om gränsvärden för
		luftvägsexponering i arbetsmiljön
SVK	Slovensko	121_2024 Z. z. Nariadenie vlády o ochrane zdravia zamestnancov pred rizikami súvisiacimi s
		expozíciou karcinogénnym, mutagénnym alebo reprodukčne toxickým faktorom pri práci
TUR	Türkiye	Kimyasal Maddelerle Çalışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik
000	11. % 112: 1	12.08.2013 / 28733; 20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU)
		2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive
		2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive
	400111	91/322/EEC.
	ACGIH	ACGIH 2025

DIACETOXYDI-TER	T-BUTOXYSILANE
Predicted no-effect concentration - PNEC	
Normal value in fresh water	0.02875 mg/l
Normal value in marine water	0.02875 mg/l
Normal value for fresh water sediment	0.03279 mg/kg/d
Normal value for marine water sediment	0.00327 mg/kg/d
	9
Normal value of STP microorganisms	13.276 mg/l
Health - Derived no-effect level - DNEL / DMEL	

	Effects or	n consumers			Effects on workers				
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic	
	local	systemic	local	systemic	local	systemic	local	systemic	
Oral			VND	10.69					
				mg/kg bw/d					
Inhalation			VND	37.2			VND	150.84	
				mg/m3				mg/m3	
Skin			VND	10.69			VND	21.39	
				mg/kg bw/d				mg/kg	
								bw/d	



Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 6 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 8. Exposure controls/personal protection .../>>

Effects on consumers

Acute

systemic

Chronic

local

VND

5.1

mg/m3

VND

Chronic

systemic

6.3

7.2

mg/m3

mg/kg/d

mg/kg bw/d

Acute

local

Route of exposure

Oral

Skin

Inhalation

	Value	T) A / A / O !-			TEL /45				. 4	
ype	Country	TWA/8h			STEL/15min		Remai	ks / Observa	ations	
CIAI	DEU	mg/m3	ppm	r	ng/m3	ppm				
GW LV		0.004 0.1	0.02				CIZINI			
LV LA	DNK ESP	0.1			0.2		SKIN			
					0.2					
LEP ITP	FRA FIN	0.1			0.2		SKIN			
							SKIN			
LV LE	NOR	0.1			0.3 0.2		SKIN			
/EL	PRT GBR	0.1			0.2		CIZINI			
							SKIN			
		ation - PNEC						0.016		
lormal value i									mg/l	
ormal value i								0.002	mg/l	
	or fresh wate							1.135	mg/kg/d	
ormal value f			.4					0.113 0.16	mg/kg/d	
		ter, intermitte						0.16	mg/l	
		r, intermittent	release					100	mg/l	
lormal value o								0.069	mg/l	
		nain (seconda rel - DNEL / D		9)				0.069	mg/kg	
itn - Derivea		cts on consun				⊏ffooto	on worke			
lauta of overa				Chronic	Chronic		S OII WOIKE	Acute	Chronic	Chronic
oute of expos	sure Acu loca			local	systemic	Acute		systemic	local	systemic
ral	luca	ı Syste	HIIC	local	Systemic	iocai		Systemic	local	0.02
halation										0.02
										mg/m3
kin										0.03
										mg/kg
										bw/d
			ME	THYLSILAN	IETRIYL-TRIA	CETATE				
licted no-effe	ect concentra	ation - PNEC								
lormal value i	n fresh water							1	mg/l	
lormal value i	n marine wate	er						0.1	mg/l	
ormal value f	or fresh wate	r sediment						3.4	mg/kg	
	or marine wa	ter sediment						0.34	mg/kg	
ormal value f								10		
		rmittent releas	se					10	mg/l	

Effects on workers

Acute

systemic

Chronic

local

31

mg/kg

VND

Chronic

systemic

25

mg/m3

14.5

mg/kg bw/d

Acute

local



Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 7 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 8. Exposure controls/personal protection .../>>

				ACETIC ACII	ס	
hreshold Limit \	Value					
Type	Country	TWA/8h		STEL/15mi	n	Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	25	10	50	20	
AGW	DEU	25	10	50	20	
MAK	DEU	25	10	50	20	
TLV	DNK	25	10	50	20	E
VLA	ESP	25	10	50	20	
VLEP	FRA	25	10	50	20	
HTP	FIN	13	5	25	10	
AK	HUN	25	10	50	20	
VLEP	ITA	25	10	50	20	
TLV	NOR	25	10	50	20	
TGG	NLD	25		50		
VLE	PRT	25	10	50	20	
NDS/NDSCh	POL	25	10	50	20	
TLV	ROU	25	10	50	20	
ПДК	RUS			5		П
NGV/KGV	SWE	13	5	25	10	
NPEL	SVK	25	10	50	20	
ESD	TUR	25	10	50	20	
WEL	GBR	25	10	50	20	
OEL	EU	25	10	50	20	
ACGIH		25	10	37	15	

		0.0	TABLETING ON	(OL OTETPAO	LOVANE			
			CTAMETHYLCY	CLOTETRAS	LOXANE			
Predicted no-effect cor	ncentration	- PNEC						
Normal value in mari	ne water					0.044	mg/l	
Normal value for fres	h water sedi	ment				0.128	mg/kg	
Normal value of STP	microorgani	isms				100	mg/l	
Normal value for the	terrestrial co	mpartment				0.16	mg/kg	
Health - Derived no-eff	ect level - D	NEL / DMEL						
	Effects or	consumers			Effects on v	vorkers		
Route of exposure	Acute	Acute	Chronic	Chronic	Acute	Acute	Chronic	Chronic
	local	systemic	local	systemic	local	systemic	local	systemic
Inhalation	61	305	61	305		-		-
	mg/m3	mg/m3	mg/m3	mg/m3				

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

Protect your hands with gloves of the following type:

Material: Nitrile rubber (NBR)

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Thickness: > 0.35 mm

The obtained break through times according to EN 374 Part III are not measured under normal operating conditions.

Breakthrough time: > 480 min

Therefore a maximum usage time of 50% of the break through time is recommended.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.



Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 8 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 8. Exposure controls/personal protection .../>>

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529. ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Value **Properties** Appearance paste colourless Colour Odour pungent Melting point / freezing point not available Initial boiling point not available Flammability not available Lower explosive limit not available not available Upper explosive limit 150 Flash point °C Auto-ignition temperature 400 Decomposition temperature not available рΗ not available Kinematic viscosity paste immiscible with water Solubility Partition coefficient: n-octanol/water not available Vapour pressure not available Density and/or relative density 1.05 not available Relative vapour density Particle characteristics not applicable

Information

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 0 % - 0 g/litre VOC (volatile carbon) 1.22 % - 12.86 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

Information not available

10.2. Chemical stability

Information not available

10.3. Possibility of hazardous reactions

The product may react violently with water.



Dated 13/08/2025 Printed on 13/08/2025 Page n. 9 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 10. Stability and reactivity .../>>

ACETIC ACID

Risk of explosion on contact with: chromium (VI) oxide,potassium permanganate,sodium peroxide,perchloric acid,phosphorus chloride,hydrogen peroxide. May react dangerously with: alcohols,bromine pentafluoride,chlorosulphuric acid,dichromate-sulphuric acid,ethane diamine,ethylene glycol,potassium hydroxide,strong bases,sodium hydroxide,strong oxidising agents,nitric acid,ammonium nitrate,potassium tert-butoxide,oleum. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Prevent moisture or water from penetrating inside the containers.

ACETIC ACID

Avoid exposure to: sources of heat,naked flames.

10.5. Incompatible materials

ACETIC ACID

Incompatible with: carbonates, hydroxides, phosphates, oxidising substances, bases.

10.6. Hazardous decomposition products

Information not available

SECTION 11. Toxicological information

Oral LD50 (Rat) >5000 mg/kg; Dermal LD50 (Rabbit) >2000 mg/kg.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: >2000 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

METHYLSILANETRIYL-TRIACETATE

ATE (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

OCTAMETHYLCYCLOTETRASILOXANE

LD50 (Dermal): > 2375 mg/kg Rat LD50 (Oral): 4800 mg/kg Rat, male

LC50 (Inhalation vapours): 36 mg/l/4h Rat, male and female

ACETIC ACID

 LD50 (Dermal):
 1060 mg/kg Rabbit

 LD50 (Oral):
 3310 mg/kg Rat

 LC50 (Inhalation vapours):
 11.4 mg/l/4h Rat





SILCOSET 153

Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 10 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 11. Toxicological information

DIMETHYLTIN NEODECANOATE

LD50 (Dermal): LD50 (Oral):

> 2000 mg/kg (Rabbit) 890 mg/kg (Rat)

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

DIMETHYLTIN NEODECANOATE

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

DIACETOXYDI-TERT-BUTOXYSILANE

LC50 - for Fish 192.34 mg/l/96h EC50 - for Algae / Aquatic Plants 28.75 mg/l/72h

OCTAMETHYLCYCLOTETRASILOXANE

LC50 - for Fish EC50 - for Crustacea EC10 for Algae / Aquatic Plants Chronic NOEC for Fish

Chronic NOEC for Crustacea

> 0.022 mg/l/96h Pseudokirchneriella subcapitata > 0.0044 mg/l Oncorhynchus mykiss

> 0.022 mg/l/96h Oncorhynchus mykiss

> 0.0015 mg/l Daphnia magna

0.015 mg/l/48h Daphnia magna

DIMETHYLTIN NEODECANOATE

LC50 - for Fish EC50 - for Crustacea EC50 - for Algae / Aquatic Plants > 1000 mg/l/96h Fathead minnows (Pimephales promelas)

39 mg/l/48h Daphnia 7.6 mg/l/72h Algae





Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 11 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 12. Ecological information .../>>

12.2. Persistence and degradability

DIACETOXYDI-TERT-BUTOXYSILANE

Rapidly degradable 79.5% Method: OECD 301 F, Exposure duration: 28 days

ACETIC ACID

Solubility in water > 10000 mg/l

Rapidly degradable

12.3. Bioaccumulative potential

ACETIC ACID

Partition coefficient: n-octanol/water -0.17

12.4. Mobility in soil

ACETIC ACID

Partition coefficient: soil/water 1.153

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

Waste Code: 08 04 09*

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

ΕN



CHT UK BRIDGWATER LTD SILCOSET 153

Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 12 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 14. Transport information .../>

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

Austrailia AICS: On or in compliance with the inventory.

Canada DSL Inventory List: On or in compliance with the inventory.

EINECS, ELINCS or NLP: On or in compliance with the inventory.

Japan (ENCS) List: On or in compliance with the inventory.

China Inv. Existing Chemical Substances: On or in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI): On or in compliance with the inventory.

Philippines PICCS: On or in compliance with the inventory.

US TSCA Inventory: On or in compliaince with the inventory.

New Zealand Inventory of Chemicals: On or in compliance with the inventory.

Taiwan Chemical Substance Inventory: On or in compliance with the inventory.

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

 Product
 3 - 40

 Point
 3 - 5

 Contained substance
 75

Point 70 OCTAMETHYLCYCLOTETRASILOXANE

REACH Reg.: 01-2119529238-36

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks





SILCOSET 153

Dated 13/08/2025 Printed on 13/08/2025 Page n. 13 / 14 Replaced revision:32 (Dated 30/04/2024)

SECTION 15. Regulatory information ... / >>

related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

German regulation on the classification of substances hazardous to water (AwSV, vom 18. April 2017)

WGK 1: Low hazard to waters

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 3 Flammable liquid, category 3 Repr. 2 Reproductive toxicity, category 2

Acute Tox. 4 Acute toxicity, category 4

STOT RE 1 Specific target organ toxicity - repeated exposure, category 1

Skin Corr. 1A
Skin Corr. 1B
Skin corrosion, category 1A
Skin Corrosion, category 1B
Eye Dam. 1
Skin Irrit. 2
Skin Irrit. 2
Skin Sens. 1A
Skin corrosion, category 1B
Skin corrosion, category 1B
Skin corrosion, category 1B
Skin corrosion, category 1A
Skin corrosion, category 1A

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1 Aquatic Chronic 3 Hazardous to the aquatic environment, chronic toxicity, category 3

H226 Flammable liquid and vapour.

H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H302 Harmful if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure.

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

EUH014 Reacts violently with water.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit



SILCOSET 153

Revision nr.33 Dated 13/08/2025 Printed on 13/08/2025 Page n. 14 / 14 laced revision:32 (Dated 30/04/2024)

SECTION 16. Other information

- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- 27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- FCHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

01 / 03 / 04 / 08 / 09 / 12 / 13 / 16.