

LOCTITE 266

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 30

SDS No.: 153615 V009.0

Revision: 06.11.2025

printing date: 07.11.2025

Replaces version from: 15.04.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE 266

UFI: NKXD-6WK5-K20W-RGNK

This mixture contains nanoforms

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Anaerobic Sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Specific target organ toxicity - single exposure Category 3

H335 May cause respiratory irritation.

Target organ: respiratory tract irritation

Chronic hazards to the aquatic environment Category 3

H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

SDS No.: 153615 LOCTITE 266 Page 2 of 30

V009.0

Hazard pictogram:



Contains N,N-(m-phenylene)dimaleimide

Hydroxypropyl methacrylate Cumene hydroperoxide

maleic acid

Acetic acid, 2-phenylhydrazide

Signal word: Warning

Hazard statement: H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation. H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment.

Prevention P280 Wear

P280 Wear protective gloves. P261 Avoid breathing vapors.

Precautionary statement: P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

Response P337+P313 If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None if used properly.

This product contains a substance that is classified as Acute Toxicity Category 2, Inhalation, in powder form. Experimental data show that this substance, as an ingredient in this mixture, is not biologically available according to CLP Art. 12 b.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

LOCTITE 266 Page 3 of 30

V009.0

SDS No.: 153615

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
EC No UK-REACH-Reg. No.				
N,N-(m-phenylene)dimaleimide 3006-93-7 221-112-8	10- < 20 %	Acute Tox. 4, Oral, H302 Skin Sens. 1A, H317 Acute Tox. 2, Inhalation, H330 Aquatic Chronic 2, H411	oral:ATE = 500 mg/kg	
Hydroxypropyl methacrylate 27813-02-1 248-666-3	5-< 10 %	Skin Sens. 1, H317 Eye Irrit. 2, H319		
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9 231-545-4	5-< 10 %	STOT RE 2, Inhalation, H373	dermal:ATE = > 5.000 mg/kg oral:ATE = > 5.000 mg/kg inhalation:ATE = > 5,01 mg/l;dust/mist	Nanoform
Cumene hydroperoxide 80-15-9 201-254-7	1-< 3 %	STOT RE 2, H373 Skin Corr. 1B, H314 Acute Tox. 2, Inhalation, H330 Aquatic Chronic 2, H411 Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Org. Perox. E, H242 STOT SE 3, H335	Eye Irrit. 2; H319; C 1 - < 3 % Skin Irrit. 2; H315; C 3 - < 10 % Eye Dam. 1; H318; C 3 - < 10 % STOT SE 3; H335; C >= 1 % Skin Corr. 1B; H314; C >= 10 % ===== dermal:ATE = 1.100 mg/kg	
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5 265-155-0	1-< 5 %	Asp. Tox. 1, H304		
N,N-Diethyl-p-toluidine 613-48-9 210-345-0	0,1-< 1 %	Acute Tox. 3, Oral, H301 Acute Tox. 3, Dermal, H311 Acute Tox. 3, Inhalation, H331 STOT RE 2, H373 Aquatic Chronic 3, H412 Skin Irrit. 2, H315	dermal:ATE = 300 mg/kg oral:ATE = 100 mg/kg inhalation:ATE = 3 mg/l;vapour	
maleic acid 110-16-7 203-742-5	0,1-< 1 %	Acute Tox. 4, Oral, H302 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315 Skin Sens. 1, H317 Acute Tox. 4, Dermal, H312	Skin Sens. 1; H317; C >= 0,1 %	
Acetic acid, 2-phenylhydrazide 114-83-0 204-055-3	0,1-< 1 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 4, Oral, H302 Skin Sens. 1, H317 Carc. 2, H351	M acute = 1 M chronic = 1	
N,N-dimethyl-o-toluidine 609-72-3 210-199-8	0,1-< 1 %	STOT RE 2, H373 Acute Tox. 3, Oral, H301 Acute Tox. 3, Dermal, H311 Acute Tox. 3, Inhalation, H331 Aquatic Chronic 3, H412	dermal:ATE = 300 mg/kg oral:ATE = 100 mg/kg inhalation:ATE = 0,5 mg/l;dust/mist	
methacrylic acid 79-41-4 201-204-4	0,1-< 1 %	Acute Tox. 4, Oral, H302 Acute Tox. 3, Dermal, H311 Acute Tox. 4, Inhalation, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	STOT SE 3; H335; C >= 1 % ====== dermal:ATE = 500 mg/kg inhalation:ATE = 3,19 mg/l;dust/mist	
1,4-Naphthalenedione	0,01-< 0,1 %	Acute Tox. 3, Oral, H301	M acute = 10	

V009.0

130-15-4	Skin Corr. 1C, H314	M chronic = 1	
204-977-6	Skin Sens. 1, H317		
	Eye Dam. 1, H318		
	Acute Tox. 1, Inhalation, H330		
	STOT SE 3, H335		
	Aquatic Acute 1, H400		
	Aquatic Chronic 1, H410		
	-		

The product contains synthetic polymer microparticles above the concentration limit, but derogation §4 or §5 apply. (4a) use at industrial sites

Generic Polymer Name	Concentration range
Polymers of vinyl chloride or of other halogenated olefins	0,1-10 %
Polymers of propylene or of other olefins	0,1-10 %

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

Particle characteristics of nanoforms

	Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica			
Particle Size Distribution				
	D50	2,5 - 50 nm		
Particle Shape	Form	spheres		
Crystallinity	Crystallinity	amorphous		
Surface Treatment/Coating	Surface Treatment/Coating	Yes		
	Chemical surface functionalization	hydrophobic		
Assessment Nanomaterial/Nanoformat	Assessment Based on	Supplier information		

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

EYE: Irritation, conjunctivitis.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

SDS No.: 153615 LOCTITE 266 Page 5 of 30

V009.0

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities

 $Ensure\ good\ ventilation/extraction.$

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Anaerobic Sealant

SDS No.: 153615 LOCTITE 266 Page 6 of 30

V009.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	72	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	143	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethene, homopolymer 9002-88-4 [Dusts non-specific]		10	Time Weighted Average (TWA):		IR_OEL
Ethene, homopolymer 9002-88-4 [Dusts non-specific]		4	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]		5	Time Weighted Average	Included in the regulation but with no data values. See regulation for further details	IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OIL PURE, HIGHLY & SEVERELY REFINED]		5	Time Weighted Average (TWA):		IR_OEL
Distillates (petroleum), hydrotreated heavy naphthenic 64742-52-5 [MINERAL OILS THAT HAVE BEEN USED BEFORE IN INTERNAL COMBUSTION ENGINES TO LUBRICATE AND COOL THE MOVING PARTS WITHIN THE ENGINE]			Skin designation:	Can be absorbed through the skin.	IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

SDS No.: 153615 LOCTITE 266 Page 7 of 30

V009.0

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value	Value			Remarks
			mg/l	ppm	mg/kg	others	
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	aqua		0,01 mg/l				
dione 3006-93-7	(freshwater)						
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	aqua (marine		0,001 mg/l				
dione	water)		0,001 mg/1				
3006-93-7	,						
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	sewage		0,051 mg/l				
dione 3006-93-7	treatment plant (STP)						
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	sediment				0,346		
dione	(freshwater)				mg/kg		
3006-93-7	,				8 8		
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	sediment				0,035		
dione	(marine water)				mg/kg		
3006-93-7 1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	Soil				0,063		
dione	3011				mg/kg		
3006-93-7							
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	oral				0,05 mg/kg		
dione							
3006-93-7 1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	F 1 4		0.1 //				
dione	Freshwater - intermittent		0,1 mg/l				
3006-93-7	intermittent						
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	Marine water -		0,01 mg/l				
dione	intermittent						
3006-93-7							
Methacrylic acid, monoester with propane-	aqua		0,904 mg/l				
1,2-diol 27813-02-1	(freshwater)						
Methacrylic acid, monoester with propane-	aqua (marine		0,0904				
1,2-diol	water)		mg/l				
27813-02-1	,						
Methacrylic acid, monoester with propane-	sewage		10 mg/l				
1,2-diol 27813-02-1	treatment plant (STP)						
Methacrylic acid, monoester with propane-	aqua		0,972 mg/l				
1,2-diol	(intermittent		0,772 mg/1				
27813-02-1	releases)						
Methacrylic acid, monoester with propane-	sediment				4,13 mg/kg		
1,2-diol	(freshwater)						
27813-02-1 Methacrylic acid, monoester with propane-	sediment				0,413		
1,2-diol	(marine water)				mg/kg		
27813-02-1	,				8 8		
Methacrylic acid, monoester with propane-	Soil				0,295		
1,2-diol					mg/kg		
27813-02-1 Methacrylic acid, monoester with propane-	Air						no hazard identified
1,2-diol	All						no nazara rachanca
27813-02-1							
Methacrylic acid, monoester with propane-	Predator						no potential for
1,2-diol							bioaccumulation
27813-02-1 .alpha.,.alphaDimethylbenzyl	0.000	1	0.0021			1	
hydroperoxide	aqua (freshwater)		0,0031 mg/l				
80-15-9	(II conwater)		1115/1				
.alpha.,.alphaDimethylbenzyl	aqua		0,031 mg/l				
hydroperoxide	(intermittent						
80-15-9	releases)		0.00021				
.alpha.,.alphaDimethylbenzyl	aqua (marine		0,00031				
hydroperoxide 80-15-9	water)		mg/l				
.alpha.,.alphaDimethylbenzyl	sewage		0,35 mg/l		1		
hydroperoxide	treatment plant		,0 -				
80-15-9	(STP)						
.alpha.,.alphaDimethylbenzyl	sediment				0,023		

SDS No.: 153615 LOCTITE 266 Page 8 of 30

V009.0

hydroperoxide 80-15-9	(freshwater)		mg/kg	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	sediment (marine water)		0,0023 mg/kg	
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Soil		0,0029 mg/kg	
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	oral		9,33 mg/kg	
methacrylic acid 79-41-4	aqua (freshwater)	0,82 mg/		
methacrylic acid 79-41-4	Freshwater - intermittent	0,45 mg/		
methacrylic acid 79-41-4	aqua (marine water)	0,082 mg	/1	
methacrylic acid 79-41-4	sewage treatment plant (STP)	100 mg/l		
methacrylic acid 79-41-4	sediment (freshwater)		3,09 mg/kg	
methacrylic acid 79-41-4	sediment (marine water)		0,309 mg/kg	
methacrylic acid 79-41-4	Soil		0,137 mg/kg	
methacrylic acid 79-41-4	Predator			no potential for bioaccumulation

SDS No.: 153615 LOCTITE 266 Page 9 of 30

V009.0

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	Workers	inhalation	Long term		0,176 mg/m3	
dione 3006-93-7			exposure - systemic effects			
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	Workers	dermal	Long term		0,05 mg/kg	
dione			exposure -			
3006-93-7 1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	General	dermal	systemic effects Long term		0,025 mg/kg	
dione	population	Comman	exposure -		0,023 mg ng	
3006-93-7	G 1	1	systemic effects		0.025	
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-dione	General population	oral	Long term exposure -		0,025 mg/kg	
3006-93-7	роримной		systemic effects			
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	General	inhalation	Long term		0,043 mg/m3	
dione 3006-93-7	population		exposure - systemic effects			
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	Workers	inhalation	Acute/short term			
dione			exposure -			
3006-93-7 1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	Workers	dermal	systemic effects Long term			
dione	WOIKCIS	German	exposure - local			
3006-93-7			effects			
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-dione	Workers	dermal	Acute/short term exposure - local			
3006-93-7			effects			
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	Workers	dermal	Long term			
dione			exposure - local effects			
3006-93-7 1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-	General	dermal	Long term			
dione	population	Comman	exposure - local			
3006-93-7			effects			
1,1'-(1,3-Phenylene)bis-1H-pyrrole-2,5-dione	General population	dermal	Acute/short term exposure - local			
3006-93-7	population		effects			
Methacrylic acid, monoester with propane-	Workers	dermal	Long term		4,2 mg/kg	no hazard identified
1,2-diol 27813-02-1			exposure - systemic effects			
Methacrylic acid, monoester with propane-	Workers	Inhalation	Long term		14,7 mg/m3	no hazard identified
1,2-diol			exposure -			
27813-02-1 Methacrylic acid, monoester with propane-	General	dermal	systemic effects		2.5 mg/lsg	no hazard identified
1,2-diol	population	dermai	Long term exposure -		2,5 mg/kg	no nazard identified
27813-02-1	1 1		systemic effects			
Methacrylic acid, monoester with propane-	General	Inhalation	Long term		8,8 mg/m3	no hazard identified
1,2-diol 27813-02-1	population		exposure - systemic effects			
Methacrylic acid, monoester with propane-	General	oral	Long term		2,5 mg/kg	no hazard identified
1,2-diol	population		exposure -			
27813-02-1 Silanamine, 1,1,1-trimethyl-N-	Workers	inhalation	systemic effects Long term			
(trimethylsilyl)-, hydrolysis products with	Workers	illinatation	exposure -			
silica			systemic effects			
7631-86-9 Silanamine, 1,1,1-trimethyl-N-	Workers	inhalation	Long term			
(trimethylsilyl)-, hydrolysis products with	Workers	illinatation	exposure - local			
silica			effects			
7631-86-9 Silanamine, 1,1,1-trimethyl-N-	Workers	inhalation	Acute/short term			
(trimethylsilyl)-, hydrolysis products with	WOIKCIS	iiiiaiatioii	exposure -			
silica			systemic effects			
7631-86-9 Silanamine, 1,1,1-trimethyl-N-	Workers	inhalati	Acute/short term			
(trimethylsilyl)-, hydrolysis products with	workers	inhalation	exposure - local			
silica			effects			
7631-86-9	XX7 1	1 1	T			
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with	Workers	dermal	Long term exposure -			
silica			systemic effects			
7631-86-9						

SDS No.: 153615 LOCTITE 266 Page 10 of 30

V009.0

Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	Workers	dermal	Acute/short term exposure - systemic effects		
7631-86-9 Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	Workers	dermal	Long term exposure - local effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	Workers	dermal	Acute/short term exposure - local effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	inhalation	Long term exposure - systemic effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	inhalation	Acute/short term exposure - systemic effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	inhalation	Long term exposure - local effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	inhalation	Acute/short term exposure - local effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	dermal	Long term exposure - systemic effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	dermal	Acute/short term exposure - systemic effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	dermal	Long term exposure - local effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	dermal	Acute/short term exposure - local effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	oral	Long term exposure - systemic effects		
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica 7631-86-9	General population	oral	Acute/short term exposure - systemic effects		
.alpha.,.alphaDimethylbenzyl hydroperoxide 80-15-9	Workers	inhalation	Long term exposure - systemic effects	6 mg/m3	
Maleic acid 110-16-7	Workers	dermal	Acute/short term exposure - local effects		
Maleic acid 110-16-7 Maleic acid	Workers Workers	dermal	Long term exposure - local effects Acute/short term		
Maleic acid 110-16-7 Maleic acid	Workers	dermal	exposure - systemic effects Long term		
110-16-7 Maleic acid	Workers	inhalation	exposure - systemic effects Acute/short term		
110-16-7 Maleic acid	Workers	inhalation	exposure - local effects Long term	0,987 mg/m3	
110-16-7			exposure - systemic effects	1 3 5 0 7 1118 1110	

V009.0

Maleic acid 110-16-7	Workers	inhalation	Long term exposure - local effects		
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects	88 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - systemic effects	29,6 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects	4,25 mg/kg	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects	6,55 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects	6,3 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects	2,55 mg/kg	no potential for bioaccumulation

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

V009.0

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form liquid
Colour Red
Odor Mild
Physical state liquid

Melting point Not applicable, Product is a liquid

Solidification temperature $< -30 \,^{\circ}\text{C} \, (< -22 \,^{\circ}\text{F})$ Initial boiling point $> 150 \,^{\circ}\text{C} \, (> 302 \,^{\circ}\text{F})$

Flammability The product is not flammable. Explosive limits Not applicable, The product is not flammable.

Flash point > 100,00° C (> 212 °F) No flash point up to 100 °C

Auto-ignition temperature $> 300 \,^{\circ}\text{C} \, (> 572 \,^{\circ}\text{F})$

Decomposition temperature

Not applicable, Substance/mixture is not self-reactive, no organic

peroxide and does not decompose under foreseen conditions of use

pH Not applicable, Product is non-polar/aprotic.

Viscosity (kinematic) > 20,5 mm2/s

(40 °C (104 °F);)

Solubility (qualitative) Slight

(20 °C (68 °F); Solvent: Water)

Solubility (qualitative) Miscible

(Solvent: Acetone)

Partition coefficient: n-octanol/water Not applicable

Mixture

Vapour pressure < 6,67 mbar

(27 °C (80.6 °F))

Vapour pressure <300 mbar;no method / method unknown

(50 °C (122 °F))

Vapour pressure < 0,13 mbar

(20 °C (68 °F))

Density 1,19 g/cm3 no method / method unknown

(20 °C (68 °F))

Relative vapour density: > 1

(20 °C)

Particle size Further particle properties for nanomaterials see section 3

Particle characteristics

Not applicable
Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reducing agents. Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

LOCTITE 266 SDS No.: 153615 Page 13 of 30

V009.0

10.5. Incompatible materials See section reactivity.

10.6. Hazardous decomposition products carbon oxides.

Hydrocarbons nitrogen oxides

Rapid polymerisation may generate excessive heat and pressure.

LOCTITE 266 Page 14 of 30

V009.0

SDS No.: 153615

SECTION 11: Toxicological information

General toxicological information:

The mixture is classified based on the available hazard information for the ingredients as defined in the classification criteria for mixtures for each hazard class or differentiation in Annex I to Regulation (EC) No 1272/2008. Relevant available health/ecological information for the substances listed under Section 3 is provided in the following.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
N,N-(m-	Acute	500 mg/kg		Expert judgement
phenylene)dimaleimide 3006-93-7	toxicity			
3006-93-7	estimate (ATE)			
N,N-(m-	LD50	> 300 - 2.000	4	OECD Collaboration A22 (A costs Constantials)
phenylene)dimaleimide	LD30		rat	OECD Guideline 423 (Acute Oral toxicity)
3006-93-7		mg/kg		
Hydroxypropyl	LD50	> 2.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
methacrylate	LD30	> 2.000 mg/kg	Tat	OLCD Guideline 401 (Acute Olai Toxicity)
27813-02-1				
Silica, surface treated	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
with	LD30	5.000 mg/kg	Tat	OLOB Guideline 401 (Neute Oldi Tokicity)
Hexamethyldisilazane -				
Nano				
7631-86-9				
Silica, surface treated	Acute	> 5.000 mg/kg		Expert judgement
with	toxicity			1 3 8
Hexamethyldisilazane -	estimate			
Nano	(ATE)			
7631-86-9				
Cumene hydroperoxide	LD50	382 mg/kg	rat	other guideline:
80-15-9				
Distillates (petroleum),	LD50	> 5.000 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
hydrotreated heavy				
naphthenic <3%DMSO				
64742-52-5				
N,N-Diethyl-p-toluidine	Acute	100 mg/kg		Expert judgement
613-48-9	toxicity			
	estimate			
	(ATE)			17.4
maleic acid	LD50	708 mg/kg	rat	not specified
110-16-7	1.050	210 //		OFCD C :11: 405 (4 + O 1F :: H 1D
Acetic acid, 2-	LD50	310 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down
phenylhydrazide				Procedure)
114-83-0	A4-	100 /1		F
N,N-dimethyl-o-toluidine 609-72-3	Acute toxicity	100 mg/kg		Expert judgement
009-72-3	estimate			
	(ATE)			
methacrylic acid	LD50	1.320 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
79-41-4	LDJU	1.320 mg/kg	Tat	Toxicity)
1,4-Naphthalenedione	LD50	124 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
130-15-4	LDJU	12 Tillg/Kg	1 at	Toxicity)
150 15-4	l .	ı	1	TOMOTO

SDS No.: 153615 LOCTITE 266 Page 15 of 30

V009.0

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Hydroxypropyl methacrylate 27813-02-1	LD50	> 5.000 mg/kg	rabbit	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	LD50	> 5.000 mg/kg	rabbit	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	Acute toxicity estimate (ATE)	> 5.000 mg/kg		Expert judgement
Cumene hydroperoxide 80-15-9	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	LD50	> 5.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
N,N-Diethyl-p-toluidine 613-48-9	Acute toxicity estimate (ATE)	300 mg/kg		Expert judgement
maleic acid 110-16-7	LD50	1.560 mg/kg	rabbit	not specified
N,N-dimethyl-o-toluidine 609-72-3	Acute toxicity estimate (ATE)	300 mg/kg		Expert judgement
methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg	rabbit	Dermal Toxicity Screening
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement

SDS No.: 153615 LOCTITE 266 Page 16 of 30

V009.0

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
N,N-(m- phenylene)dimaleimide 3006-93-7	LC50	0,055 mg/l	dust	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	LC50	> 5,01 mg/l	dust/mist	4 h	rat	OECD Guideline 436 (Acute Inhalation Toxicity: Acute Toxic Class (ATC) Method)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	Acute toxicity estimate (ATE)	> 5,01 mg/l	dust/mist			Expert judgement
Cumene hydroperoxide 80-15-9	LC50	1,370 mg/l	vapour	4 h	rat	not specified
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	LC50	> 5,53 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
N,N-Diethyl-p-toluidine 613-48-9	Acute toxicity estimate (ATE)	3 mg/l	vapour			Expert judgement
N,N-dimethyl-o-toluidine 609-72-3	Acute toxicity estimate (ATE)	0,5 mg/l	dust/mist	4 h		Expert judgement
methacrylic acid 79-41-4	LC50	3,19 - 6,5 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	3,19 mg/l	dust/mist			Expert judgement
1,4-Naphthalenedione 130-15-4	LC50	0,046 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

Causes skin irritation.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
N,N-(m- phenylene)dimaleimide 3006-93-7	not corrosive	60 min	Human, EpiDermTM SIT (EPI-200), Reconstructed Human Epidermis (RHE)	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
N,N-(m- phenylene)dimaleimide 3006-93-7	not irritating	60 min	Human, EpiDermTM SIT (EPI-200), Reconstructed Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Hydroxypropyl methacrylate 27813-02-1	not irritating	24 h	rabbit	Draize Test
Silica, surface treated with Hexamethyldisilazane - Nano	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

SDS No.: 153615 LOCTITE 266 Page 17 of 30

V009.0

1	1		1	,
7631-86-9		1		
Cumene hydroperoxide 80-15-9	corrosive		rabbit	Draize Test
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	not irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
N,N-Diethyl-p-toluidine 613-48-9	irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
maleic acid 110-16-7	irritating	24 h	human	Patch Test
Acetic acid, 2- phenylhydrazide 114-83-0	not corrosive		Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
Acetic acid, 2- phenylhydrazide 114-83-0	not irritating		Human, EpiSkinTM (SM), Reconstructed Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
methacrylic acid 79-41-4	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
1,4-Naphthalenedione 130-15-4	Category 1C (corrosive)		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
N,N-(m- phenylene)dimaleimide 3006-93-7	not irritating		Bovine, cornea, in vitro test	OECD Guideline 437 (BCOP)
Hydroxypropyl methacrylate 27813-02-1	Category 2B (mildly irritating to eyes)		rabbit	Draize Test
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
maleic acid 110-16-7	highly irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Acetic acid, 2- phenylhydrazide 114-83-0	not irritating		Chicken, eye, isolated	OECD Guideline 438 (Isolated Chicken Eye Test Method)
methacrylic acid 79-41-4	corrosive		rabbit	Draize Test

SDS No.: 153615 LOCTITE 266 Page 18 of 30

V009.0

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
N,N-(m-phenylene)dimaleimide 3006-93-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydroxypropyl methacrylate 27813-02-1	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Hydroxypropyl methacrylate 27813-02-1	sensitising	Guinea pig maximisation test	guinea pig	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
maleic acid 110-16-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
maleic acid 110-16-7	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Acetic acid, 2- phenylhydrazide 114-83-0	positive	Direct peptide reactivity assay (DPRA)	cysteine and lysine, in chemico test	OECD Guideline 442C (Direct Peptide Reactivity Assay (DPRA))
Acetic acid, 2- phenylhydrazide 114-83-0	positive	Activation of keratinocytes	human keratinocytes, in vitro test	OECD Guideline 442D (ARE-Nrf2 Luciferase Test Method)
Acetic acid, 2- phenylhydrazide 114-83-0	positive	activation of dendritic cells	human monocytes, in vitro test	OECD Guideline 442E (H-CLAT: Human Cell Line Activation Test)
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
1,4-Naphthalenedione 130-15-4	sensitising	not specified	guinea pig	not specified

SDS No.: 153615 LOCTITE 266 Page 19 of 30

V009.0

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
N,N-(m- phenylene)dimaleimide 3006-93-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
N,N-(m- phenylene)dimaleimide 3006-93-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
N,N-(m- phenylene)dimaleimide 3006-93-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Hydroxypropyl methacrylate 27813-02-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Hydroxypropyl methacrylate 27813-02-1	positive	in vitro mammalian chromosome aberration test	with and without		Chromosome Aberration Test
Hydroxypropyl methacrylate 27813-02-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	negative	bacterial reverse mutation assay (e.g Ames test)			OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	negative	in vitro mammalian chromosome aberration test			OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	negative	mammalian cell gene mutation assay			OECD Guideline 490 (In Vitro Mammalian Cell Gene Mutation Tests Using the Thymidine Kinase Gene)
Cumene hydroperoxide 80-15-9	positive	bacterial reverse mutation assay (e.g Ames test)	without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
maleic acid 110-16-7	negative	bacterial reverse mutation assay (e.g Ames test)	no data		Ames Test
maleic acid 110-16-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Acetic acid, 2- phenylhydrazide 114-83-0	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Acetic acid, 2- phenylhydrazide 114-83-0	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)

V009.0

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Hydroxypropyl methacrylate 27813-02-1	not carcinogenic	inhalation	2 y 6 h/d, 5 d/w	rat	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
maleic acid 110-16-7	not carcinogenic	oral: feed	2 y daily	rat	male/female	OECD Guideline 451 (Carcinogenicity Studies)
Acetic acid, 2- phenylhydrazide 114-83-0	carcinogenic	oral: drinking water	continuous	mouse	male/female	not specified
methacrylic acid 79-41-4	not carcinogenic	inhalation	2 y	mouse	male/female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
N,N-(m- phenylene)dimaleimide 3006-93-7	NOAEL P 240 mg/kg NOAEL F1 240 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL P 300 mg/kg NOAEL F1 1.000 mg/kg	screening	oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL P 400 mg/kg NOAEL F1 400 mg/kg	two- generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	NOAEL P >= 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
maleic acid 110-16-7	NOAEL F1 150 mg/kg NOAEL F2 55 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)
methacrylic acid 79-41-4	NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

May cause respiratory irritation.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
methacrylic acid 79-41-4	May cause respiratory irritation.			

V009.0

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
N,N-(m- phenylene)dimaleimide 3006-93-7	NOAEL 15 mg/kg	oral: gavage	42-52 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL 300 mg/kg	oral: gavage	49 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydroxypropyl methacrylate 27813-02-1	NOAEL 0,352 mg/l	inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOAEL 491,5 mg/kg	oral: feed	6 months daily	rat	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOAEL 0,01 mg/kg	inhalation: dust	12 months 6 h/d, 5 d/wk	rat	not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOAEL 0,01 mg/kg	inhalation: dust	12 months 6 h/d, 5 d/wk	monkey	not specified
Cumene hydroperoxide 80-15-9		inhalation: aerosol	6 h/d 5 d/w	rat	not specified
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	LOAEL 125 mg/kg	oral: gavage		rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
maleic acid 110-16-7	NOAEL >= 40 mg/kg	oral: feed	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
methacrylic acid 79-41-4		inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

LOCTITE 266 Page 22 of 30

V009.0

SDS No.: 153615

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hydroxypropyl methacrylate 27813-02-1	LC50	493 mg/l	48 h	Leuciscus idus melanotus	DIN 38412-15
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	LC50	> 10.000 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Cumene hydroperoxide 80-15-9	LC50	3,9 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	LL50	> 100 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
N,N-Diethyl-p-toluidine 613-48-9	LC50	78,62 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
maleic acid 110-16-7	LC50	> 245 mg/l	48 h	Leuciscus idus	DIN 38412-15
N,N-dimethyl-o-toluidine 609-72-3	LC50	46 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
methacrylic acid 79-41-4	LC50	85 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
methacrylic acid 79-41-4	NOEC	10 mg/l	35 d	Danio rerio	OECD Guideline 210 (fish early lite stage toxicity test)
1,4-Naphthalenedione 130-15-4	LC50	0,045 mg/l	96 h	Oryzias latipes	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
N,N-(m-phenylene)dimaleimide 3006-93-7	EC50	31,6 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Hydroxypropyl methacrylate 27813-02-1	EC50	> 143 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	EC50	> 1.000 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Cumene hydroperoxide 80-15-9	EC50	18,84 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	EL50	> 10.000 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	10,34 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
maleic acid 110-16-7	EC50	42,81 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

SDS No.: 153615 LOCTITE 266 Page 23 of 30

V009.0

Acetic acid, 2- phenylhydrazide 114-83-0	EC50	1,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
methacrylic acid 79-41-4	EC50	> 130 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
1,4-Naphthalenedione 130-15-4	EC50	0,026 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Hydroxypropyl methacrylate 27813-02-1	NOEC	45,2 mg/l	21 d		OECD 211 (Daphnia magna, Reproduction Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOEC	132,7 mg/l	21 d		OECD 211 (Daphnia magna, Reproduction Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	NOELR	10 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
maleic acid 110-16-7	NOEC	10 mg/l	21 d	Daphnia magna	other guideline:
methacrylic acid 79-41-4	NOEC	53 mg/l	21 d		OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

LOCTITE 266 Page 24 of 30

V009.0

SDS No.: 153615

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No. N,N-(m-	type ErC50	67,898 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga,
phenylene)dimaleimide 3006-93-7	EIC30		/2 11	Desinodesinus suospicatus	Growth Inhibition Test)
N,N-(m- phenylene)dimaleimide 3006-93-7	EC10	0,308 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate 27813-02-1	EC50	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Hydroxypropyl methacrylate 27813-02-1	NOEC	> 97,2 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	EC50	> 173,1 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	NOEC	173,1 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	EC50	3,1 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Cumene hydroperoxide 80-15-9	NOEC	l mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	NOELR	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
N,N-Diethyl-p-toluidine 613-48-9	EC50	23,69 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	EC50	74,35 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic acid 110-16-7	EC10	11,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Acetic acid, 2- phenylhydrazide 114-83-0	EC50	0,258 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Acetic acid, 2- phenylhydrazide 114-83-0	NOEC	0,012 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	NOEC	8,2 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	EC50	45 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	NOEC	0,07 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
1,4-Naphthalenedione 130-15-4	EC50	0,42 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Hydroxypropyl methacrylate 27813-02-1	EC10	1.140 mg/l	16 h		not specified
Silica, surface treated with Hexamethyldisilazane - Nano 7631-86-9	EC50	> 2.500 mg/l	3 h	predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Cumene hydroperoxide 80-15-9	EC10	70 mg/l	30 min	not specified	not specified
Distillates (petroleum), hydrotreated heavy naphthenic	NOEC	> 1,93 mg/l	96 h	other:	other guideline:

SDS No.: 153615 LOCTITE 266 Page 25 of 30

V009.0

<3%DMSO 64742-52-5					
maleic acid 110-16-7	EC10	44,6 mg/l	18 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
methacrylic acid 79-41-4	EC10	100 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
1,4-Naphthalenedione 130-15-4	EC50	5,94 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
N,N-(m- phenylene)dimaleimide 3006-93-7	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Hydroxypropyl methacrylate 27813-02-1	readily biodegradable	aerobic	94,2 %	28 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)
Cumene hydroperoxide 80-15-9	not readily biodegradable.	aerobic	3 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Distillates (petroleum), hydrotreated heavy naphthenic <3%DMSO 64742-52-5	not readily biodegradable.	aerobic	31 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
N,N-Diethyl-p-toluidine 613-48-9	not readily biodegradable.	not specified	1 %	28 day	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
maleic acid 110-16-7	readily biodegradable	aerobic	97,08 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Acetic acid, 2- phenylhydrazide 114-83-0	not readily biodegradable.	aerobic	39 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
N,N-dimethyl-o-toluidine 609-72-3	not readily biodegradable.	aerobic	1 %	14 d	other guideline:
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	14 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
1,4-Naphthalenedione 130-15-4	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Cumene hydroperoxide	9,1			calculation	OECD Guideline 305
80-15-9					(Bioconcentration: Flow-through
					Fish Test)

SDS No.: 153615 Page 26 of 30

V009.0

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
N,N-(m- phenylene)dimaleimide 3006-93-7	0,67	24 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
Hydroxypropyl methacrylate 27813-02-1	0,97	20 °C	not specified
Cumene hydroperoxide 80-15-9	1,6	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
N,N-Diethyl-p-toluidine 613-48-9	3,7		QSAR (Quantitative Structure Activity Relationship)
maleic acid 110-16-7	-1,3	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Acetic acid, 2- phenylhydrazide 114-83-0	0,74		QSAR (Quantitative Structure Activity Relationship)
methacrylic acid 79-41-4	0,93	22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
1,4-Naphthalenedione 130-15-4	1,71		not specified

12.5. Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or vPvB.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Do not spill substance/product and prevent environmental releases.

Do not rinse packaging before disposal.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances
The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes
for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We
will be happy to advise you.

V009.0

SECTION 14: Transport information

14.1. UN number or ID number

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.2. UN proper shipping name

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.3. Transport hazard class(es)

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.4. Packing group

ADR	Not dangerous goods
RID	Not dangerous goods
ADN	Not dangerous goods
IMDG	Not dangerous goods
IATA	Not dangerous goods

14.5. Environmental hazards

not applicable
not applicable
not applicable
not applicable
not applicable

14.6. Special precautions for user

ADR	not applicable
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SDS No.: 153615 LOCTITE 266 Page 28 of 30

V009.0

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

VOC content < 3 % (2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

V009.0

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H242 Heating may cause a fire.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H330 Fatal if inhaled.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

ASTM: American Society for Testing and Materials

ATE: acute toxicity estimate

AS: Australian Standard

AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water

CAS: Chemical Abstract Service

CLP: Regulation (EC) No 1272/2008

CMR: cancerogenic, mutagenic or reprotoxic

DIN: German Institute for Standardization

ECx: Effective concentration (x% effective level)

ECHA: European Chemicals Agency

EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS

ECTLV: European community threshold limit value

ED:Substance identified as having endocrine disrupting properties

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

EN: European Standard

ENCS: Japanese chemical inventory

EPA: US Environmental Protection Agency

EU: European Union

EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148 EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148

EWC: European Waste Catalogue

GHS: Globally Harmonised System for Classification and Labelling of Chemicals

GLP: Good Laboratory Practice

HSNO: Hazardous Substances and New Organisms

IARC: International Agency for Research of Cancer

IATA: International Air Transport Association

IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk

IC50: half maximal inhibitory concentration

ICAO: International Civil Aviation Organization

IMDG-Code: International Maritime Code for Dangerous Goods

IMO: International Maritime Organization

ISO: International Standardization Organisation

LC50: Median lethal concentration

V009.0

LD50: Median lethal dose

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

n.o.s.: not otherwise specified

NO(A)EC: No (adverse) effect concentration

NO(A)EL: No (adverse) effect level NZS: New Zealand Standard

OECD: Organisation for Economic Co-operation and Development

OEL: Occupational Exposure Limit

OPPT: US EPA Office of Pollution Prevention and Toxics

OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances

PBT: Persistent, bioaccumulative, toxic

(Q)SAR: (Quantitative) structure-activity relationship

REACH: Regulation (EC) No. 1907/2006

RID: Regulations concerning the International Transport of Dangerous Goods by Rail

SADT: Self Accelerating Decomposition Temperature

SDS: Safety Data Sheet

STOT: Specific Target Organ Toxicity

STOT SE: Specific Target Organ Toxicity - single exposure STOT RE: Specific Target Organ Toxicity - repeated exposure

SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons

SVHC: Substance of very high concern (REACH Candidate List)

TRGS: German Technical Rules for hazardous substances

UN: United Nations

VOC: Volatile Organic Compound

814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds

vPvB: Very persistent, very bioaccumulative

VwVwS: Administrative Regulation on Substances Hazardous to Waters

WGK: Water hazard class

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer.

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.