

**DOW CORNING(R) 3140 RTV COATING****1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY**

<b>Trade name</b>	:	DOW CORNING(R) 3140 RTV COATING
<b>Company</b>	:	Dow Corning S.A. rue Jules Bordet - Parc Industriel - Zone C B-7180 Seneffe Belgium
<b>Service</b>	:	Dow Corning Central Europe Dow Corning Northern Europe Dow Corning Southern Europe
<b>Emergency Phone Number</b>	:	Dow Corning (Barry U.K. 24h) Dow Corning (Wiesbaden 24h) Dow Corning (Seneffe 24h)
<b>Use of the substance/preparation</b>	:	Adhesive, binding agents Electrical and electronic applications

**2. COMPOSITION / INFORMATION ON INGREDIENTS****Chemical characterization:** Silicone elastomer**Hazardous Ingredients:**

Name	CAS-No.	EINECS/ ELINCS No.	Conc. (% w/w)	Classification	
Trimethylated silica	68909-20-6	272-697-1	14.0		
Trimethoxy(methyl)silane	1185-55-3	214-685-0	5.8	F Xn	R11 R22
Methanol	67-56-1	200-659-6	0.12	F T	R11 R39/23/24/25 R23/24/25

**3. HAZARDS IDENTIFICATION**

Not hazardous according to Council Directive 1999/45/EC and its subsequent amendments.

**4. FIRST AID MEASURES**

<b>On contact with eyes</b>	:	Flush with water.
<b>On skin contact</b>	:	Flush with water.
<b>If inhaled</b>	:	Remove to fresh air.

**DOW CORNING(R) 3140 RTV COATING**

**On ingestion** : Obtain medical attention.

**5. FIRE FIGHTING MEASURES**

**Suitable extinguishing media** : Carbon dioxide, foam, dry powder or fine water spray. Water can be used to cool fire exposed containers.

**Unsuitable extinguishing media** : None known.

**Hazards during fire fighting** : None known.

**Special protective equipment/procedures** : A self-contained respirator and protective clothing should be worn. Keep containers cool with water spray until well after the fire is out. Determine the need to evacuate or isolate the area according to your local emergency plan.

**Hazardous Combustion Products** : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions** : Wear proper protective equipment.

**Precautions to protect the environment** : Prevent from spreading or entering into drains, ditches or rivers by using sand, earth or other appropriate barriers.

**Methods for cleaning up** : Determine the need to evacuate or isolate the area according to your local emergency plan. Very large spills should be contained by bunding, etc... procedures. Mop, wipe or soak up with absorbent material and place in a container with a lid. The spilled product produces an extremely slippery surface.

**7. HANDLING AND STORAGE**

**Advice on safe handling** : General ventilation is required. Local ventilation is recommended. Avoid eye contact. Do not breathe vapour. Do not breathe spray or mist. Do not ingest.

**Advice on storage** : Do not store with oxidizing agents.

**Specific uses** : Refer to technical data sheet available on request.

**Unsuitable packaging materials** : None known.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**DOW CORNING(R) 3140 RTV COATING**

**Engineering Controls** : Ventilation : Refer to Section 7

**Exposure controls for hazardous components**

Name	CAS-No.	Exposure Limits
Trimethylated silica	68909-20-6	5 mg/m <sup>3</sup> (OEL, 8h TWA) respirable dust; 10mg/m <sup>3</sup> (OEL, 8h TWA) total inhalable dust.
Trimethoxy(methyl)silane	1185-55-3	200 ppm TWA, 250 ppm STEL as methanol
Methanol	67-56-1	250 ppm STEL 200 ppm TWA 333 mg/m <sup>3</sup> STEL 266 mg/m <sup>3</sup> TWA

**Personal protection equipment**

**Respiratory protection** : Suitable respiratory protection should be worn if the product is used in large quantities, confined spaces or in other circumstances where the OEL may be approached or exceeded.  
A suitable respirator must be worn if the product is used in any circumstances where an aerosol or mist may be generated, such as during spraying or similar activities.  
A full-face mask is recommended.  
Recommended Filter type: AXPSL  
The choice of a filter type depends on the amount and type of chemical being handled in the workplace. Regarding filter characteristics, contact your respiratory protection supplier.

**Hand protection** : Gloves are not normally required.

**Eye protection** : Safety glasses should be worn.

**Skin protection** : Protective equipment is not normally necessary.

**Hygiene measures** : Exercise good industrial hygiene practice. Wash after handling, especially before eating, drinking or smoking.

**Environmental exposure controls** : Refer to section 6 and 12.

**Additional information** : These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions. For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these types of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance**

## DOW CORNING(R) 3140 RTV COATING

**Form:** Liquid      **Colour:** Translucent white      **Odour:** Slight

**Important health, safety and environmental information**

**Boiling point/range** : > 65 °C

**Flash point** : > 101.1 °C (Closed Cup)

**Explosive properties** : No

**Specific Gravity** : 1.05

**Viscosity** : 300 Poise at 25°C.

**Oxidizing properties** : No

The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**10. STABILITY AND REACTIVITY**

**Stability** : Stable under normal usage conditions.

**Conditions to avoid** : None established.

**Materials to avoid** : Can react with strong oxidising agents. Cures in the presence of water or moisture, releasing a small amount of methanol.

**Hazardous decomposition products** : Thermal breakdown of this product during fire or very high heat conditions may evolve the following decomposition products: Silica. Carbon oxides and traces of incompletely burned carbon compounds. Formaldehyde.

**11. TOXICOLOGICAL INFORMATION**

**On contact with eyes** : May cause temporary discomfort.

**On skin contact** : No adverse effects are normally expected.

**If inhaled** : May cause dizziness, drowsiness, confusion, headaches, nausea, and at high concentrations, unconsciousness.

**On ingestion** : Forms methanol and may cause serious injury to man at doses > 200 mg/kg.

**Other Health Hazard Information** : This product contains (a) powder(s) hazardous by inhalation. This is not relevant to the current physical form of the product, which is not in a respirable form. Product may emit formaldehyde vapour at temperatures above 180°C in the presence of air. Formaldehyde vapour is a suspected carcinogen, toxic by inhalation and irritating to eyes and the respiratory system. Exposure limits should be strictly respected.

<sup>1</sup> Based on product test data.

<sup>2</sup> Based on test data from similar products.

**12. ECOLOGICAL INFORMATION**

**DOW CORNING(R) 3140 RTV COATING****Environmental fate and distribution**

Siloxanes are removed from water by sedimentation or binding to sewage sludge. In soil, siloxanes are degraded. This product hydrolyses in water or moist air, releasing methanol and organosilicons.

**Ecotoxicity effects**

No adverse effects on aquatic organisms are predicted.

**Bioaccumulation** : No bioaccumulation is predicted.

**Fate and effects in waste water treatment plants**

No adverse effects on bacteria are predicted. Removed > 90% by binding onto sewage sludge. The siloxanes in this product do not contribute to the BOD.

**13. DISPOSAL CONSIDERATIONS**

**Product disposal** : Dispose of in accordance with local regulations. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**Packaging disposal** : Dispose of in accordance with local regulations. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

**14. TRANSPORT INFORMATION****Road / Rail (ADR/RID)**

Not subject to ADR/RID.

**Sea transport (IMDG)**

Not subject to IMDG code.

**Air transport (IATA)**

Not subject to IATA regulations.

**DOW CORNING(R) 3140 RTV COATING****15. REGULATORY INFORMATION****Labelling according to EEC Directive**

**S-phrases** : S23(S) Do not breathe spray.  
S51 Use only in well-ventilated areas.

**National legislation / regulations**

**Ozone depleting chemicals** : No ozone depleting chemicals are present or used in manufacture.

**Status**

**AICS** : All ingredients listed, exempt or notified.

**DSL** : All ingredients listed or exempt.

**IECSC** : All ingredients listed or exempt.

**EINECS** : All ingredients listed, exempt or notified (ELINCS).

**KECL** : All ingredients listed, exempt or notified.

**PICCS** : All ingredients listed, exempt or notified.

**TSCA** : All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**MITI** : All ingredients listed, exempt or notified.

**DOW CORNING(R) 3140 RTV COATING****16. OTHER INFORMATION**

This product safety data sheet was prepared in compliance with Commission Directive 91/155/EEC, 67/548/EEC and 1999/45/EC as well as their relevant amendments, on the approximation of laws, regulations and administrative provisions relative to the classification, packaging and labelling of dangerous substances and preparations.

It is the responsibility of persons in receipt of this Product Safety Data Sheet to ensure that the information contained herein is properly read and understood by all people who may use, handle, dispose or in any way come in contact with the product. If the recipient subsequently produces a formulation containing the Dow Corning product, it is the recipient's sole responsibility to ensure the transfer of all relevant information from the Dow Corning Product Safety Data Sheet to their own Product Safety Data Sheet in compliance with Commission Directive 1999/45/EC.

All information and instructions provided in this Safety Data Sheet (SDS) are based on the current state of scientific and technical knowledge at the date indicated on the present SDS. Dow Corning shall not be held responsible for any defect in the product covered by this SDS, should the existence of such defect not be detectable considering the current state of scientific and technical knowledge.

As stated above, this Safety Data Sheet has been prepared in compliance with applicable European law. If you purchase this material outside Europe, where compliance laws may differ, you should receive from your local Dow Corning supplier a SDS applicable to the country in which the product is sold and intended to be used. Please note that the appearance and content of the SDS may vary - even for the same product - between different countries, reflecting the different compliance requirements. Should you have any question, please refer to your local Dow Corning supplier.

**R11** Highly flammable., **R22** Harmful if swallowed., **R23/24/25** Toxic by inhalation, in contact with skin and if swallowed., **R39/23/24/25** Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.