

ULTRAGLIDE X5 Machine Tool Slideway Lubricant

Ultraglide X5 has been formulated to provide excellent lubrication and corrosion protection for machine tool slideway systems. Being formulated to be compatible with water mix cutting and grinding fluids this product reduces the formation of solids and therefore the possibility of oilway blockages which cause expensive downtime and repairs.

Ultraglide X5 provides excellent resistance to wash-off, its rapid demulsification characteristics eliminate the formation of grease-like deposits in oilways and under machine tool slideways. This in turn eliminates chatter and vibration. The high film strength prevents metal to metal contact and reduces wear.

Features

- Excellent resistance to wash-off.
- Rapid demulsification characteristics – eliminating the formation of grease like deposits in oilways, under machine tool slideways, etc.
- Overcomes 'stick slip' phenomena, eliminating chatter and vibration – ensuring smooth and precise movement.
- Excellent lubrication characteristics.
- High film strength prevents metal to metal contact – reduces wear.
- Protects against corrosion and staining.
- Contains no silicone.

Directions for Use

ROCOL® Ultraglide X5 can be used to lubricate the slideways on any machine tool where a slideway oil of viscosity ISO VG 68 is designated.

Fill the machine lubricator reservoir or apply the product in accordance with the machine tool manufacturer's recommendations.

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67
Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.

ULTRAGLIDE X5

Appearance (applied film)	Clear brown oil
Odour	Characteristic
Kinematic Viscosity (applied film)	68 cSt at 40°C
Density at 20°C	0.89 g/cm ³
Storage	Store at normal ambient temperature (5 to 30°C)
Pack Sizes – Part Codes	5 ltr - 52086 20 ltr - 52083 200 ltr - 52089

Date: Jan-09

T +44 (0) 113 232 2600
F +44 (0) 113 232 2740
E customer-service@rocol.com
www.rocol.com

ROCOL House, Swillington, Leeds LS26 8BS

Registered Company No. 559693 VAT No. 742 0531 67

Registered Office: Admiral House, St Leonard's Road, Windsor, Berkshire SL4 3BL

ROCOL A division of **ITW** Ltd



BS EN ISO 9001
Certificate No. FM 12448



BS EN ISO 14001
Certificate No. EMS 67596



OHSAS 18001
Certificate No. OHS 78173



INVESTOR IN PEOPLE

The information in this publication is based on our experience and reports from customers. There are many factors outside our control or knowledge which affect the use and performance of our products, for which reason it is given without responsibility.