

Trade name: edding 725 neon board marker, green

Version: 1.0.0 / GB Status: 07.03.2008

1.) <u>Identification of the substance/preparation and of the</u>

company/undertaking

Identification of the substance or preparation

Trade name

edding 725 neon board marker, green

Use of the substance/preparation

Ink for use in drawliners

Company/undertaking identification

Address

edding Aktiengesellschaft

Bookkoppel 7

D-22926 Ahrensburg

Telephone no. +49 (0) 41 02 / 80 8-0

Information provided by / telephone

+49 (0)4102 - 808-0

Emergency telephone

+49 (0)30 192 40 (Toxic Substance Emergency Call Centre Berlin)

Advice on Safety Data Sheet

sdb_info@umco.de

2.) Hazards identification

Classification

F; R11 Highly flammable. Xi; R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

Hazard symbols

F Highly flammable

Xi Irritant

R phrases

Highly flammable.Irritating to eyes.

Vapours may cause drowsiness and dizziness.

3.) Composition / information on ingredients

Chemical characterization

Mixture (preparation)

Hazardous ingredients

ETHANOL

EC no. 200-578-6 Index no. 603-002-00-5 CAS no. 64-17-5

Concentration > 15 < 25 %-b.w.

Classification F: R11

Hazard symbols F R phrases 11

PROPAN-1-OL

EC no. 200-746-9 Index no. 603-003-00-0 CAS no. 71-23-8

Concentration > 5 < 10 %-b.w.

Classification F; R11 Xi; R41 R67

Hazard symbols F, Xi R phrases 11-41-67



Trade name: edding 725 neon board marker, green

Version: 1.0.0 / GB Status: 07.03.2008

PROPAN-2-OL

EC no. 200-661-7 Index no. 603-117-00-0 CAS no. 67-63-0

Concentration > 5 < 10 %-b.w.

Classification F; R11 Xi; R36 R67

Hazard symbols F, Xi R phrases 11-36-67

Other information (chapter 3.)

The product is an article. The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

4.) First aid measures

General information

In case of persisting adverse effects consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

Ensure supply of fresh air.

After skin contact

Wash off immediately with soap and water.

After eye contact

Separate eyelids, wash the eyes thoroughly with water (15 min.). Eye treatment by an oculist.

After ingestion

Rinse mouth thoroughly with water. Summon a doctor immediately. Never give anything by mouth to an unconscious person.

5.) Fire-fighting measures

Suitable extinguishing media

Alcohol-resistant foam; Carbon dioxide; Dry chemical extinguisher; Water spray jet

Extinguishing media that must not be used for safety reasons

Full water jet

Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

In the event of fire, the following can be released:

Carbon dioxide (CO2)

Carbon monoxide (CO)

Special protective equipment for fire-fighters

Use self-contained breathing apparatus. Wear protective clothing.

Other information

Cool endangered containers with water spray jet.

6.) Accidental release measures

Personal precautions

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing.

Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

Methods for cleaning up/taking up

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When picked up, treat material as prescribed under heading "Disposal considerations".



Trade name: edding 725 neon board marker, green

Version: 1.0.0 / GB Status: 07.03.2008

7.) Handling and storage

Handling

Advice on safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Product inherent handling risks must be minimised taking the appropriate measures for protection and preventive actions. The working process should be designed to rule out the release of hazardous substances or skin contact as far it is possible by the by the state of the art

Advice on protection against fire and explosion

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools

Storage

Requirements for storage rooms and vessels

Store product in closed containers.

Advice on storage assembly

None known

Further information on storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place. Protect from heat and direct sunlight.

8.) Exposure controls / personal protection

Exposure limit values

ETHANOL

CAS no. 64-17-5 EC no. 200-578-6

Occupational Exposure Standards (OESs) / EH40

Ethanol

TWA 1920 mg/m³ 1000 ml/m³

PROPAN-1-OL

CAS no. 71-23-8 EC no. 200-746-9

Occupational Exposure Standards (OESs) / EH40

Propan-1-ol

TWA 500 mg/m³ 200 ml/m³ STEL 625 mg/m³ 250 ml/m³

Skin resorption / Sk

sensibilisation

PROPAN-2-OL

CAS no. 67-63-0 EC no. 200-661-7

Occupational Exposure Standards (OESs) / EH40

Propan-2-ol

TWA 999 mg/m³ 400 ml/m³ STEL 1250 mg/m³ 500 ml/m³

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.



Trade name: edding 725 neon board marker, green

Version: 1.0.0 / GB Status: 07.03.2008

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product . Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Eye protection

Safety glasses with side protection shield (EN 166)

Skin protection

Clothing as usual in the chemical industry.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Wash hands before breaks and after work. Do not inhale vapours. Have eye wash fountain available.

0,87

g/cm³

9.) Physical and chemical properties

General information

Form liquid Colour green

Odour weak; characteristic

Important health, safety and environmental information

Changes in physical state

Type Value	Boiling point	78	°C
Flash point Value		12	°C
Explosion limits			
Upper explosion limit	19,00		% vol
Lower explosion limit	2,00		% vol
Vapour pressure Value Reference temperature	28	10 °C	mm Hg
Density			

Solubility in water

Value

Remarks soluble

10.) Stability and reactivity

Conditions to avoid

Heat; Moisture

Materials to avoid

None known

Hazardous decomposition products

No hazardous decomposition products known.



Trade name: edding 725 neon board marker, green

Version: 1.0.0 / GB Status: 07.03.2008

11.) <u>Toxicological information</u>

Experience in practice

Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin.

Eye contact with the product may lead to irritation.

Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness.

Other information (chapter 11.)

Product specific toxicological data are not known.

12.) Ecological information

Other adverse effects

Ecological data are not available.

Do not discharge product unmonitored into the environment.

13.) <u>Disposal considerations</u>

Product

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

Packaging

Residuals must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

Classification code

F1

14.) Transport information

Land transport ADR/RID

Class	3
Packaging group	II
Hazard id. no.	33
Label	3
UN number	1263
Technical name	Paint
Special Provision 640	D

Marine transport IMDG

Class	3
Packaging group	II
UN number	1263
Proper shipping name	Paint
EmS	F-E,S-E
MARPOL	-
Label	3

Air transport ICAO/IATA

Class	3
Packaging group	II
UN number	1263
Proper shipping name	Paint
Label	3

15.) Regulatory information

Labelling in accordance with EC directives

The product is classified and labelled in accordance with EC Directive 1999/45/EC.



Trade name: edding 725 neon board marker, green

Version: 1.0.0 / GB Status: 07.03.2008

The product is an article. The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

Hazard symbols

F Highly flammable

Xi Irritant

R phrases

Highly flammable. 36 Irritating to eyes.

Vapours may cause drowsiness and dizziness.

S phrases

26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

51 Use only in well-ventilated areas.

Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

Remarks Annex I, part 2, category 7 b

16.) Other information

Sources of key data used to compile the data sheet:

EC Directive 67/548/EC resp. 99/45/EC as amended in each case.

Regulation (EC) No 1907/2006 (REACH) as amended in each case.

EC Directives 2000/39/EC, 2006/15/EC as amended in each case.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding chapter.

Relevant R-phrases (chapter 3):

Highly flammable. 36 Irritating to eyes.

41 Risk of serious damage to eyes.

Vapours may cause drowsiness and dizziness.

Department issuing safety data sheet

UMCO Umwelt Consult GmbH

Georg-Wilhelm-Str. 183 b, D-21107 Hamburg

Tel.: +49 40 / 41 92 13 00 Fax: +49 40 / 41 92 13 57 e-mail: umco@umco.de

This information is based on our present state of knowledge. However, it should not constitute a guarantee for any specific product properties and shall not establish a legally valid relationship.