

## Electronic transformers

**Type: EST70/12.480 240V 50/60Hz**

**Item number: 176497 FP**

**LiteLine**

Casing : Heat resistant polyamide  
 Max. permitted casing temperature: 85°C  
 Output voltage Secondary: 11,5 V  
 Mains frequency: 50-60 Hz  
 Power factor: 0,98  
 Efficiency: 95%  
 Nominal current: 0,29 A  
 Screw terminals: 2,5 mm<sup>2</sup>

### With 1.5 metre flex and plug

Output:	70VA
Main voltage AC:	240V
Version:	Compact plastic casing LiteLine
Dimming:	Phase-cutting trailing-edge and leading-edge dimmer
Kind of connection:	2
Protection class:	For luminaires of protection class II
Width B:	37mm
Height:	28mm
Length:	128mm
Fixing centre:	117mm
Max. ambient temperature:	45 <sup>0</sup> C

Unit: 36 pcs.

Overtemperature protection, overload protection and protection against short circuit over thermal cut-out with automatic restart

EN 61046 (Safety)  
 EN 61047 (Working method)  
 EN 61000-3-2 (Mains harmonics)  
 EN 55015 (Radio-frequency interference suppression)  
 EN 61547 (EMV Immunity to interference)

