

# Wiha Torque Blades.

## Interchangeable Blades.

### Interchangeable Blade for Slotted Screws.

Blade High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Colour-coding: grey.

Standards: Tip DIN 5264, ISO 2380.

Application: For applications where recommended torque settings are important.

Use in combination with a Wiha torque handle.

| Order-No. | Colour-coding | ⊖;   | <b>D</b> : | 61 | =   | Nm max. |   |                 |
|-----------|---------------|------|------------|----|-----|---------|---|-----------------|
| 26227 3   |               | 0.25 | 1.5        | 4  | 175 | 0.15    | 1 | TENESTE SERVICE |
| 26228 0   |               | 0.4  | 2.0        | 4  | 175 | 0.4     | 1 |                 |
| 26151 1   |               | 0.4  | 2.5        | 4  | 175 | 0.4     | 1 |                 |
| 26277 8   |               | 0.5  | 3.0        | 4  | 175 | 0.6     | 1 | 443-1601        |
| 26278 5   |               | 0.6  | 3.5        | 4  | 175 | 1.1     | 1 | 663-1613        |
| 26279 2   |               | 0.8  | 4.0        | 4  | 175 | 2.5     | 1 | 643-1625        |

### Interchangeable Blades.



# Interchangeable Blade for TORX® Screws.

Blade High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Colour-coding: dark green.

Application: For applications where recommended torque settings are important.

Use in combination with a Wiha torque handle.

| Order-No.      | Colour-coding |     | - 1 | =   | Nm max. |            |
|----------------|---------------|-----|-----|-----|---------|------------|
| <b>26158</b> 0 |               | T5  | 4   | 175 | 0.4     | 1 643-1698 |
| 26064 4        |               | T6  | 4   | 175 | 0.6     | 1 663-1704 |
| 26065 1        |               | T7  | 4   | 175 | 0.9     | 1663-1716  |
| 26066 8        |               | T8  | 4   | 175 | 1.3     | 1663-1728  |
| <b>26059</b> 0 | TO HE BUT     | T9  | 4   | 175 | 2.5     | 1 463-1739 |
| <b>26067</b> 5 |               | T10 | 4   | 175 | 3.8     | 1 443-174  |
| <b>26068</b> 2 | BALLEY I      | T15 | 4   | 175 | 5.5     | 1 443-1753 |
| 26069 9        |               | T20 | 4   | 175 | 8.0     | 1 443-1765 |
| <b>26070</b> 5 | THE SAME      | T25 | 4   | 175 | 8.0     | 1 663-1747 |



#### 2859 Interchangeable Blade for Phillips Screws.

High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Colour-coding: dark blue.

Standards: Tip DIN ISO 8764-1.

Application: For applications where recommended torque settings are important.

Use in combination with a Wiha torque handle.

| Order-No.      | Colour-coding | <del>0</del> | 0: | =   | Nm max. |   | STOCKED BETTER SEASON STOCKED AND AND AND AND |
|----------------|---------------|--------------|----|-----|---------|---|-----------------------------------------------|
| <b>26199</b> 3 |               | PH 000       | 4  | 175 | 0.4     | 1 | 443-1637                                      |
| 26196 2        |               | PH 00        | 4  | 175 | 0.4     |   | 443-1649                                      |
| 26197 9        |               | PH 0         | 4  | 175 | 0.9     |   | 443-1650                                      |
| 26058 3        |               | PH 1         | 4  | 175 | 3.8     |   | 443-1662                                      |
| 27079 7        | 150           | PH 2         | 4  | 175 | 5.5     | 1 |                                               |



## Interchangeable Blade for TORX PLUS® Screws.

Blade High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Colour-coding: light green.

Application: For applications where recommended torque settings are important.

Use in combination with a Wiha torque handle.

| Order-No.      | Colour-coding |      | •1 | =   | Nm max. | -    |  |
|----------------|---------------|------|----|-----|---------|------|--|
| 26159 7        |               | 5IP  | 4  | 175 | 0.5     | 11   |  |
| 26071 2        |               | 6IP  | 4  | 175 | 0.8     | 1    |  |
| <b>26152</b> 8 |               | 7IP  | 4  | 175 | 1.3     | 1    |  |
| 26072 9        |               | 8IP  | 4  | 175 | 2.0     | 1    |  |
| <b>26154</b> 2 |               | 9IP  | 4  | 175 | 2.5     | 1111 |  |
| 26155 9        |               | 10IP | 4  | 175 | 3.8     | 1    |  |
| <b>26073</b> 6 |               | 15IP | 4  | 175 | 5.5     | 1    |  |
| <b>26156</b> 6 |               | 20IP | 4  | 175 | 8.0     | 1    |  |
| <b>26157</b> 3 |               | 25IP | 4  | 175 | 8.0     | 10.1 |  |



Blade

## Interchangeable Blade for Pozidriv Screws.

High quality chrome-vanadium-molybdenum steel, through

hardened, chrome-plated.

Wiha ChromTop finish on tip for a perfect fit every time.

Colour-coding: light blue.

Standards: Tip DIN ISO 8764-1.

Application: For applications where recommended torque settings are important.

Use in combination with a Wiha torque handle.

| Order-No.      | Colour-coding | •    | 0 | === | Nm max. |   |          |
|----------------|---------------|------|---|-----|---------|---|----------|
| <b>26198</b> 6 | ΔD.           | PZ 0 | 4 | 175 | 0.9     | 1 | 643-1674 |
| 26148 1        | V V           | PZ 1 | 4 | 175 | 3.8     | 1 | 443-1636 |
| <b>26889</b> 3 |               | PZ 2 | 4 | 175 | 5.5     | 1 |          |