

# 2N6394 Series

Preferred Device

## Silicon Controlled Rectifiers Reverse Blocking Thyristors

Designed primarily for half-wave ac control applications, such as motor controls, heating controls and power supplies.

### Features

- Glass Passivated Junctions with Center Gate Geometry for Greater Parameter Uniformity and Stability
- Small, Rugged, Thermowatt Construction for Low Thermal Resistance, High Heat Dissipation and Durability
- Blocking Voltage to 800 V
- Pb-Free Packages are Available\*

### MAXIMUM RATINGS<sup>†</sup> (T<sub>J</sub> = 25°C unless otherwise noted)

| Rating  | Symbol                                 | Value                   | Unit             |
|---|--|-------------------------|------------------|
| Peak Repetitive Off-State Voltage (Note 1)<br>(T <sub>J</sub> = -40 to 125°C, Sine Wave,<br>50 to 60 Hz, Gate Open) | V <sub>DRM</sub> ,<br>V <sub>RRM</sub> | 50<br>100<br>400<br>800 | V                |
| On-State RMS Current<br>(180° Conduction Angles; T <sub>C</sub> = 90°C)   | I <sub>T(RMS)</sub>                    | 12                      | A                |
| Peak Non-Repetitive Surge Current<br>(1/2 Cycle, Sine Wave, 60 Hz, T <sub>J</sub> = 90°C)                           | I <sub>TSM</sub>                       | 100                     | A                |
| Circuit Fusing (t = 8.3 ms)   | I <sup>2</sup> t                       | 40                      | A <sup>2</sup> s |
| Forward Peak Gate Power<br>(Pulse Width ≤ 1.0 μs, T <sub>C</sub> = 90°C)  | P <sub>GM</sub>                        | 20                      | W                |
| Forward Average Gate Power<br>(t = 8.3 ms, T <sub>C</sub> = 90°C)   | P <sub>G(AV)</sub>                     | 0.5                     | W                |
| Forward Peak Gate Current<br>(Pulse Width ≤ 1.0 μs, T <sub>C</sub> = 90°C)  | I <sub>GM</sub>                        | 2.0                     | A                |
| Operating Junction Temperature Range  | T <sub>J</sub>                         | -40 to +125             | °C               |
| Storage Temperature Range   | T <sub>stg</sub>                       | -40 to +150             | °C               |

### MAXIMUM RATINGS<sup>†</sup> (T<sub>J</sub> = 25°C unless otherwise noted)

| Rating   | Symbol           | Max | Unit |
|--|------------------|-----|------|
| Thermal Resistance, Junction-to-Case   | R <sub>θJC</sub> | 2.0 | °C/W |
| Maximum Lead Temperature for Soldering<br>Purposes 1/8" from Case for 10 Seconds | T <sub>L</sub>   | 260 | °C   |

<sup>†</sup>Indicates JEDEC Registered Data

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. V<sub>DRM</sub> and V<sub>RRM</sub> for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.




ON Semiconductor®

<http://onsemi.com>


**SCRs**  
**12 AMPERES RMS**  
**50 thru 800 VOLTS**



### MARKING DIAGRAM



**TO-220AB**  
**CASE 221A**  
**STYLE 3**



2N639x = Device Code  
x = 4, 5, 7, or 9  
G = Pb-Free Package  
A = Assembly Location  
Y = Year  
WW = Work Week

### PIN ASSIGNMENT

| Pin | Assignment |
|-----|------------|
| 1   | Cathode    |
| 2   | Anode      |
| 3   | Gate       |
| 4   | Anode      |

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 4 of this data sheet.

**Preferred** devices are recommended choices for future use and best overall value.

# 2N6394 Series

## ELECTRICAL CHARACTERISTICS (T<sub>C</sub> = 25°C unless otherwise noted.)

| Characteristic | Symbol | Min | Typ | Max | Unit |
|----------------|--------|-----|-----|-----|------|
|----------------|--------|-----|-----|-----|------|

### OFF CHARACTERISTICS

|  |                                     |                        |   |   |     |    |
|--|-------------------------------------|------------------------|---|---|-----|----|
| †Peak Repetitive Forward or Reverse Blocking Current<br>(V <sub>AK</sub> = Rated V <sub>DRM</sub> or V <sub>RDM</sub> , Gate Open) | I <sub>DRM</sub> , I <sub>RDM</sub> | T <sub>J</sub> = 25°C  | - | - | 10  | μA |
|  |                                     | T <sub>J</sub> = 125°C | - | - | 2.0 | mA |

### ON CHARACTERISTICS

|  |                 |     |          |     |    |
|--|-----------------|-----|----------|-----|----|
| †Peak Forward On-State Voltage (Note 2) (I <sub>TM</sub> = 24 A Peak)  | V <sub>TM</sub> | -   | 1.7      | 2.2 | V  |
| †Gate Trigger Current (Continuous dc) (V <sub>D</sub> = 12 Vdc, R <sub>L</sub> = 100 Ohms)   | I <sub>GT</sub> | -   | 5.0      | 30  | mA |
| †Gate Trigger Voltage (Continuous dc) (V <sub>D</sub> = 12 Vdc, R <sub>L</sub> = 100 Ohms)   | V <sub>GT</sub> | -   | 0.7      | 1.5 | V  |
| Gate Non-Trigger Voltage (V <sub>D</sub> = 12 Vdc, R <sub>L</sub> = 100 Ohms, T <sub>J</sub> = 125°C)  | V <sub>GD</sub> | 0.2 | -        | -   | V  |
| †Holding Current (V <sub>D</sub> = 12 Vdc, Initiating Current = 200 mA, Gate Open)   | I <sub>H</sub>  | -   | 6.0      | 50  | mA |
| Turn-On Time (I <sub>TM</sub> = 12 A, I <sub>GT</sub> = 40 mAdc, V <sub>D</sub> = Rated V <sub>DRM</sub> )   | t <sub>gt</sub> | -   | 1.0      | 2.0 | μs |
| Turn-Off Time (V <sub>D</sub> = Rated V <sub>DRM</sub> )<br>(I <sub>TM</sub> = 12 A, I <sub>R</sub> = 12 A)<br>(I <sub>TM</sub> = 12 A, I <sub>R</sub> = 12 A, T <sub>J</sub> = 125°C) | t <sub>q</sub>  | -   | 15<br>35 | -   | μs |

### DYNAMIC CHARACTERISTICS

|  |       |   |    |   |      |
|--|-------|---|----|---|------|
| Critical Rate-of-Rise of Off-State Voltage Exponential<br>(V <sub>D</sub> = Rated V <sub>DRM</sub> , T <sub>J</sub> = 125°C) | dv/dt | - | 50 | - | V/μs |
|--|-------|---|----|---|------|

†Indicates JEDEC Registered Data

2. Pulse Test: Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

## Voltage Current Characteristic of SCR

| Symbol           | Parameter                                 |
|------------------|---|
| V <sub>DRM</sub> | Peak Repetitive Off State Forward Voltage |
| I <sub>DRM</sub> | Peak Forward Blocking Current             |
| V <sub>RDM</sub> | Peak Repetitive Off State Reverse Voltage |
| I <sub>RDM</sub> | Peak Reverse Blocking Current             |
| V <sub>TM</sub>  | Peak On State Voltage                     |
| I <sub>H</sub>   | Holding Current                           |





Figure 1. Current Derating




Figure 2. Maximum On-State Power Dissipation

# 2N6394 Series




Figure 3. On-State Characteristics




Figure 4. Maximum Non-Repetitive Surge Current




Figure 5. Thermal Response

# 2N6394 Series

## TYPICAL CHARACTERISTICS




Figure 6. Typical Gate Trigger Current versus Pulse Width




Figure 7. Typical Gate Trigger Current versus Temperature




Figure 8. Typical Gate Trigger Voltage versus Temperature




Figure 9. Typical Holding Current versus Temperature

## ORDERING INFORMATION


| Device  | Package               | Shipping**       |
|---------|-----------------------|------------------|
| 2N6394  | TO-220AB              | 500 Units / Bulk |
| 2N6394G | TO-220AB<br>(Pb-Free) | 500 Units / Bulk |
| 2N6395  | TO-220AB              | 500 Units / Bulk |
| 2N6395G | TO-220AB<br>(Pb-Free) | 500 Units / Bulk |
| 2N6397  | TO-220AB              | 500 Units / Bulk |
| 2N6397G | TO-220AB<br>(Pb-Free) | 500 Units / Bulk |
| 2N6399  | TO-220AB              | 500 Units / Bulk |
| 2N6399G | TO-220AB<br>(Pb-Free) | 500 Units / Bulk |

\*\*For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# 2N6394 Series

## PACKAGE DIMENSIONS

TO-220AB  
CASE 221A-09  
ISSUE AD



NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. DIMENSION Z DEFINES A ZONE WHERE ALL BODY AND LEAD IRREGULARITIES ARE ALLOWED.

| DIM | INCHES |       | MILLIMETERS |       |
|-----|--------|-------|-------------|-------|
|     | MIN    | MAX   | MIN         | MAX   |
| A   | 0.570  | 0.620 | 14.48       | 15.75 |
| B   | 0.380  | 0.405 | 9.66        | 10.28 |
| C   | 0.160  | 0.190 | 4.07        | 4.82  |
| D   | 0.025  | 0.035 | 0.64        | 0.88  |
| F   | 0.142  | 0.147 | 3.61        | 3.73  |
| G   | 0.095  | 0.105 | 2.42        | 2.66  |
| H   | 0.110  | 0.155 | 2.80        | 3.93  |
| J   | 0.018  | 0.025 | 0.46        | 0.64  |
| K   | 0.500  | 0.562 | 12.70       | 14.27 |
| L   | 0.045  | 0.060 | 1.15        | 1.52  |
| N   | 0.190  | 0.210 | 4.83        | 5.33  |
| Q   | 0.100  | 0.120 | 2.54        | 3.04  |
| R   | 0.080  | 0.110 | 2.04        | 2.79  |
| S   | 0.045  | 0.055 | 1.15        | 1.39  |
| T   | 0.235  | 0.255 | 5.97        | 6.47  |
| U   | 0.000  | 0.050 | 0.00        | 1.27  |
| V   | 0.045  | ---   | 1.15        | ---   |
| Z   | ---    | 0.080 | ---         | 2.04  |

STYLE 3:

- PIN 1. CATHODE
2. ANODE
3. GATE
4. ANODE

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

### PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT:**  
Literature Distribution Center for ON Semiconductor  
P.O. Box 5163, Denver, Colorado 80217 USA  
**Phone:** 303-675-2175 or 800-344-3860 Toll Free USA/Canada  
**Fax:** 303-675-2176 or 800-344-3867 Toll Free USA/Canada  
**Email:** orderlit@onsemi.com

**N. American Technical Support:** 800-282-9855 Toll Free  
USA/Canada  
**Europe, Middle East and Africa Technical Support:**  
Phone: 421 33 790 2910  
**Japan Customer Focus Center**  
Phone: 81-3-5773-3850

**ON Semiconductor Website:** [www.onsemi.com](http://www.onsemi.com)  
**Order Literature:** <http://www.onsemi.com/orderlit>

For additional information, please contact your local Sales Representative