


Accessory

Miscellaneous

Lead free solder



Order No.	Description
	Lead Free Solder Wire
	Weller lead free solder wire for hand soldering application. The wire is save packed in a ESD safe handy red.
005 13 822 99	Ø 0,5 mm SN 96,5 AG3,0CU-0,5 F3L1, 4,0 m
005 13 832 99	Ø 1,0 mm SN 96,5 AG3,0CU-0,5 F3L1, 1,5 m



Order No.	Model	Description
005 13 031 99		Tip Activator
		The Weller Tip Activator for regeneration of oxidzed tips works fast and easy with low temperature. The Tip Activator is environmentally safe and contains no halides, lead, rosin or residue. Regular us will prolong the life time o the tips. Packaging unit 6 pcs.



Order No.	Model	Description
005 13 030 99		Antiblock Paste
		The Weller Antiblock paste is to prevent screwed in desoldering nozzles (e.g. DS 80) seizing due to oxidation or heat. Regular use will ensure easy tip exchange. Content 10 g.



Order No.	Model	Description
		Desoldering Wires
		The desoldering wire consists of a coper net with flux F-SW32. The special surface treatment allows efficient solder removal.
005 13 010 99		Desoldering wire 1,6 m coil, width 1,5 mm
005 13 011 99		Desoldering wire 1,6 m coil, width 2 mm
005 13 012 99		Desoldering wire 1,6 m coil, width 2,5 mm
005 13 028 99		Desoldering wire 15 m coil, width 2,5 mm
005 13 026 99		Desoldering wire 30 m coil, width 1,5 mm
005 13 027 99		Desoldering wire 30 m coil, width 2 mm



Order No.	Model	Description
005 13 016 99		Flux Set
		Liquid flux with brush, 100 ml, type 1.1.3.A (F-SW32), EN29 454. Remaining flux is not corrosive.



Order No.	Model	Description
005 33 525 99		Flux Pen
		For easy and exact application of flux, eliminating the mess from flux bottles. The spring loaded tip dispenses just the right amount of flux to the soldering joint. Body and function like a text marker. Content 10 cm3, Halogen-free, not refillable. Flux type 1.1.3.A (F-SW32), EN29 454.