

## Label Remover

Product Code: LRM

### PRODUCT DESCRIPTION

**Label Remover** has been specially formulated for the quick and efficient removal of paper based pressure sensitive adhesive labels. **LRM** is 100% Ozone Friendly.

### PRODUCT USE

For the removal of pressure sensitive adhesive labels from a variety of surfaces. Product contains combustible solvent so do not spray onto live electrical equipment or other sources of ignition.

Spray or wipe on, leave in contact for 5 minutes and then peel off label. Wipe surface clean.

### FEATURES

- \* Non-CFC, non-halogenated solvent which will not attack Ozone Layer.
- \* Allows label to be simply peeled off without leaving adhesive residue or scratching surface.
- \* Harmless to most plastics, rubbers, elastomers, and surface coatings when used as directed. Test sensitive plastics on a small area first, and do not use on polystyrene.
- \* CO<sub>2</sub> propelled aerosol version available containing 20% more active cleaner, fitted with a 360° valve for use in any orientation.

### TYPICAL PROPERTIES

Specific Gravity @ 20°C:	0.830(LRM01L), 0.79(LRM200D)
Inhalation Toxicity:	300 ppm
Residue on Evaporation:	<1ppm

TECHNICAL  
DATA  
SHEET



### **Copyright Electrolube 2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## Label Remover – Page 2

### PACKAGING

12ml Pen (Pack of 5 Pens)  
200ml Aerosol  
200ml Aerosol with Brush  
1 Litre Bulk

### ORDER CODE

LRM12P  
LRM200D  
LRM200DB  
LRM01L

**NATO Stock no (LRM200D): 8010-99-810-4705**

### TECHNICAL DATA SHEET



### Copyright Electrolube 2003

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

