



## SMD Super Bright LED

## **OVS-30 Series**

## Features:

- Standard PLCC-4 Package
- High Reliability LED Package
- Super Wide Viewing Angle
- Note: Electrical connections for all cathodes recommended





## Maximum Ratings at Ta=25℃

Reverse Voltage (<100 $\mu$ A)	5.0V
D.C. Forward Current	30mA
Pulse Current (Pulse Width of 0.1ms, 1/10 Duty Cycle)	100mA
Operating Temperature Range	25 to +85°C
Storage Temperature Range	40 to +100°C
Soldering Temperature Dip Soldering	260°C for 5 secs
Soldering Temperature Hand Soldering	350°C for 3 secs

	Viewing
Ant Part No. Material Emitted Colour Brightness Lens Colour Wavelength at 20mA at 20mA int. typ. min. typ.	Angle 2 <del>0</del> <sup>1/2</sup> (deg

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Famell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the pioducts to which it relates. No licence of any intellectual poperty rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, a ny error in or omission from it or for any use made of it. Users of this data sheets here inducts to themselves the Information and the suitability of the products for their purposes and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2008.

http://www.farnell.com http://www.newark.com http://www.cpc.co.uk

