

VR1129 RG316/U

DATE: 14/11/06 ORIGINATOR: A.J.R. CHECKED:

## **SPECIFICATION DATA SHEET**

CABLE TYPE RG 316/U RADIO FREQUENCY, COAXIAL, 50 OHM.

GENERAL DESCRIPTION SPCCS CONDUCTOR, PTFE DIELECTRIC, SPCW

BRAID, FEP SHEATH.

**RELEVANT STANDARDS** IN ACCORDANCE WITH MIL-C-17/172

COMPONENT	MATERIAL BREAKDOWN	DIAMETER (nom) mm
Conductor	07/0.170mm SILVER PLATED COPPER CLAD STEEL (Tensile Strength: 50 Klbf/inch² min, Elongation: 10% min	0.51 n)
Dielectric	EXTRUDED PTFE OF NOMINAL WALL 0.51mm (NATURAL)	1.52
Screen	0.102mm SPCW OF 95.2% NOMINAL COVERAGE	1.97
Jacket	EXTRUDED FEP OF NOMINAL WALL 0.26mm (TRANSLUCENT BROWN)	2.49

## CABLE CHARACTERISTICS

CONTINUOUS WORKING VOLTAGE: 900 V rms MAXIMUM

TEMPERATURE RATING: -55° to +200°C

DIMENSIONS: 2.39mm MINIMUM, 2.59mm MAXIMUM

WEIGHT: 14.67 KG/KM NOMINAL

ELECTRICAL CHARACTERISTICS: CONDUCTOR RESISTANCE: 276 OHMS/KM MAXIMUM

IMPEDANCE:  $50 \pm 2$  OHMS

CAPACITANCE: 105 pF/M MAXIMUM

ATTENUATION: 37.0 dB/100M NOMINAL @ 100 MHz

47.0 dB/100M NOMINAL @ 200 MHz 55.0 dB/100M NOMINAL @ 400 MHz 68.9 dB/100M MAXIMUM @ 400 MHz 102 dB/100M NOMINAL @ 1000 MHz

VELOCITY OF PROPAGATION: 69.5% NOMINAL

Information in this publication and otherwise supplied to users is based on our general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of products, no warranty is given nor is implied with respect to such information. Users should make their own enquiries to determine the suitability of products for any particular use. Freedom under patents, copyright and registered designs cannot be assumed. This design may be subject to change without notification – please check this data sheet is still correct.