

PRODUCT SPECIFICATION

GP PowerBank M510 Model: GPPB510

Revision History

Revision	Date	Initiator	Reason for Change	
00	1 March 2007	Natalie Chow	New release	

Prepared By	Approved By
Natalie Chow	Iris Lai
Date: 1 Mar 07	Date: 1 Mar 07

GPI International Limited

Gold Peak Building, 8/F, 30 Kwai Wing Road, Kwai Chung, New Territories, Hong Kong. Tel: (852) 2484 3333 Fax: (852) 24805912 Email: gpii@goldpeak.com Website: http://www.gpbatteries.com.hk

Member Gold Peak Group Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.



Product Specification

Model No.: GPPB510



Unit:mm

Description	:	NiMH Battery Charger (Plug-in type with detachable travel plugs)				
Input Voltage	:	AC 100-240V 50/60Hz				
Input Power	:	15W max				
Application	:	For charging 1 to 4 pcs of NiMH AA or AAA batteries				
Output Voltage	:	8V DC				
Charging Current	:	: AA/AAA 600mA ± 100mA				
Trickle Charge Current	:	AA/AAA 20mA – 60mA				
Charging Time	:	Size AA				
		Battery 1300mAh 1600mAh 1800mAh 2000series 2100series 2300series 2500series 2700series				
		Min 155 190 215 235 245 270 295 310				
		Size AAA Battery 600mAh 650mAh 700mAh 750mAh 800mAh 850mAh 950series 1000series 1100series				
		Min 60 65 70 75 90 100 110 120 130				
Termination Method	:	$-\Delta V$ and safety timer				
MTBF	:	30000 hours (at ambient temperature 25°C)				
Operating Temperature	:	0°C to 40°C				
Storage Temperature	:	-20°C to 60°C				
Charge Indicator		: 3 x Color LED (BLUE for power on; FLASHING GREEN for charging in progress;				
		GREEN for fully charged; RED for primary battery detected or bad battery				
		contacted)				
Dimensions	:	84(L) x 35(W) x 40(T)				
Approval	:	GS, CE, UL				
Warranty Period	:	12 months from ex-factory date				

Member Gold Peak Group

Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.









- 3 hours to charge up 1 to 4 pcs NiMH AA or AAA batteries
- Ultra compact and lightweight
- Detachable adaptor plugs (US, BS & GS) for traveller convenience
- 3 color LED indicators
- Auto cut-off safety control by voltage and time to prevent overcharging
- Primary battery and bad contact detection
- AC100-240V worldwide use





GPI International Limited 8/F Gold Peak Building, 30 Kwai Wing Road, Kwai Chung, N.Y., Hong Kong. Tel: (852) 2484 3333 Fax: (852) 2480 5912 E-mail address: gpii@goldpeak.com Website: www.gpbatteries.com.hk