Printing date 03.07.2008 V - 5 Revision: 03.07.2008

1 Identification of substance:

· Product details:

· Trade name: Cramolin Contaclean

· Article number: 101 Aerosol

· Application of the substance / the preparation:

Oil based Powerful Contact Cleaner dissolving Oxide and Sulphide Layers.

· Manufacturer/Supplier:

Rivelec

1. Rue des Entrepreneurs

F-78540 Vernouillet

Tel: +33 1 39716363 Fax: +33 1 39716400

· Informing department: Product safety department

Emergency information:

Rivelec

Tel: +33 1 39716363

2 Hazards identification

· Hazard designation:







Xi Irritant

F Highly flammable

N Dangerous for the environment

· Information pertaining to particular dangers for man and environment

The marking is valid for all pressurized container up to 50ml carrying capacity.

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

R 11 Highly flammable.

R 36/38 Irritating to eyes and skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Do not pierce or burn, even after use.

84.3 % by mass of the contents are flammable

Keep out of the reach of children

· Classification system

The classification is in line with current EC lists. It is expanded, however, by information from technical literature and by information furnished by supplier companies.

3 Composition/information on ingredients

- · Chemical characterization
- · Description: Active substance with propellant.

(Contd. on page 2)

Printing date 03.07.2008 V - 5 Revision: 03.07.2008

Trade name: Cramolin Contaclean

			(Contd. of page 1)	
· components:				
CAS: 107-83-5 EINECS: 203-523-4	Isohexan	X Xn, X Xi, F, N; R 11-38-51/53-65-67	50-100%	
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol	Xi, F; R 11-36-67	25-<50%	
· Regulation (EC) No 648/2004 on detergents / Labelling for contents				
aliphatic hydrocarbor	าร		≥ 30%	

4 First aid measures

- · General information Instantly remove any clothing soiled by the product.
- · After inhalation

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness bring patient into stable side position for transport.

· Additional information For the wording of the listed risk phrases refer to section 16.

· After skin contact

Instantly wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact

Rinse opened eye for several minutes under running water. Then consult doctor.

After swallowing

Do not induce vomiting; instantly call for medical help.

A person vomiting while lying on their back should be turned onto their side.

5 Fire fighting measures

· Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fire with alcohol-resistant foam.

· For safety reasons unsuitable extinguishing agents

Water.

Water with a full water jet.

· Special hazards caused by the material, its products of combustion or resulting gases:

Formation of toxic gases is possible during heating or in case of fire.

Store in a cool place. Heat will increase pressure and may lead to the container exploding.

· Protective equipment:

Wear self-contained breathing apparatus.

Do not inhale explosion gases or combustion gases.

· Additional information Cool endangered containers with water spray jet.

6 Accidental release measures

· Person-related safety precautions:

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

Avoid contact with the eyes and skin.

· Measures for environmental protection:

Inform respective authorities in case product reaches water or sewage system.

(Contd. on page 3)

Printing date 03.07.2008 V - 5 Revision: 03.07.2008

Trade name: Cramolin Contaclean

(Contd. of page 2)

Do not allow to enter drainage system, surface or ground water.

· Measures for cleaning/collecting:

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Absorb liquid components with liquid-binding material.

Dispose of the material collected according to regulations.

· Additional information: See Section 7 for information on safe handling

7 Handling and storage

- · Handling
- · Information for safe handling:

Store in cool, dry place in tightly closed containers.

Ensure good ventilation/exhaustion at the workplace.

· Information about protection against explosions and fires:

Do not spray on flames or red-hot objects.

Beware: Container is pressurized. Keep away from direct sun exposure and temperatures over 50°C. Do not open by force or throw into fire even after use.

- Storage
- · Requirements to be met by storerooms and containers:

Store in cool location.

Store only in the original container.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed containers.

Store in a cool place. Heat will increase pressure and may lead to the container exploding.

8 Exposure controls and personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Components with limit values that require monitoring at the workplace:				
107-83-5 Isohexan (50-100%)				
TLV (European Union)	Long-term value: 700 mg/m³, 200 ppm			
67-63-0 propan-2-ol (25-<50%)				
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm			
8002-74-2 Paraffin waxes and Hydrocarbon waxes (2.5-<10%)				
WEL (Great Britain)	Short-term value: 6 mg/m³ Long-term value: 2 mg/m³			
124-38-9 carbon dioxide (2.5-<10%)				
WEL (Great Britain)	Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm			
IOELV (European Union)	Long-term value: 9000 mg/m³, 5000 ppm			

- · Additional information: The lists that were valid during the compilation were used as basis.
- · Personal protective equipment
- · General protective and hygienic measures

The usual precautionary measures should be adhered to general rules for handling chemicals.

(Contd. on page 4)

Printing date 03.07.2008 V - 5 Revision: 03.07.2008

Trade name: Cramolin Contaclean

(Contd. of page 3)

Keep away from foodstuffs, beverages and feed.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

- · Breathing equipment: Use breathing protection in case of insufficient ventilation.
- · Protection of hands:

Gloves made of Nitril.

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Tightly sealed safety glasses.

9 Physical and chemical properties:		
· General Information		
Form: Colour: Odour:	Aerosol Red Characteristic	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 		
· Flash point:	-26°C	
· Ignition temperature:	295°C	
· Self-inflammability:	Product is not self igniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/ steam mixtures is possible.	
· Critical values for explosion:		
Lower: Upper:	0.8 Vol % 12.0 Vol %	
· Vapour pressure at 20°C:	240 hPa	
· Density at 20°C	0.7 g/cm ³	
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix	

(Contd. on page 5)

Printing date 03.07.2008 V - 5 Revision: 03.07.2008

Trade name: Cramolin Contaclean

(Contd. of page 4)

· Solvent content:		
Organic solvents:	84.3 %	
VOC (EC)	30.4 %	
. Solids content:	65%	

10 Stability and reactivity

- · Thermal decomposition/ Conditions to be avoided:
 - No decomposition if used and stored according to specifications.
- · Dangerous reactions Danger of bursting
- · Dangerous products of decomposition: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values that are relevant for classification:					
107-83-5 I	107-83-5 Isohexan				
Oral	LD50	>2000 mg/kg (rat)			
Dermal	LD50	>2000 mg/kg (rat)			
Inhalative	LC50/4 h	>190 mg/l (rat)			
67-63-0 propan-2-ol					
Oral	LD50	4570 mg/kg (rat)			
Dermal	LD50	13400 mg/kg (kan)			
Inhalative	LC50/4 h	30 mg/l (rat)			

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritant effect.
- · Sensitisation: No sensitising effect known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information:

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Toxic for aquatic organisms (for not coated material, powder form)

Do not allow product to reach ground water, water bodies or sewage system.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

GB

Printing date 03.07.2008 V - 5 Revision: 03.07.2008

Trade name: Cramolin Contaclean

(Contd. of page 5)

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Hand over to disposers of hazardous waste.

Disposal must be made according to official regulations.

· European waste catalogue

16 05 04 gases in pressure containers (including halons) containing dangerous substances

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· ADR/RID-GGVS/E Class: 2 5F Gases.

Kemler Number: -UN-Number: 1950

· Packaging group: - . Label 2.1

· Designation of goods: 1950 AEROSOLS

Limited quantities (LQ)
 Transport category
 Tunnel restriction code

· Maritime transport IMDG:



IMDG Class: 2.1
UN Number: 1950
Label 2.1
Packaging group: EMS Number: F-D,S-U
Marine pollutant: No

· Correct technical name: AEROSOLS (HEXANES, ISOPROPANOL (ISOPROPYL ALCOHOL))

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 2.1

(Contd. on page 7)

Printing date 03.07.2008 V - 5 Revision: 03.07.2008

Trade name: Cramolin Contaclean

(Contd. of page 6)

UN/ID Number: 1950Label 2.1Packaging group: -

· Correct technical name: AEROSOLS, flammable (HEXANES, ISOPROPANOL (ISOPROPYL

ALCOHOL))

15 Regulatory information

· Designation according to EC guidelines:

The product has been classified and labelled in accordance with EC Directives and the Ordinance on Hazardous Materials (GefStoffV).

· Code letter and hazard designation of product:







Xi Irritant

F Highly flammable

N Dangerous for the environment

· Risk phrases:

11 Highly flammable.

36/38 Irritating to eyes and skin.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

67 Vapours may cause drowsiness and dizziness.

Safety phrases:

- 3/7 Keep container tightly closed in a cool place.
- 9 Keep container in a well-ventilated place.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe fumes/aerosol.
- 24/25 Avoid contact with skin and eyes.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 33 Take precautionary measures against static discharges.
- 37 Wear suitable gloves.
- 51 Use only in well-ventilated areas.
- 57 Use appropriate container to avoid environmental contamination.

· Special designation of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

84.3 % by mass of the contents are flammable

Keep out of the reach of children

- · National regulations
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.

GB -

Printing date 03.07.2008 V - 5 Revision: 03.07.2008

Trade name: Cramolin Contaclean

(Contd. of page 7)

16 Other information:

Information is based on our current knowledge but does not establish a promise of product characteristics and does not substantiate any contractual legal relationship. Drawing of back-up data file for:

MSDS - Service - Center gmbH. Materiel-Safety-Data-Sheet Alemannenstrasse 49 6830 Rankweil AUSTRIA

Tel.: +43-(0)5522-60067 Fax.: +43-(0)5522-41031 E-Mail: office@msds.at www.msds.at

· Relevant R-phrases

- 11 Highly flammable.
- 36 Irritating to eyes.
- 38 Irritating to skin.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.
- · Contact:

see page 1

see page 1

·* Data compared to the previous version altered. .

GB