

SAFETY DATA SHEET

RX774D/BK

Page 1 of 4

		$\mathbf{NA} / /$	4D/BK			
					Revision	
1. IDENTIFICATION OF T					Revision date	21-Nov-2
Product name						
Company	RX774D/BK Robnor Resins Ltd Hunts Rise South Marston Park Swindon Wiltshire SN3 4TE support@robnor.co.uk www.robnor.co.uk					
Telephone	+44 (0)1793	+44 (0)1793 823741				
Fax	+44 (0)1793	827033				
Emergency telephone number	+44 07831 1	30543				
2. COMPOSITION / INFO	RMATION ON IN	GREDIENTS				
Hazardous ingredients						
1,3-bis(2,3-Epoxypropoxy)butan Bisphenol A-(epichlorhydrin) (rea reaction product: bisphenol A-(e epoxy resin (number average m <700)	action product) pichlorhydrin);	Conc. 10 - 20% 1 - 10% 70 - 80%	CAS 2425-79-8 25068-38-6 25068-38-6	EINECS 219-371-7 500-033-5	Symbols/Risk phrase Xn; R20/21 Xi; R36/3 Xi; R36/37/38 R43 N; Xi;R36 Xi;R38 Xi;R43	8 R43 R51/53
3. HAZARDS IDENTIFICA	TION					
Main hazards	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.					
4. FIRST AID MEASURES	5					
Skin contact	Wash with soap and water. Seek medical attention if irritation or symptoms persist.					
Eye contact	Rinse immediately with plenty of water for 15 minutes holding the eyelids open.					
Inhalation	Move the exposed person to fresh air. Seek medical attention.					
Ingestion	Drink 1 to 2 glasses of water. DO NOT INDUCE VOMITING. Immediate medical attention is required. If unconscious place in the recovery position.					
5. FIRE FIGHTING MEAS	URES					
Extinguishing media	Water spray. Carbon dioxide (CO2) Alcohol resistant foam. Dry chemical. Do NOT use Water jet.					
	obnoxious and toxic fumes may be formed in fire conditions.					
Fire hazards	obnoxious ar		may be former			

RX774D/BK

Revision 0 Revision date 21-Nov-2006

6. ACCIDENTAL RELEASE	MEASURES	
Personal precautions	Wear suitable protective equipment. Ensure adequate ventilation of the working area. Surfaces contaminated with the product will become slippery.	
Environmental precautions	Do not let product contaminate subsoil. Do not flush into surface water. Do not allow product to enter drains.	
Clean up methods	Absorb with inert, absorbent material. Transfer to suitable, labelled containers for disposal.	
7. HANDLING AND STORA	GE	
Handling	Avoid contact with eyes and skin. Do not eat, drink or smoke in areas where this product is used or stored. Wear suitable protective equipment. Use in a well ventilated area. Take precautionary measures against static discharges. Open container carefully. Appropriate local exhaust ventilation is required.	
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Do not store with food, drink and animal feed stuffs	
8. EXPOSURE CONTROLS	/ PERSONAL PROTECTION	
Engineering measures	Ensure adequate ventilation of the working area.	
Respiratory protection	Wear: Suitable respiratory equipment.	
Hand protection	Chemical resistant gloves (plastic)	
Eye protection	Approved safety goggles. Face shield.	
Protective equipment	Wear protective clothing. Safety shoes.	
9. PHYSICAL AND CHEMIC	CAL PROPERTIES	
Description	Paste.	
Colour	Black.	
Odour	Slight.	
Boiling point	200°C	
Flash point	220°C	
10. STABILITY AND REACT	ΓΙVΙΤΥ	
Stability	Stable under normal conditions.	
Conditions to avoid	Heat, sparks and open flames.	
Materials to avoid	Strong acids and strong bases. Strong oxidising agents.	
Hazardous decomposition products	Carbon oxides.	
11. TOXICOLOGICAL INFO	RMATION	
Corrosivity	Irritating to eyes and skin.	
Sensitization	May cause sensitisation by skin contact.	
Repeated or prolonged exposure	Prolonged or repeated exposure may cause irritation to skin and mucous membranes.	
12. ECOLOGICAL INFORM	ATION	
Degradability	Not readily biodegradable.	

0

RX774D/BK

Revision

date 21-Nov-2006

with local and

		Revisi
		Revision da
13. DISPOSAL CONSIDE	RATIONS	
General information	Can be incinerated if in cor	mpliance with local and national regulations.
Disposal of packaging	Empty containers can be s national regulations.	ent to landfill after cleaning, if in compliance
14. TRANSPORT INFOR	MATION	
ADR/RID		
UN 3	3082	Packing group III
Class 9)	Hazard ID 90
Proper Shipping E	ENVIRONMENTALLY	
Name H	HAZARDOUS SUBSTANCE,	
L	IQUID, N.O.S.	
IMDG		
UN 3	3082	Packing group III
Class 9)	Marine pollutant .
EmS Code F	F-A S-F	
ΙΑΤΑ		

UN 3082 Class 9 Packing Instruction 914 (Cargo) Packing Instruction 914 (Passenger)

Packing group III Subsidiary risk -Maximum quantity 450 L

Maximum quantity 450 L

15. REGULATORY INFORMATION		
Symbols	Xi - Irritant; N - Dangerous for the environment	
Risk phrases	R36/38 - Irritating to eyes and skin.	
	R43 - May cause sensitisation by skin contact.	
	R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
Safety phrases	S24 - Avoid contact with skin.	
	S29 - Do not empty into drains.	
	S37 - Wear suitable gloves.	

RX774D/BK

Revision

(0
21-Nov-200	6

	Revision date 21-Nov-20			
16. OTHER INFORMATIC	DN			
Text of risk phrases in Section 2	R20/21 - Harmful by inhalation and in contact with skin. R36 - Irritating to eyes.			
	R36/37/38 - Irritating to eyes, respiratory system and skin. R36/38 - Irritating to eyes and skin. R38 - Irritating to skin.			
	R38 - Irritating to skin. R43 - May cause sensitisation by skin contact. R51/53 - Toxic to aquatic organisms, may cause long-term adverse effects in the			
General information	aquatic environment. IT SHOULD BE NOTED THAT THIS PRODUCT IS INTENDED FOR USE WITH A HARDENER DESIGNATED BY ROBNOR RESINS LTD. THE CORRESPONDING SAFETY DATA FOR THAT HARDENER MUST BE STUDIED ALONG WITH THE DATA ON THIS SHEET PRIOR TO USE. USING HARDENERS WHICH HAVE NOT BEEN SUPPLIED AND/OR RECOMMENDED BY ROBNOR RESINS LTD FOR USE WITH THIS PRODUCT IS POTENTIALLY HAZARDOUS AND SHOULD NOT BE CONTEMPLATED.			
	Safety instructions and operating procedures for specified tasks must be written, communicated and enforced. These will include:			
	**Provision of hazard information and training of personnel based on operating procedures and safety data sheets, together with instructions on how to avoid exposure.			
	**Assessment of the risk of exposure and contact after all reasonable practical steps have been taken to avoid exposure, selection of suitable personal protective equipme and implementation of an appropriate programme.			
	**Provision of facilities for washing, storage of clothing and skin care and promotion o their use.			
	**Close supervision to identify failure in the perfomance of process controls or in following operating instructions, the occurence of irritation and inadequate use of personal protective equipment. Assessment should also be made of the need for industrial personal hygiene and medical surveillance, and provision of appropriate services.			
	Occupational dermatitis contracted during exposure to resin systems is a reportable disease under Schedule 3 of the RIDDOR regulations (UK). Form F2508A available from the HSE should be used for such notification.			
	It is a statutory requirement that Medical Supervision is carried out when using product which can cause an identifiable disease, there is reasonable liklihood that the disease may occur under the particular conditions of work and there are valid techniques for detecting indications of the disease.			
	The Safety Data Sheet was compliled using information gathered concerning its individual components. No synergistic effects are known to us but we cannot exclude the existence of such effects.			
	If this product is to be machined in any way then the toxicological information in Secti 11 and the information concerning respiratory protection in Section 8 should be noted			