

DATE OF ISSUE : 2007. 07. 12

**SPECIFICATION**  
MODEL : SLSRGBW815TS

[Approved Rank :  $V_F(S)$ ,  $\lambda_D(A, B, C, D)$ ,  $I_V(S)$ ]

RGBW TOP VIEW

CUSTOMER : 대표 승인원

<b>SAMSUNG ELECTRO-MECHANICS</b>		
<b>DRAWN</b>	<b>CHECKED</b>	<b>APPROVED</b>

<b>CUSTOMER : 대표 승인원</b>		
<b>DRAWN</b>	<b>CHECKED</b>	<b>APPROVED</b>

*SAMSUNG ELECTRO-MECHANICS CO., LTD.*

314. MAETAN3-DONG, YEONGTONG-KU,  
SUWON-SI, GYUNGKI-DO, KOREA, 442-743

## Contents

1. Product outline-----	3
2. Absolute Maximum Rating-----	3
3. Characteristics -----	3
4. Typical Characteristic Graph -----	5
5. Color Mixing Characteristics -----	6
6. Outline Drawing and Dimension -----	7
7. Reliability Test Items and Conditions ---	8
8. Solder Conditions -----	9
9. Taping Dimension -----	10
10. Label Structure -----	11
11. Lot Number -----	11
12. Reel Packing Structure -----	12
13. Aluminum Vinyl Bag-----	13
14. Precaution for Use -----	14
15. Hazard Substance Analysis-----	16
16. Revision History -----	19

# 1. Product Outline

## 1) Feature

- . Lead Frame Type LED Package ( 5.2 \* 6.0 \* t 1.3mm )
- . Beam Angle (  $\Delta\theta$  : 120 ° )
- . AlGaInP, GaN/Al<sub>2</sub>O<sub>3</sub> Chip & Long Time Reliability

## 2) Applications

- . Indoor, Outdoor Display and etc.

# 2. Absolute Maximum Rating

Item	Symbol	Absolute Maximum Rating			Unit
		Red	Green	Blue	
Forward Current	I <sub>F</sub>	30	30	30	mA
Pulse Forward Current	I <sub>FP</sub>	100	100	100	mA
Reverse Voltage	V <sub>r</sub>	5	-	-	V
Reverse Current	I <sub>R</sub>	-	85	85	mA
Operating Temperature	T <sub>opr</sub>	-30 ~ 85			°C
Storage Temperature Range	T <sub>stg</sub>	-40 ~ 100			°C

-. I<sub>FP</sub> Conditions : Duty 1/10 Pulse Width 10msec

# 3. Characteristics

## Electrical properties

( Ta : 25°C )

Item	Symbol	Condition	Rank	Color	min.	Typ.	MAX.	Unit
Forward Voltage (*)	V <sub>F</sub>	I <sub>F</sub> = 20 mA	S	Red	1.8	2.1	2.6	V
				Green	2.9	3.2	3.7	
				Blue	2.9	3.2	3.6	
Reverse Current	I <sub>R</sub>	V <sub>R</sub> = 5V	-	R	-	-	100	μA
Reverse Voltage	V <sub>r</sub>	I <sub>R</sub> = 10mA	-	G, B	0.6	-	2.0	V

## Dominant Wavelength

( Ta : 25°C )

Item	Symbol	Condition	Rank	Color			Unit
				Red	Green	Blue	
Dominant Wavelength (*)	λ <sub>D</sub>	I <sub>F</sub> = 20 mA	A	619 ~ 627	523 ~ 528	460 ~ 466	nm
			B	619 ~ 627	523 ~ 528	466 ~ 472	
			C	619 ~ 627	528 ~ 533	460 ~ 466	
			D	619 ~ 627	528 ~ 533	466 ~ 472	

**Luminous Intensity**

( Ta : 25°C )

Item	Symbol	Condition	Rank	Color	min.	typ.	MAX.	Unit
Luminous Intensity (*)	$I_v$	$I_F = 20 \text{ mA}$	S	Red	550	700	880	mcd
				Green	1200	1400	1700	
				Blue	250	400	650	
		-		1900	2400	3050		
		$I_F = 60 \text{ mA}$ (R,G,B $I_F = 20 \text{ mA}$ )						

\* Tolerance :  $V_F$  ;  $\pm 0.1V$ ,  $\lambda_D$  ;  $\pm 2nm$ ,  $I_v$  ;  $\pm 10\%$ ,

\* Luminous intensity measuring equipment : CAS140 B

※ Approved Rank









Item	$V_F$	$\lambda_D$	$I_v$
Rank	S	A, B, C, D	S

\* Each reel contains only one of the A, B, C or D, a segment (1/4) of the  $\lambda_D$  rank.

# 4. Typical Characteristics Graph

( Ta : 25°C )

\* These graphs show typical values.



## 5. Color Mixing Characteristics


※ These graphs and data are example values.

Color Mixing Data :


Bias Current : Red 20mA, Green 20mA, Blue 10mA

Standard Rank	Color			CIE		IV
	Red	Green	Blue	x	y	
SAS	20mA	20mA	10mA	0.292	0.283	2.18
SBS				0.298	0.3167	2.30
SCS				0.294	0.280	2.20
SDS				0.30	0.316	2.29


Color Mixing Spectrum



Chromaticity Diagram




## 6. LED Package Outline Dimensions




Common Cathode




1. Tolerance is  $\pm 0.1\text{mm}$ .
2. Do not place pressure on the encapsulating resin ('A').
3. The maximum compressing force is 15N on the polymer ('B').



Circuit Diagram




Land Pattern



NUMBER	ITEM	MATERIAL
①	FRAME	Copper Frame(Silver Plated)
②	LED CHIP	AlGaInP, GaN/Al <sub>2</sub> O <sub>3</sub>
③	Zener Diode	Si
④	WIRE	Gold Wire
⑤	RESIN	Resin
⑥	PACKAGE	Heat-resistant Polymer

## 7. Reliability Test Items and Conditions

### 1) Test Items and Results

Test Item	Test Conditions	Test Hours/Cycles	Sample No
Room Temperature life test	25°C ±3°C, Red;DC30 mA, Green;DC30 mA, Blue;DC30 mA	500 h	50
High Temperature humidity life test	60°C ±3°C, 95%±2%RH, Red;DC18 mA, Green;DC18 mA, Blue;DC18 mA	500 h	50
High Temperature life test	85°C ±3°C, Red;DC9 mA, Green;DC9 mA, Blue;DC9 mA	500 h	50
Low Temperature life test	-30°C ±3°C, Red;DC30 mA, Green;DC30 mA, Blue;DC30 mA	500 h	50
Thermal Shock	-40°C ~ 100°C 0.5 h      0.5 h	100 cycles	22
High Temperature Storage	Ta=100°C ±3°C	500 h	22
Low Temperature Storage	Ta=-40°C ±3°C	500 h	22
High Temperature humidity Storage	60°C ±3°C, 95%±2%RH	500 h	50
Temperature humidity Cycle	25°C ~ 65°C ~ -10°C 24hrs/1cycle, 95%RH	10 cycles	22
Reflow Soldeing (Pb-Free)	Peak 260±5°C for 10sec, 220°C over time 60sec max	3 times	22
ESD(HBM)	 <p>-R1:10MΩ , R2:1.5KΩ , C:100pF</p>	5 times	5
On/Off test	50°C ±3°C, 95%±2%RH, On/2sec, Off/2sec Red;DC30 mA, Green;DC30 mA, Blue;DC30 mA	120h	50



## 2) Criteria for Judging the Damage


Item	Symbol	Test Condition	Limit	
			Min	Max
Forward Voltage	$V_F$	$I_F=20 \text{ mA}$	-	U.S.L.*1.2
Luminous Intensity	IV	$I_F=20 \text{ mA}$	L.S.L.*0.5	-

\* USL : Upper Standard Level    LSL : Lower Standard Level

## 8. Solder Conditions

### 1) Reflow Conditions ( Pb Free )


Reflow Frequency : 2 times max.



### 2) For Manual Soldering

Not more than 5 seconds @MAX $300^\circ\text{C}$ , under soldering iron.(one time only)

## 9. Taping Dimension



End


Start

More than 40 mm  
Unloaded tape

Mounted with  
Flash LED

More than (100~200)mm  
Unloaded tape


Leading part more than  
(200~400)mm



Tolerance  $\pm 0.2$ , Unit:mm

- (1) Quantity : The quantity/reel to be 1000pcs.
- (2) Cumulative Tolerance : Cumulative tolerance/10 pitches to be  $\pm 0.2$  mm
- (3) Adhesion Strength of Cover Tape : Adhesion strength to be 0.1–0.7N when the cover tape is turned off from the carrier tape at  $10^\circ$  angle to be the carrier tape.
- (4) Packaging : P/N, Manufacturing data code no. and quantity to be indicated on a damp proof package.

## 10. Label Structure




### Rank Code

- Ⓐ : Forward Voltage( $V_F$ ) Rank (refer to page. 3)
- Ⓑ : Wavelength( $\lambda_D$ ) Rank (refer to page. 3)
- Ⓒ : Luminous Intensity( $I_v$ ) Rank (refer to page. 4)

## 11. Lot Number



The Lot number is composed of the following characters




- ◎◇◆□■△△△ / |▲▲▲ / 1000PCS
- : Production Site (S:SEMCO, G:Gosin China)
- ◎ : L (LED)
- ◇ : Product State (A:Normality, B: Bulk, C:First Production, R:reproduction, S:Sample)
- ◆ : Year (Q:2006, R:2007, S:2008...)
- : Month (1 ~ 9, A, B)
- : Day (1 ~ 9, A, B ~ V)
- △ : SEMCO. Product number (1 ~ 999)
- ▲ : Reel Number (1 ~ 999)

# 12. Reel Packing Structure

## Reel





## Aluminum Vinyl Bag




Material : Paper(SW3B(B))

TYPE	SIZE(mm)		
	a	b	c
7inch	245	220	182

### ① SIDE



# 13. Aluminum Vinyl Bag



**CAUTION**

This bag contains  
**MOISTURE SENSITIVE DEVICES**

**LEVEL**  
**2a**

1. Shelf life in sealed bag: 12 months at <math><40^{\circ}\text{C}</math> and <math><90\%</math> relative humidity (RH)
2. Peak package body temperature: 240 °C
3. After this bag is opened, devices that will be subjected to reflow solder or other high temperature processes must be:
  - a. Mounted within 672 hours at factory conditions of equal to or less than 30°C / 60% RH, or
  - b. Stored at <math><10\%</math> RH
4. Devices require bake, before mounting, if:
  - a. Humidity Indicator Card is > 65% when read at 23±5°C, or
  - b. 2a is not met.
5. If baking is required, devices must be baked for 1 hours at 60±5°C

Note: if device containers cannot be subjected to high temperature or shorter bake times are desired, reference IPC/JEDEC J-STD-033 for bake procedure,

Bag seal due date: \_\_\_\_\_  
(if blank, see code label)

Note: Level and body temperature by IPC/JEDEC J-STD-020

**SAS**

SLSRGBW815TS      SAS      01

|||||

GLAR94001 / 1001 / 1,000pcs

|||||



**주의 사항**


이 알루미늄 지퍼 백은 습기 및 정전기로부터 제품을 보호하기 위하여 제작되었습니다. 개봉 후에는 즉시 솔더 작업을 실시하는 것을 권장합니다.

습기 및 정전기로부터 제품을 보호 하기 위해서 개봉 후 사용하지 않는 자재는 본 팩에 넣어 보관 하시기 바랍니다. 사용하지 않는 자재를 본 팩에 넣을 때는 반드시 동봉된 드라이 팩과 함께 넣고 지퍼부분을 완전하게 밀봉하여 주시기 바랍니다.

**Important**

This Al Zipper bag is designed to protect the enclosed products from moisture and ESD. Once opened, the products should be soldered onto the printed circuit board immediately. When not in use, please do not leave the products unprotected by the Al Zipper Bag. To repack unused products., please ensure the zip-lock is completely sealed with the dry pack left inside.

## Silica gel & Humidity Indicator Card in Aluminum Vinyl Bag



## 14. Precaution for Use (취급상 주의사항)

- 1) For over-current-proof function, customers are recommended to apply resistors to prevent sudden change of the current caused by slight shift of the voltage.  
과전류 방지를 위해 전압의 미세한 이동에 의해 야기되는 전류의 순간 변화를 방지하기 위해 저항 등의 설치를 권장함.
- 2) This device should not be used in any type of fluid such as water, oil, organic solvent, etc. When washing is required, IPA is recommended to use.  
제품은 물, 오일, 유기물과 같은 액체 타입에서의 사용은 제한되며, 세정이 필요할 시에는 IPA 사용을 권장함.
- 3) When the LEDs illuminate, operating current should be decided after considering the ambient maximum temperature.  
LED의 발광 시, 동작 전류는 주변 최고온도를 고려하여 결정되어야 함.
- 4) LEDs must be stored in a clean environment.  
If the LEDs are to be stored for 3 months or more after being shipped from SEMCO, they should be packed by a sealed container with nitrogen gas injected.  
(Shelf life of sealed bags: 12 months, temp. 0~40°C, 20~70%RH)  
LED의 보관은 청정한 환경에서 보존되어야 하며, 만약 삼성전기로부터 공급받는 후 3개월 또는 그 이상 보관이 필요하다면 질소 가스를 동봉한 보존용기에 보관되어야 함.  
(보존 bag의 수명 : 12 개월, 보존 온도 0~40°C, 습도 20~70%RH)
- 5) After storage bag is open, device subjected to soldering, solder reflow, or other high temperature processes must be:  
보존 Bag이 개봉된 후에, 납땀이나 reflow등의 높은 온도에 노출되는 제품은 다음의 사항에 부합되어야 함.
  - a. Mounted within 168 hours (7 days) at an assembly line with a condition of no more than 30°C/60%RH,  
a. 제품은 30°C/60%RH보다 같거나 낮은 조립조건에서 168시간(7일)이내에 조립되어야 함.
  - b. Stored at <10% RH.  
b. 10% 이하의 상대습도에서 보관되어야 함.
- 6) Repack unused Products with anti-moisture packing, fold to close any opening and then store in a dry place.  
사용하지 않은 제품은 방습팩에 넣어 개봉 부위를 닫아서 다시 포장한 후, 건조한 장소에서 보관할 것을 권장함.

7) Devices require baking before mounting, if humidity card reading is  $>65\%$  at  $23\pm 5^{\circ}\text{C}$ .

만약 습도표시카드의 수치가  $23\pm 5^{\circ}\text{C}$ 에서  $65\%$  이상이라면, 제품 실장 전에 baking하여야 함.

8) Devices must be baked for 24hours at  $65\pm 5^{\circ}\text{C}$ , if baking is required.

만약 baking이 필요하다면, 제품은  $65\pm 5^{\circ}\text{C}$ 에서 24시간 정도 baking 되어야 함.

9) The LEDs are sensitive to the static electricity and surge. It is recommended to use a wrist band or anti-electrostatic glove when handling the LEDs.

LED는 정전기 및 서지에 민감한 제품이므로, LED 제품을 다룰 시에는 정전기 방지장갑이나 손목밴드를 사용하기를 권장함.

If voltage exceeding the absolute maximum rating is applied to LEDs, it may cause damage or even destruction to LED devices.

만약 절대 허용치를 초과하는 전압이 LED에 가해지면, LED 소자는 파괴되거나 손상될 수 있음.

Damaged LEDs may show some unusual characteristics such as increase in leak current, lowered turn-on voltage, or abnormal lighting of LEDs at low current.

손상된 제품은 누설전류의 증가, Turn on 전압의 저하, 저 전류에서의 점등불량 등의 이상 거동을 보일 수 있음.

# 15. Hazard Substance Analysis



**Test Report No. F690501/LF-CTSAYA07-08113**

Date: April 03, 2007

Page 1 of 3

To: **SAMSUNG ELECTRO-MECHANICS CO., LTD.**  
314, Maetan3-dong  
Yeongtong-gu  
Suwon-city  
GYEONGGI-DO 442-373  
Korea

The following merchandise was submitted and identified by the client as :

**Product Name** : 5252 Full Color LED  
**SGS File No.** : AYA07-08113  
**Received Date** : March 28, 2007  
**Test Performing Date** : March 29, 2007  
**Test Performed** : SGS Testing Korea tested the sample(s) selected by applicant with following results  
**Test Results** : For further details, please refer to following page(s)

Pluto Kim  
Monet Jeong  
Jully Oh  
Jerry Jung  
/Testing Person

SGS Testing Korea Co. Ltd.

Jeff Jang / Chemical Lab Mgr

This document is issued by the Company under its General Conditions of Service accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any other holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

SGS Testing Korea Co., Ltd. 322, The O valley, 555-9, Hoge-dong, Dongan-gu, Anyang-si, Gyeonggi-do, Korea 431-080  
t +82 (0)31 4608 000 f +82 (0)31 4608 059 www.sgslab.co.kr, www.kr.sgs.com/greenlab  
1002-2, Hwasan-ri, Onsan-eub, Uiju-gun, Ulsan, Korea 689-890 t +82 (0)52 239 6908-10 f +82 (0)52 239 6913





Test Report No. F890501LP-GTSAYA07-08113

Date: April 03, 2007

Page 2 of 3

Sample No. : AYA07-08113.001  
 Sample Description : S2S2 Full Color LED  
 Item No./Part No. : N/A

**Heavy Metals**

Test Item	Unit	Test Method	MDL	Results
Cadmium (Cd)	mg/kg	US EPA 3050B(1995), US EPA 8010B(1995), ICP	0.5	N.D.
Lead (Pb)	mg/kg	US EPA 3050B(1995), US EPA 8010B(1995), ICP	5	N.D.
Mercury (Hg)	mg/kg	US EPA 3052(1995), US EPA 8010B(1995), ICP	2	N.D.
Hexavalent Chromium (Cr VI)	mg/kg	US EPA 3060A(1995), US EPA 7195A(1992), UV	1	N.D.

**Flame Retardants-PPRS/BBR/Es**

Test Item	Unit	Test Method	MDL	Results
Monobromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Dibromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Tri bromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Tetrabromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Pentabromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Hexabromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Heptabromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Octabromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Nonabromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Decabromodiphenyl	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Monobromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Dibromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Tri bromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Tetrabromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Pentabromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Hexabromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Heptabromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Octabromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Nonabromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.
Decabromodiphenyl ether	mg/kg	US EPA 3540C, GC/MS	5	N.D.

- NOTE: (1) N.D. = Not detected.(<MDL)  
 (2) ppm = mg/kg  
 (3) MDL = Method Detection Limit  
 (4) - = No regulation  
 (5) \*\* = Qualitative analysis (No Unit)  
 (6) Negative = Undetectable / Positive = Detectable

This document is issued by the Company under its General Conditions of Service available at [http://www.sgs.com/terms\\_and\\_conditions](http://www.sgs.com/terms_and_conditions). His attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any other holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Picture of Sample as Received:

Sample Color :

White



\*\*\* End \*\*\*

- NOTE: (1) N.D. = Not detected (-MDL)  
(2) ppm = mg/kg  
(3) MDL = Method Detection Limit  
(4) - = No regulation  
(5) \*\* = Qualitative analysis (No Unit)  
(6) Negative = Undetectable / Positive = Detectable

This document is issued by the Company under its General Conditions of Service accessible at [http://www.sgs.com/terms\\_and\\_conditions](http://www.sgs.com/terms_and_conditions). His attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any other holder of this document is advised that information contained herein reflects the Company's findings at the date of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

